

AIRLITEC Sarl 88, rue Jean Jaures 80470 Dreuil Les Amiens France
 TEL.: +33 (0) 3 22 54 83 47 FAX: +33 (0) 3 22 54 83 29
 Siret: 514 488 105 00016 Code APE: 4669B

To : Murat Bayram
 Electrical-Electronics Engineer

DATE: 21-avr-10

HTG /ENTEK TEKNIK
 Att.: Maltepe, Istanbul/Turkey
 Tel.: Tel:+90 216-4598660
 Fax: Fax: +90 216-4598370
 Email: <http://www.htgrup.com>
 Web:

Your reference No. :
 Our Quotation No. : A20100030
 Contact person : Mr. Regis Houllier
 Tel: +33 3 22 54 83 47
 Fax: +33 3 22 54 83 29
 Email: regis.houllier@airlitec.com
 Web: www.airlitec.com

ITEM	MODEL	DESCRIPTION	Q'TY	U/PRICE (EURO)	AMOUNT (EURO)	LEAD TIME (Weeks)
15	MAG5722-5LA61-2CB0 B11	Mag-flux Flowsensor A - neoprene soft rub design: Remote nominal diameter / flange type: flange DIN 2501 PN 16 DN 150 Electrode material: Platinum protection rings/protection washers: with cable gland entires: M16x1,5 degree of protection: IP 67 / NEMA5 output/communication: 4-20 mA with HART protocol power supply: AC 110-230 V operating and display panel: with Tag plate: FT50307 with Grounding ring	1	2 165,00	2 165,00	6
	Cable	20 meters	1	124,00	124,00	6
16	83F80-BD2CAAADAAA5	Mass Flowmeter DN80 Material tube: Alloy C-22 PN40 Mass flow: 0,1% Remote version with 20meters cable	1	14 995,00	14 995,00	6
17	MAG5712-5NA61-2CB0 B11	Mag-flux Flowsensor A - neoprene soft rub design: Remote nominal diameter / flange type: flange DIN 2501 PN 10 DN 250 Electrode material: Platinum protection rings/protection washers: with cable gland entires: M16x1,5 degree of protection: IP 67 / NEMA5 output/communication: 4-20 mA with HART protocol power supply: AC 110-230 V operating and display panel: with Tag plate: FT50305 with Grounding ring	1	2 684,00	2 684,00	6
	Cable	20 meters	1	124,00	124,00	6
18	MAG5722-5LA61-2CB0 B11	Mag-flux Flowsensor A - neoprene soft rub design: Remote nominal diameter / flange type: flange DIN 2501 PN 16 DN 150 Electrode material: Platinum protection rings/protection washers: with cable gland entires: M16x1,5 degree of protection: IP 67 / NEMA5 output/communication: 4-20 mA with HART protocol power supply: AC 110-230 V operating and display panel: with Tag plate: FT50306	1	2 165,00	2 165,00	6

		with Grounding ring				
	Cable	20 meters	1	124,00	124,00	6
19	MAG5704-1HA20-2CB0 B11	Mag-flux Flowsensor A - PTFE design: Remote nominal diameter / flange type: flange DIN 2501 PN 40 DN 80 Electrode material: Hastelloy C4 protection rings/protection washers: with cable gland entires: M16x1,5 degree of protection: IP 67 / NEMA5 output/communication: 4-20 mA with HART protocol power supply: AC 110-230 V operating and display panel: with Tag plate: FT51302	1	997,00	997,00	6
	Cable	20 meters	1	124,00	124,00	6
38	7ME5822-2JT00-0AA0	FVA250 Variable area meter DN65 Flange DIN 2501 PN16 Measuring range: 2500 to 25000l/h	1	575,00	575,00	6
79	MAG5702-1HA60-2CB0 B11	Mag-flux Flowsensor A - PTFE design: Remote nominal diameter / flange type: flange DIN 2501 PN 16 DN 80 Electrode material: Platinum protection rings/protection washers: with cable gland entires: M16x1,5 degree of protection: IP 67 / NEMA5 output/communication: 4-20 mA with HART protocol power supply: AC 110-230 V operating and display panel: with Tag plate: FT51307	1	2 123,00	2 140,00	6
	Cable	20 meters	1	124,00	124,00	6

		Total	EURO	26 341,00
		Minimum Charge	EURO	0,00
		* Packing & Handling charges	EURO	0,00
		Freight Charge	EURO	
		Sub-total	EURO	26 341,00
		VAT 21%	EURO	
		Total	EURO	26 341,00

REMARKS:

* Lead time may be changed depending on the condition of the outstanding orders at our factory side.

TERMS and CONDITIONS:

Trade Terms: Ex- works

Payment Terms: Advance Payment

Minimum Order Amount: Euro 150 per order (Packing & Handling and Freight charges excluded).

Partial Shipment: Not allowed.

Shipping Route:

Validity: 60 days from quotation date.

Cancellation: Not allowed after your order is acknowledged.

(The Trade Terms are in accordance with Incoterms 2000.)