

AIRLITEC Sarl 88, rue Jean Jaures 80470 Dreuil Les Amiens France  
 TEL.: +33 (0) 3 22 54 83 47 FAX: +33 (0) 3 22 54 83 29  
 Siret: 514 488 105 00016 Code APE: 4669B

<b>To :</b> Eurotech International Adresse Postale : CS 80509 78108 SAINT-GERMAIN-EN-LAYE cedex Tel: +33 (0) 1 39 10 55 00 - Fax: +33 (0) 1 39 10 55 13	<b>DATE:</b> 26-janv-12
<b>Att.:</b> Mr Mohamed Echaïb <b>Tel.:</b> Tel: +33 (0) 1 39 10 55 17 <b>Fax:</b> Fax: +33 (0) 1 39 10 55 13 <b>Email:</b> Email: <a href="mailto:mechaib@eurotech-intl.com">mechaib@eurotech-intl.com</a> <b>Web:</b>	<b>Your reference No. :</b> 201201403 <b>Our Quotation No. :</b> A2012RH033 <b>Contact person :</b> Mr. Regis Houllier Tel: +33 3 22 54 83 47 Fax: +33 3 22 54 83 29 Email: <a href="mailto:regis.houllier@airlitec.com">regis.houllier@airlitec.com</a> Web: <a href="http://www.airlitec.com">www.airlitec.com</a>

ITEM	MODEL	DESCRIPTION	Q'TY	U/PRICE (EURO)	AMOUNT (EURO)	LEAD TIME (Weeks)
1	HM 013 E05.G.TC.10	Turbine Flow Meter measuring range:.... 8.5 to 85 lpm measuring medium:.... water linearity:.....±1.0% of act. val. repeatability:..... 0.1% pulses/litre:..... approx. 900 operating temp:..... 100 °C operating pressure: 100 bar connections:..... Ermeto nut m 20s (M 30 x 2) overall length:..... 84 mm	1	1 598,00	1 598,00	5
2	HM 019 E05.G.TC.10	Turbine Flow Meter measuring range:.... 15 to 150 lpm measuring medium:.... water linearity:.....±1.0% of act. val. repeatability:..... 0.1% pulses/litre:..... approx. 310 operating temp:..... 100 °C operating pressure: 100 bar connections:..... Ermeto nut m 25s (M 36 x 2) overall length:..... 107 mm	1	1 672,00	1 672,00	5
3	VTEK/P	Carrier-Frequency Pulseamplifier design:..... with integral pickup frequency range:.... 3 to 3,000 Hz outputs:..... frequency output 1) push pull active or 2) passive NPN/OC medium temp:..... -20 to +120 °C supply voltage:.... 7 to 29 V/DC electr. connection: 5-pin amphenolplug (T3362500)	1	295,00	295,00	5
4	Stecker 5plg. Typ 423 (PG 7)	AMP socket 5-pin (PG 7) type: 423 2 99-5114-00-05	1	20,00	20,00	5
5	IF 3	Inductive Pickup Coil for pulse amplifier VIEG version:..... single pickup coil output:..... Uss 0.5 to 500 mV output resistor:.... < 100 Ohm inductivity:..... < 25 mH fluid temperature:..-20 °C to +120 °C electr. connection: 3-pin amphenol plug	2	224,00	448,00	5
6	3-pin connector with strain relief	for IF* and IG* Series consisting of: - CVS 06A 10 SL-3S F5 - MS 3057-4A F5 + 3 Special Seal Gaskets	2	34,00	68,00	5

<b>Total</b>	EURO	4 101,00
<b>Minimum Charge</b>	EURO	0,00
<b>* Packing &amp; Handling charges</b>	EURO	0,00
<b>Freight Charge</b>	EURO	50,00
<b>Sub-total</b>	EURO	4 151,00
<b>VAT 19,6%</b>	EURO	813,60
<b>Total</b>	EURO	4 964,60

**REMARKS:**

\* Lead time may be changed depending on the condition of the outstanding orders at our factory side.

**TERMS and CONDITIONS:**

**Trade Terms:** Livré sur Brest  
**Payment Terms:** 30 days net  
**Minimum Order Amount:** Euro 150 per order (Packing & Handling and Freight charges excluded).  
**Partial Shipment:** Not allowed.  
**Validity:** 60 days from quotation date.  
**Cancellation:** Not allowed after your order is acknowledged.

(The Trade Terms are in accordance with Incoterms 2000.)

Regis Houllier  
 Director