

AIRLITEC Sarl 88, rue Jean Jaures 80470 Dreuil Les Amiens France
 TEL.: +33 (0) 3 22 54 83 47 FAX: +33 (0) 3 22 54 83 29
 Siret: 514 488 105 00016 Code APE: 4669B

A: ALTEN pour KREMLIN-REXSON
 150, Avenue de Stalingrad
 93 245 STAINS Cedex - France

DATE: 22-mars-12

Votre reference No. :
 Notre offre No. : A2012RH121
 Contact : Mr. Regis Houllier
 Tel: +33 3 22 54 83 47
 Fax: +33 3 22 54 83 29
 Email: regis.houllier@airlitec.com
 Web: www.airlitec.com

Att.: Christophe NEPERT
Tel.: Fax.: +33 (0) 1 49 40 25 12
Fax: Port.: +33 (0) 6 70 31 05 89
Email: e-mail: christophe.nepert.ext@kremlin-rexson.com
Web:

Item	Modèle	Description	Qté	Prix unit. (EURO)	Total (EURO)	Délais (semaines)
1	TCM 5500-AI-SHSS-CSDS	Coriolis Massflow meter	2	3 974,00	7 948,00	6-8
	C-Flow Transducer	Compact-Design measuring range:.... 79 to 5500 kg/h operating range:.... 120 to 1,782 kg/h * measuring medium:... mastic density:..... 1,100 kg/m ³ viscosity:..... 0.73 Pas operating temp:.... 20 to 35 °C (max. Medium temp. +100°C) operating pressure:. max. 180 bar connections:..... G ½" female thread p max. 350 bar Pressure drop:..... approx. 4 bar at 27 lpm & 0.73 Pas connections:..... flanges 1" ASA 1,500 lbs ANSI B 16.5 dimensions [w;h]:... 462 mm; 525 mm tube material:.....SS316L housing material:... SS304				
	C-Flow Transmitter	analog output 2 off:.. 4 to 20 mA free programmable:... for mass , volume flow, density or temperature pulse output 1 off:.. for mass- or volume flow status output 1 off:.. fault out info status input 1 off:.. configurable Interface:..... RS 485 LCD-display:..... graphic 32 x 132 pixel supply voltage:..... 24 VDC electr. connection:... screw terminals via 2 off ½" NPT cable glands housing:..... Aluminium diecast Weight:..... approx. 12 kg				

ALTERNATIVE

1	KCM 3000.CF-HD-RF.1/2".PN200	Coriolis Mass Flow Meter	2	3 570,00		3-4
	C-Flow Transducer	Compact-Design measuring range:.... 30 to 3,000 kg/h operating range:.... 120 to 1,782 kg/h * measuring medium:... mastic density:..... 1,100 kg/m ³ viscosity:..... 0.4 Pas operating temp:.... 20 to 35 °C (max. Medium temp. +125°C) operating pressure:. max. 180 bar connections:..... G ½" female thread				

p max. 200 bar
dimensions [w;h]:... 214 mm; 181.5 mm
tube material:..... CrNi steel SS316 Ti
housing material:... CrNi steel SS316 Ti

C-Flow Transmitter

analog output 2 off:.. 4 to 20 mA
free programmable:... for mass , volume flow, density or temperature
pulse output 1 off:.. for mass- or volume flow
status output 1 off:.. fault out info
status input 1 off:.. configurable
Interface:..... RS 485
LCD-display:..... graphic
32 x 132 pixel
supply voltage:..... 24 VDC
electr. connection:... screw terminals via 2 off ½" NPT
cable glands
housing:..... Aluminium diecast
weight:..... approx. 4.6 kg

	Total	EURO	7 948,00
	Charge minimale	EURO	0,00
	Extra charge et emballage	EURO	0,00
	Transport	EURO	
	Sous total	EURO	7 948,00
	TVA19,6%	EURO	1 557,81
	Total	EURO	9 505,81

REMARQUES:

* le délai peut varier en fonction du plan de charge de l'usine

Termes et Conditions de vente:

Conditions commerciales: ex work Bad Kötzing Allemagne

Conditions de paiement: 30 jours net

Charge minimale par commande: Euro 150 par commande (Extra charge, emballage et transport exclus).

Expédition partielle: Non autorisée.

Validité: 60 jours à partir de la date de l'offre

Annulation: Non autorisée après acceptation de la commande

(Conditions commerciales suivants Incoterms 2000.)

Regis Houllier
Directeur