

# Specification Sheet

<p>No.: 1 QTY: 1</p> <p>Tag no. 28-TV-014</p> <p>Service</p> <p><b>&lt; Specification &gt;</b></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 3 inch</p> <p>Port size 3 inch</p> <p>Rated Cv 120</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE FACE</p> <p>Flow characteristic %C</p> <p>Bonnet type FIN</p> <p>Actuator HA3D</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Push down to open)</p> <p>Gland packing TK397</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p><b>&lt; Accesories &gt;</b></p> <p>Positioner / Signal HTP-1D</p> <p>Exprosn-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><b>&lt;Option&gt;</b></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0202-050 Range ability: 50:1</p> <p><b>&lt;Finish&gt;</b></p> <p>Body: Silver</p> <p>Diaph. Case: Yellow</p> <p>Yoke: Yellow</p> <p>Paint Standard</p>																																																																				
<p><b>&lt;Operating condition&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: center;">Hot Oil</th> <th></th> <th style="text-align: center;">[ LIQUID ]</th> <th style="text-align: left;">UNIT</th> </tr> <tr> <th></th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th></th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td style="text-align: center;">46.2</td> <td></td> <td></td> <td>m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td style="text-align: center;">5.2</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td style="text-align: center;">1.0</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">12.3</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td style="text-align: center;">316</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td style="text-align: center;">0.689</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table> <p>Calculated Cv 44.77</p>	Fluid name	Hot Oil		[ LIQUID ]	UNIT		MAX	NOR	MIN		Flow rate	46.2			m3/h	Inlet pressure	5.2			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	1.0			kgf/cm2	Shut-off press.		12.3		kgf/cm2	Temperature	316			degC	Sp.Gr. (liq.)	0.689			water=1	Sp.Gr. (gas,vapor)				MW	Viscosity				cP	Flash				%	<p><b>&lt;Seat Leakage&gt;</b></p> <p style="text-align: center;">CLASS II (SV0201-007)</p> <p><b>&lt;Note&gt;</b> Tokumi: V93-8763-00 - 1 Existing Valve Prod No. 416-8318-0800</p> <p><b>&lt;Line spec&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">inch</td> </tr> <tr> <td>Line Sch. / Thick.</td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	inch	Line Sch. / Thick.	mm
Fluid name	Hot Oil		[ LIQUID ]	UNIT																																																																	
	MAX	NOR	MIN																																																																		
Flow rate	46.2			m3/h																																																																	
Inlet pressure	5.2			kgf/cm2A																																																																	
Outlet pressure				kgf/cm2A																																																																	
Diff. pressure	1.0			kgf/cm2																																																																	
Shut-off press.		12.3		kgf/cm2																																																																	
Temperature	316			degC																																																																	
Sp.Gr. (liq.)	0.689			water=1																																																																	
Sp.Gr. (gas,vapor)				MW																																																																	
Viscosity				cP																																																																	
Flash				%																																																																	
Design press.	kPaG																																																																				
Design temp.	degC																																																																				
Line size in/out	inch																																																																				
Line Sch. / Thick.	mm																																																																				

**Specification Sheet**

<p>No.: 2 QTY: 1</p> <p>Tag no. 25-TV-016</p> <p>Service</p> <p><b>&lt; Specification &gt;</b></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 3 inch</p> <p>Port size 3 inch</p> <p>Rated Cv 110</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type FIN</p> <p>Actuator HA3D</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Push down to open)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p><b>&lt; Accesories &gt;</b></p> <p>Positioner / Signal HTP-1D</p> <p>Exprosn-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><b>&lt;Option&gt;</b></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><b>&lt;Finish&gt;</b></p> <p>Body: Silver</p> <p>Diaph. Case: Yellow</p> <p>Yoke: Yellow</p> <p>Paint: Standard</p>																																																																								
<p><b>&lt;Operating condition&gt;</b></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Hot Oil</th> <th></th> <th></th> <th>[ LIQUID ]</th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>79.3</td> <td></td> <td></td> <td>m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>6.15</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>2.8</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>17</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>235</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.75</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td>0.825</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table> <p>Calculated Cv 47.91</p>	Fluid name	Hot Oil			[ LIQUID ]		MAX	NOR	MIN	UNIT	Flow rate	79.3			m3/h	Inlet pressure	6.15			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	2.8			kgf/cm2	Shut-off press.		17		kgf/cm2	Temperature	235			degC	Sp.Gr. (liq.)	0.75			water=1	Sp.Gr. (gas,vapor)				MW	Viscosity	0.825			cP	Flash				%	<p><b>&lt;Seat Leakage&gt;</b></p> <p><b>&lt;Note&gt;</b> Tokumi: V93-8814-00 - 1 Existing Valve Prod No. 416-8314-3500</p> <p><b>&lt;Line spec&gt;</b></p> <table border="1"> <tr> <td>Design press.</td> <td></td> <td>kgf/cm2G</td> </tr> <tr> <td>Design temp.</td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick.</td> <td>/</td> <td>mm</td> </tr> </table>	Design press.		kgf/cm2G	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick.	/	mm
Fluid name	Hot Oil			[ LIQUID ]																																																																					
	MAX	NOR	MIN	UNIT																																																																					
Flow rate	79.3			m3/h																																																																					
Inlet pressure	6.15			kgf/cm2A																																																																					
Outlet pressure				kgf/cm2A																																																																					
Diff. pressure	2.8			kgf/cm2																																																																					
Shut-off press.		17		kgf/cm2																																																																					
Temperature	235			degC																																																																					
Sp.Gr. (liq.)	0.75			water=1																																																																					
Sp.Gr. (gas,vapor)				MW																																																																					
Viscosity	0.825			cP																																																																					
Flash				%																																																																					
Design press.		kgf/cm2G																																																																							
Design temp.		degC																																																																							
Line size in/out	/	inch																																																																							
Line Sch. / Thick.	/	mm																																																																							

# Specification Sheet

<p>No.: 3 QTY: 1</p> <p>Tag no. 25-TV-050</p> <p>Service</p> <p><b>&lt; Specification &gt;</b></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1-1/2 inch</p> <p>Port size 1-1/2 inch</p> <p>Rated Cv 30</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type</p> <p>Actuator HA2D</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Push down to open)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 800</p> <p>Air supply</p> <p>Spring range 0.2-1.0kgf/cm2</p> <p><b>&lt; Accesories &gt;</b></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal</p> <p>Regurator</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve</p> <p style="padding-left: 20px;">Action</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><b>&lt;Option&gt;</b></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><b>&lt;Finish&gt;</b></p> <p>Body: Silver</p> <p>Diaph. Case: Yellow</p> <p>Yoke: Yellow</p> <p>Paint Standard</p>																																																																				
<p><b>&lt;Operating condition&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">Solvent</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th style="text-align: left;">[ LIQUID ]</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>MAX 17.1</td> <td></td> <td></td> <td>UNIT m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>3.52</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>1.5</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">9</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>55</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.779</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td>0.39</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Calculated Cv</td> <td>14.38</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Fluid name	Solvent	NOR	MIN	[ LIQUID ]	Flow rate	MAX 17.1			UNIT m3/h	Inlet pressure	3.52			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	1.5			kgf/cm2	Shut-off press.		9		kgf/cm2	Temperature	55			degC	Sp.Gr. (liq.)	0.779			water=1	Sp.Gr.(gas,vapor)				MW	Viscosity	0.39			cP	Flash				%	Calculated Cv	14.38				<p><b>&lt;Seat Leakage&gt;</b></p> <p style="text-align: center;">CLASS II (SV0201-007)</p> <p><b>&lt;Note&gt;</b> Tokumi: V93-8763-00 - 2</p> <p>Existing Valve Prod No. 416-8315-2900</p> <p><b>&lt;Line spec&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">inch</td> </tr> <tr> <td>Line Sch. / Thick.</td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	inch	Line Sch. / Thick.	mm
Fluid name	Solvent	NOR	MIN	[ LIQUID ]																																																																	
Flow rate	MAX 17.1			UNIT m3/h																																																																	
Inlet pressure	3.52			kgf/cm2A																																																																	
Outlet pressure				kgf/cm2A																																																																	
Diff. pressure	1.5			kgf/cm2																																																																	
Shut-off press.		9		kgf/cm2																																																																	
Temperature	55			degC																																																																	
Sp.Gr. (liq.)	0.779			water=1																																																																	
Sp.Gr.(gas,vapor)				MW																																																																	
Viscosity	0.39			cP																																																																	
Flash				%																																																																	
Calculated Cv	14.38																																																																				
Design press.	kPaG																																																																				
Design temp.	degC																																																																				
Line size in/out	inch																																																																				
Line Sch. / Thick.	mm																																																																				