

Multifunction pulse/Pneumatic Pressure Converter Model J - APN11

Issued : Jun. 1,2002	Page : 10-1-12
Effective : Jun. 1,2002	UNIT : 1000YEN

Pricing Procedure = Basic Price + Additional Price

Multifunction Pulse/Pneumatic Pressure Converter (Model J - APN11)

Model No. Structure : J - APN11 - (1)(2)(3)(4)(5)(6)(7)(8)(9)(10)(11)(12)(13)(14) - Optional Specifications

Basic Model No

Basic Price

Multifunction Pulse/Pneumatic Pressure C	J - APN11		772
--	-----------	--	-----

Selections

Additional Price

(1)	Power Supply Unit	24V DC Isolation type	B				0
(2)	Input Signal	Pulse Length	I				0
		Pulse Row	J				0
(3)	Pneumatic Pressure Output Singnal	0.2 to 1.0 kgf / cm ²	1				0
		3 to 15 psi	2				0
		0.2 to 1.0 bar	3				0
		20 to 100 kpa	4				0
(4)	Current Signal	4 to 20 mA DC	1				0
		20 to 4 mA DC(reverse characteris	2				11
(5)	External Connection	Pneumatic Rc1/4, Electric G3/4 Internal thread	R				0
		Pneumatic 1/4 NPT, Electric G3/4 NPT Internal thread	N				0
(6)	Case Finish	Standard	1				0
		Corrosion - proof	2				11 (15)
		Heavy duty corrosion - proof	3				17 (25)
		Silver - painted	4				11 (15)
		Corrosion - proof silver - painted	5				17 (23)
(7)	Mounting bracket	for 2 in. pipe	T				0
		for wall	S				0
(8)	Water - resistant Gland	N/A	X				0
		SUS304 (Packing diameter : 12)	1				15
		SUS304 (Packing diameter : 13)	2				15
		SUS304 (Packing diameter : 15)	3				15
(9)	Power Failure Monitor	N/A	X				0
		Normally closed	H				5
		Normally oper	K				5
(10)	Pneumatic Pressure Failure Monitor	N/A	X				0
		Normally closed	H				55
		Normally oper	K				55
(11)	Pneumatic Pressure Output Signal Monitor	N/A	X				0
		One point (Upper), Normally closed	1				55
		One point (Lower), Normally closed	2				55
		Two points (Upper and lower), Normally closed	3				110
		One point (Upper), Normally open	4				55
		One point (Lower), Normally open	5				55
	Two points (Upper and lower), Normally ope	6				110	
(12)	Case	Water - resistant	W				0
(13)	Power supply for P/I Unit	Integrally mounted in the case	1				0
		External	2				0
(14)	Limit Contact Signal	Contact Output available, Normally closedd	H				5
		Contact Output available, Normally open	K				5
		Contact Output unavailable, Normally closec	E				0
Options							
	N/A		X				0
	Manual Operation Unit		M				67
	Pressure regulator with filte		7				26

Note 1 : Water - resistant gland unavailable for External Connection N.

2 : Additional price for Regulator with Air Filter selected is parenthesized.

3 : Two points pneumatic Pressure Output Signal Monitor unavailable if Limit Contact Output Signal available selected.

4 : Manual Operation Unit unavailable if Two points Pneumatic Pressure Output Signal Monitor Selected.