

MagneW 3000 PLUS FM/CSA Explosion-proof detector (Wafer type 2.5mm - 10mm, PFA liner)

Issued : Oct. 31, 2001	Page : 2-133
Effective : Oct. 31, 2001	UNIT : 1000YEN

MGG17D - I II III IV V VI VII VIII IX - X XI - Y/ Options (Some Options can be selected per each moc

Option "Y" must be specified for Yamatake Version

Lead-time : After receipt of order(s), ex-factory basis.

					Basic price / Additional price			Lead time
					2.5mm	5mm	10mm	
Basic Model No.		MGG17D						
I	Diameter	2.5mm	002		391			5
		5mm	005			371		5
		10mm	010				365	5
II	Liner	PFA	P					
III	Piping connection	Wafer JIS10K	11		0	0	0	
		Wafer JIS20K	12		0	0	0	
		Wafer JIS30K	13		0	0	0	
		Wafer JIS10/20K for 10mm flange	14		0	0	0	
		Wafer JIS30K for 10mm flange	15		0	0	0	
		Wafer ANSI150	21		0	0	0	
		Wafer ANSI300	22		0	0	0	
		Wafer DIN PN10	41		0	0	0	
		Wafer DIN PN16	42		0	0	0	
		Wafer DIN PN25	43		0	0	0	
		Wafer DIN PN40	44		0	0	0	
		Wafer DIN PN10/16/25/40 for 10mm flange	45		0	0	0	
		Wafer JPI150	61		0	0	0	
Wafer JPI300	62		0	0	0			
IV	Electrodes	SUS316L	L		0	0	0	
		Hastelloy C	C		36	36	36	
		Titanium	K		41	41	41	
		Zirconium	H		170	170	170	10
		Tantalum	T		103	103	103	
		Tungsten carbide (only for size 10mm or larger)	W				180	
		Platinum iridium	P		171	171	171	
		Others	<input type="checkbox"/>		Refer to Option table of Electrodes			
V	Ground rings	SUS316	S		0	0	0	
		Hastelloy C	C		57	57	57	
		Titanium	K		52	52	52	
		Zirconium	H		80	80	80	10
		Tantalum	T		103	103	103	
		Platinum	P		149	149	149	
		Others	<input type="checkbox"/>		Refer to Option table of Grounding rings			
VI	Electrical connection / Watertight gland / Protective assembly	Remote type	1/2 NPT internal thread/ without watertight gland / with zener barrier	5	10	10	10	
VII	Face to face	Standard	A		0	0	0	
		Others	<input type="checkbox"/>		Refer to Option table of Face to face dimension			
VIII	Installation / Wiring direction	Remote type	Upstream side (Horizontal / Vertical piping mounting)	A	0	0	0	
			Downstream side (Horizontal / Vertical piping mounting)	B	0	0	0	
			Horizontal piping mounting / Left side viewed from upstream	C	0	0	0	
			Horizontal piping mounting / Right side viewed from upstream	D	0	0	0	
IX	Calibration	Standard	A		0	0	0	
		Others	<input type="checkbox"/>		Refer to Option table of calibration			
X	Finish	Standard	X		0	0	0	
		Corrosion-resistant finish	1		5	5	5	
		Corrosion-proof finish	2		10	10	10	
XI	Bolt/nuts	None	X		0	0	0	
		Carbon steel	1		3	3	3	
		SUS304	2		5	5	5	

MagneW 3000 PLUS FM/CSA Explosion-proof detector (Wafer type 2.5mm - 10mm, PFA liner)

Issued : Oct. 31, 2001	Page : 2-134
Effective : Oct. 31, 2001	UNIT : 1000YEN

Option (Some options can be selected per each model.)

Lead-time : The term after receipt of order(s) to ex-factory.

Remote type			Additional Price	Lead Time (Weeks)
Option	Y	Yamatake Version (Must be selected)	0	7
	A	Calibration certificate(Sent to ordering location separately)	2	
	B	Traceability certificate for detector	10	
	C	Material certificate (only for electrodes and grounding rings)	45	
	J	W/Gasket for plastic piping	7	
	K	Attachment of the TAG number to the terminal box for detector**Note 3	4	
	L	Attachment of the TAG number plate to the neck section for detector** Note3	8	
	P	Specific color finish for detector **Note 4	40	8
	E	Water free treatment	40	8
	F	Oil free treatment	50	

Note 3 : Must be selected for Tag No. requirement

Note 4: Must specify Munsel No.

Option table of Grounding rings material

		Additional Price	Lead time
A	Alloy 20	70	10
E	SUS304	10	Refer to factory basis
L	SUS316L	25	10

Option table of Electrode material

		Additional Price	Lead time
A	Alloy 20	80	10
E	SUS304	20	10
M	Monel	60	10

Option table of Face to face dimension

		Additional Price	Lead time
B	YOKOGAWA YEWAG / YM, CYM(1,2), Tantalum / Platinum	Refer to factory basis	
C	YOKOGAWA ADMAG / AM, AE(1,2), Tantalum / Platinum	Refer to factory basis	
P	YOKOGAWA YEWAG / ADMAG, other than Tantalum / Platinum	13	
D	Hitachi FMR / FMR22, FMR23(1)	13	10
E	Hitachi FMR / FMR104, (1)	13	10
F	Toshiba TOSMAC / 335 (1)	13	10
G	Toshiba LF / LF200 (1)	13	10
H	F&P COPA-XM/D10D30XM (1,3)	13	10
J	F&P MINI-MAG/10D1475 (4)	13	10
K	Krohne ALTOFLUX/X1000 (3)	13	10
L	Brooks WAFER-MAG/74 (1)	13	10

1: Teflon liner

2: Polyurethane rubber liner

3: Ceramic liner

4: Tefzel liner

Option table of Calibration

		Additional Price	Lead time
B	3 point dual range (0, 50, 100%)	100	10
E	5 point single range (0, 25, 50, 75, 100%)	100	10
F	5 point dual range (0, 25, 50, 75, 100%)	200	10
G	7 point single range (0, 5, 10, 25, 50, 75, 100%)	450	10
H	7 point dual range (0, 5, 10, 25, 50, 75, 100%)	600	10

MagneW 3000 PLUS FM/CSA Explosion-proof detector (Wafer type 15mm - 200mm, PFA liner)

Issued : Oct. 31, 2001	Page : 2-135
Effective : Oct. 31, 2001	UNIT : 1000YEN

MGG17D - I II III VI V VI VII VIII IX - X XI - Y/ Options (Some Options can be selected per each model.)

Option "Y" must be specified for Yamatake Version
Lead-time : After receipt of order(s), ex-factory basis.

Basic Model No.		MGG17D		Basic price / Additional price										Lead time			
				15mm	25mm	40mm	50mm	65mm	80mm	100mm	125mm	150mm	200mm				
I	Diameter	15mm	015	328												7	
		25mm	025		365												7
		40mm	040			389											7
		50mm	050				426										7
		65mm	065					495									7
		80mm	080						521								7
		100mm	100							645							7
		125mm	125								878						7
		150mm	150									989					7
200mm	200										1310				7		
II	Liner	PFA	P														
III	Piping connection	Wafer JIS10K	11	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer JIS20K	12	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer JIS30K	13	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer ANSI150	21	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer ANSI300	22	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer DIN PN10	41	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer DIN PN16	42	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer DIN PN25	43	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer DIN PN40	44	0	0	0	0	0	0	0	0	0	0	0	0		
		Wafer JPI150	61	0	0	0	0	0	0	0	0	0	0	0	0		
Wafer JPI300	62	0	0	0	0	0	0	0	0	0	0	0	0				
IV	Electrodes	SUS316L	L	0	0	0	0	0	0	0	0	0	0	0			
		Hastelloy C	C	36	36	36	36	36	36	36	36	36	36	36			
		Titanium	K	41	41	41	41	41	41	41	41	41	41	41			
		Zirconium	H	170	170	170	170	170	170	170	170	170	170	170	10		
		Tantalum	T	103	103	103	103	103	103	103	103	103	103	103			
		Tungsten carbide (only for size 10mm or larger)	W	180	180	180	180	180	180	180	180	180	180	180			
		Platinum iridium	P	175	175	175	175	175	175	175	175	175	175	175			
Others	□	Refer to Option table of Electrodes															
V	Ground rings	SUS316	S	0	0	0	0	0	0	0	0	0	0	0			
		Hastelloy C	C	57	57	57	57	72	72	93	112	134	170				
		Titanium	K	52	52	52	52	67	67	82	99	124	155				
		Zirconium	H	104	104	104	104	134	134	164	198	248	305	10			
		Tantalum	T	103	103	103	103	113	113	134	161	206	258				
		Platinum	P	149	149	149	149	160	160	185	222	256	338				
		Others	□	Refer to Option table of Grounding rings													
VI	Electrical connection / Watertight gland / Protective	Remote type	1/2 NPT internal thread / without watertight gland / with zener barrier	5	10	10	10	10	10	10	10	10	10	10			
VII	Face to face	Standard	A	0	0	0	0	0	0	0	0	0	0	0			
		Others	□	Refer to Option table of Face to face dimension													
VIII	Installation / Wiring direction	Remote type	Upstream side (Horizontal / Vertical piping mounting)	A	0	0	0	0	0	0	0	0	0	0			
		Downstream side (Horizontal / Vertical piping mounting)	B	0	0	0	0	0	0	0	0	0	0	0			
		Horizontal piping mounting / Left side viewed from upstream	C	0	0	0	0	0	0	0	0	0	0	0			
		Horizontal piping mounting / Right side viewed from upstream	D	0	0	0	0	0	0	0	0	0	0	0			
IX	Calibration	Standard	A	0	0	0	0	0	0	0	0	0	0	0			
		Others	□	Refer to Option table of calibration													
X	Finish	Standard	X	0	0	0	0	0	0	0	0	0	0	0			
		Corrosion-resistant finish	1	5	5	5	5	5	5	5	5	5	5	5			
		Corrosion-proof finish	2	10	10	10	10	10	10	10	10	10	10	10			
XI	Bolt/nuts	None	X	0	0	0	0	0	0	0	0	0	0	0			
		Carbon steel	1	3	3	3	3	9	9	9	9	9	22				
		SUS304	2	5	5	5	5	20	20	20	20	20	40				

MagneW 3000 PLUS FM/CSA Explosion-proof detector (Wafer type 15mm - 200mm, PFA liner)

Issued : Oct. 31,2001	Page : 2-136
Effective : Oct. 31,2001	UNIT : 1000YEN

Option (Some options can be selected per each model.)

Lead-time : The term after receipt of order(s) to ex-factory.

Remote type

Option	Y	Additional Price	Lead Time
	Yamatake Version (Must be selected)	0	
	A Calibration certificate(Sent to ordering location separately)	2	
	B Traceability certificate for detector	10	
	C Material certificate (only for electrodes and grounding rings)	45	7
	J W/Gasket for plastic piping	Refer to table of gasket	
	K Attachment of the TAG number to the terminal box for detector**Note 3	4	
	L Attachment of the TAG number plate to the neck section for detector**	8	
	P Specific color finish for detector **Note 4	40	8
	E Water free treatment	40	
	F Oil free treatment	50	

Note 3 : Must be selected for Tag No. requirement

Note 4: Must specify Munsel No.

Table of gasket for plastic piping

Diameter (mm)	15	25	40	50	65	80	100	125	150	200
J	7	10	14	19	19	35	45	80	80	120

Option table of Electrode material

		Additional Price	Lead time
A	Alloy 20	80	10
E	SUS304	20	10
M	Monel	60	10
N	Nickel	120	10
S	SUS316	20	10
1	SUS316L Protuded Electrode Note 1	55	10
2	SUS316L Alumina Specification Protuded Electrode w/flat tip Note 1	80	10
3	SUS316L Alumina Specification Protuded Electrode w/pointed tip Note 1	70	10

Note 1: Protrusion : Dia. 15mm(1.5mm), Dia. 25mm(2mm), Dia.40-200mm(3mm)

Option table of Calibration

		Additional Price	Lead time
B	3 point dual range (0, 50, 100%)	100	10
E	5 point single range (0, 25, 50, 75, 100%)	100	10
F	5 point dual range (0, 25, 50, 75, 100%)	200	10
G	7 point single range (0, 5, 10, 25, 50, 75, 100%)	450	10
H	7 point dual range (0, 5, 10, 25, 50, 75, 100%)	600	10

Option table of Grounding rings material

	Diameter (mm)	15	25	40	50	65	80	100	125	150	200	Lead time
A	Alloy 20	70	70	70	70	70	80	100	140	140	180	10
E	SUS304	10	10	10	10	10	10	10	10	10	10	7
G	SUS316 Top Hat Grounding Rings	Refer to factory basis										
L	SUS316L	25	25	25	25	25	30	40	60	60	70	7
N	Nickel	45	45	55	65	65	100	110	250	250	350	10

Option table of Face to face dimension

	Diameter (mm)	15	25	40	50	80	100	150	200	Lead time
B	YOKOGAWA YEWMAG / YM, CYM(1,2), Tantalum / Platinum	Refer to factory basis				20	26	40	53	Refer to factory basis
C	YOKOGAWA ADMAG / AM, AE(1,2), Tantalum / Platinum	Refer to factory basis				20	26	40	53	Refer to factory basis
P	YOKOGAWA YEWMAG / ADMAG, other than Tantalum / Platinum					20	26	40	53	Refer to factory basis
D	Hitachi FMR / FMR22, FMR23(1)	13	14	15	16	20	26	40	53	10
E	Hitachi FMR / FMR104, (1)									
F	Toshiba TOSMAC / 335 (1)									
G	Toshiba LF / LF200 (1)	Refer to factory basis								
H	F&P COPA-XM/D10D30XM (1,3)	13	14	15	16					
J	F&P MINI-MAG/10D1475 (4)	Refer to factory basis								
K	Krohne ALTOFLUX/X1000 (3)	13	14	15	16					
L	Brooks WAFER-MAG/74 (1)	Refer to factory basis								

1: Teflon liner

2: Polyurethane rubber liner

3: Ceramic liner

4: Tefzel liner

MagneW 3000 PLUS FM/CSA Explosion-proof detector (Flange type 15mm - 200mm, PFA liner)

Issued : Oct. 31, 2001	Page : 2-1-38
Effective : Oct. 31, 2001	UNIT : 1000YEN

Option (Some options can be selected per each model.)

Lead-time : The term after receipt of order(s) to ex-factory.

Remote type

Option			Additional Price	Lead Time (Weeks)
Option	Y	Yamatake Version (Must be selected)	0	7
	A	Calibration certificate(Sent to ordering location separately)	2	
	B	Traceability certificate for detector	10	
	C	Material certificate (only for electrodes and grounding rings)	45	
	J	W/Gasket for plastic piping	Refer to table of gasket	8
	K	Attachment of the TAG number to the terminal box for detector**Note 3	4	
	L	Attachment of the TAG number plate to the neck section for detector** Note 4	8	
	P	Specific color finish for detector **Note 4	40	
E	Water free treatment	40		
F	Oil free treatment	50		

Note 3 : Must be selected for Tag No. requirement

Note 4: Must specify Munsel No.

Table of gasket for plastic piping

Diameter (mm)	15	25	40	50	65	80	100	125	150	200
J	7	10	14	19	19	35	45	80	80	120

Option table of Electrode material

		Additional Price	Lead time
A	Alloy 20	80	10
E	SUS304	20	10
M	Monel	60	10
N	Nickel	120	10
S	SUS316	20	10
1	SUS316L Protuded Electrode Note 1	55	10
2	SUS316L Alumina Specification Protuded Electrode w/flat tip Note 1	80	10
3	SUS316L Alumina Specification Protuded Electrode w/pointed tip Note 1	70	10

Note 1: Protrusion : Dia. 15mm (1.5mm), Dia. 25mm (2mm), Dia. 40-200mm (3mm)

Option table of Grounding rings material

	Diameter (mm)	15	25	40	50	65	80	100	125	150	200	Lead time
A	Alloy 20	70	70	70	70	70	80	100	140	140	180	10
E	SUS304	10	10	10	10	10	10	10	10	10	10	7
G	SUS316 Top Hat Grounding Rings	Refer to factory basis										
L	SUS316L	25	25	25	25	25	30	40	60	60	70	7
N	Nickel	45	45	55	65	65	100	110	250	250	350	10

Option table of Face to face dimension

	Diameter (mm)	80	100	150	200	Lead time
B	YOKOGAWA YEWMAG / YM, CYM(1,2), Tantalum / Platinum	30	39	60	80	Refer to factory basis
C	YOKOGAWA ADMAG / AM, AE(1,2), Tantalum / Platinum	30	39	60	80	Refer to factory basis
P	YOKOGAWA YEWMAG / ADMAG, other than Tantalum / Platinum	30	39	60	80	Refer to factory basis
E	Hitachi FMR / FMR104, (1)	Refer to factory basis				4
F	Toshiba TOSMAC / 335 (1)					
H	F&P COPA-XM/D10D30XM (1,3)					
J	F&P MINI-MAG/10D1475 (4)					
K	Krohne ALTOFLUX/X1000 (3)					
L	Brooks WAFER-MAG/74 (1)					
M	Yamatake MagneW/ NNM (1)	60	78	120	160	4

1: Teflon liner

2: Polyurethane rubber liner

3: Ceramic Liner

4: Tefzel liner

Option table of Flange Material (Flange Material : SUS304) Option table of Calibration

	Diameter (mm)	80	100	125	150	200	Lead time	Additional Price	Lead time
4	Flange JIS10K	115	144	230	301	606	10	100	10
	Flange JIS20K	154	197	320	439	760	10		
	Flange JIS30K	276	339	526	708	1249	10		
	Flange ANSI150	149	197	300	388	734	10		
	Flange ANSI300	248	347	495	617	1170	10		
	Flange DIN PN10	208	259	370	475	862	10		
	Flange DIN PN16	208	259	425	530	942	10		
	Flange DIN PN25	273	339	533	755	1313	10		
	Flange DIN PN40	273	339	533	755	1313	10		
	Flange JPI150	149	197	300	388	734	10		
	Flange JPI300	248	347	495	617	1170	10		
B	3 point dual range (0, 50, 100%)							100	10
E	5 point single range (0, 25, 50, 75, 100%)							100	10
F	5 point dual range (0, 25, 50, 75, 100%)							200	10
G	7 point single range (0, 5, 10, 25, 50, 75, 100%)							450	10
H	7 point dual range (0, 5, 10, 25, 50, 75, 100%)							600	10

MagneW 3000 PLUS FM/CSA Explosion-proof detector (Flange type 250mm - 400mm, PFA

Issued : Oct. 31,2001	Page : 2-139
Effective : Oct. 31,2001	UNIT : 1000YEN

MGG17F - I II III IV V VI VII VIII IX X - XI -Y/Option (Some Options can be selected per each mod

Option "Y" must be specified for Yamatake Version

Lead-time : After receipt of order(s), ex-factory basis.

Basic Model No. MGG17F						Basic price / Additional price				Lead time
						15mm	300mm	350mm	400mm	
I	Diameter	250mm	250			2688				10
		300mm	300				3780			10
		350mm	350					4690		10
		400mm	400						5768	10
II	Liner	PFA	P			0	0	0	0	
III	Piping connection	Flange JIS10K	J1			0	0	0	0	
		Flange JIS20K	J2			100	140	196	274	
		Flange ANSI150	A1			0	0	0	0	14
		Flange ANSI300	A2			100	140	196	274	14
		Flange DIN PN10	D1			0	0	0	0	14
		Flange DIN PN16	D2			110	154	216	301	14
		Flange DIN PN25	D3			110	154	216	301	14
		Flange JPI150	P1			0	0	0	0	14
		Flange JPI300	P2			100	140	196	274	14
IV	Flange Material	Standard	1			0	0	0	0	
		Others	<input type="checkbox"/>			Refer to Option table of Flange Material				
V	Electrodes	SUS316L	L			0	0	0	0	
		Hastelloy C	C			36	36	36	36	
		Titanium	K			41	41	41	41	
		Zirconium	H			170	170	170	170	10
		Tantalum	T			120	120	120	120	
		Tungsten carbide (only for size 10mm or larger)	W			180	180	180	180	
		Platinum iridium	P			210	210	210	210	
		Others	<input type="checkbox"/>			Refer to Option table of Electrodes				
VI	Ground rings	SUS316	S			0	0	0	0	
		Hastelloy C	C			200	240	360	480	
		Titanium	K			200	240	360	480	
		Others	<input type="checkbox"/>			Refer to Option table of Grounding rings				
VII	Electrical connection/ Watertight gland/ Protective assembly	Remote type	1/2 NPT internal thread/ without watertight gland / with zener barrier	5		10	10	10	10	
		Standard								
VIII	Face to face dimension	Standard		A		0	0	0	0	
		Others		<input type="checkbox"/>		Refer to Option table of Face to face dimension				
IX	Installation / Wiring direction	Remote type	Upstream side (Horizontal / Vertical piping mounting)	A		0	0	0	0	
			Downstream side (Horizontal / Vertical piping mounting)	B		0	0	0	0	
			Horizontal piping mounting / Left side viewed from upstream	C		0	0	0	0	
			Horizontal piping mounting / Right side viewed from upstream	D		0	0	0	0	
X	Calibration	Standard		A		0	0	0	0	
		Others		<input type="checkbox"/>		Refer to Option table of calibration				
XI	Finish	Standard		X		0	0	0	0	
		Corrosion-resistant finish		1		5	5	5	5	
		Corrosion-proof finish		2		10	10	10	10	

MagneW 3000 PLUS FM/CSA Explosion-proof detector (Flange type 250mm - 400mm, PFA

Issued : Oct. 31,2001	Page : 2-140
Effective : Oct. 31,2001	UNIT : 1000YEN

Option (Some options can be selected per each model.)

Lead-time : The term after receipt of order(s) to ex-factory.

Remote type

Option			Additional Price	Lead Time (Weeks)
Y	Yamatake Version (Must be selected)		0	
A	Calibration certificate(Sent to ordering location separately)		2	
B	Traceability certificate for detector		10	
C	Material certificate (only for electrodes and grounding rings)		45	7
J	W/Gasket for plastic piping		Refer to table of gasket	
K	Attachment of the TAG number to the terminal box for detector**Note 3		4	
L	Attachment of the TAG number plate to the neck section for detector** Note3		8	
P	Specific color finish for detector **Note 4		40	8
E	Water free treatment		40	
F	Oil free treatment		50	

Note 3 : Must be selected for Tag No. requirement

Note 4: Must specify Munsel No.

Table of gasket for plastic piping

Diameter (mm)	250	300	350	400
J	180	270	405	608

Option table of Calibration

		Additional Price	Lead time
B	3 point dual range (0, 50, 100%)	100	10
E	5 point single range (0, 25, 50, 75, 100%)	100	10
F	5 point dual range (0, 25, 50, 75, 100%)	200	10
G	7 point single range (0, 5, 10, 25, 50, 75, 100%)	450	10
H	7 point dual range (0, 5, 10, 25, 50, 75, 100%)	600	10

Option table of Electrode material

		Additional Price	Lead time
A	Alloy 20	80	10
E	SUS304	20	10
M	Monel	60	10
N	Nickel	120	10

Option table of Grounding rings material

	Diameter (mm)	250	300	350	400	Lead time
A	Alloy 20	216	260	286	390	10
E	SUS304	12	15	17	25	7
G	SUS316 Top Hat Grounding Rings	Refer to factory basis				
L	SUS316L	84	101	111	166	7
N	Nickel	420	504	555	831	10

Option table of Face to face dimension

	Diameter (mm)	250	300	350	400	Lead time
P	YOKOGAWA 8 / ADMAG, other than Tantalum / Platinum					
H	F&P COPA-XM/D10D30XM (1,3)	96	135	168	206	
J	F&P MINI-MAG/10D1475 (4)					
K	Krohne ALTOFLUX/X1000 (3)					
M	Yamatake MagneW / NNM (1, 2)	192	270	336	412	
N	Yamatake MagneW3000 / KID (1, 2)	96	135	168	206	

1: Teflon liner

2: Polyurethane rubber liner

3: Ceramic Liner

4: Tefzel liner

Option table of Flange Material (Flange Material : SUS304)

	Diameter (mm)	250	300	350	400	Lead time
4	Flange JIS10K	325	391	510	650	10
	Flange JIS20K	588	727	961	1249	10
	Flange ANSI150	650	782	1020	1300	10
	Flange ANSI300	1400	1704	2236	2874	10
	Flange DIN PN10	650	782	1020	1300	10
	Flange DIN PN16	760	936	1236	1601	10
	Flange DIN PN25	1085	1327	1746	2251	10
	Flange JPI150	650	782	1020	1300	10
	Flange JPI300	1400	1704	2236	2874	10