

# Specification Sheet

<p>No.: 1 QTY: 1</p> <p>Tag no. HV-3711A</p> <p>Service</p> <p><b>&lt; Specification &gt;</b></p> <p>Model HTS</p> <p>Description Top-Guided Single Seated Control Valves</p> <p>Valve size 6 inch</p> <p>Port size 5 inch</p> <p>Rated Cv 275</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection BW</p> <p>Body material A351CF3</p> <p>Trim material SUS316L STELLITE</p> <p>Flow characteristic LINEAR</p> <p>Bonnet type EXTENTION-2W</p> <p>Actuator PSA6</p> <p>Manual operator</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V-PTFE</p> <p>Gasket V544(PTFE), V564(PTFE)</p> <p>Grease</p> <p>Air supply 5.0bar</p> <p>Spring range 2.0-3.9bar</p> <p><b>&lt; Accesories &gt;</b></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal On-Off action</p> <p>Regurator KZ03-2B-1B</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve with</p> <p style="padding-left: 20px;">Action En. : Control , De-en.: CV Close</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><b>&lt;Option&gt;</b></p> <p>SV0703-102 Indicating unit : "bar"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0210 High differential pressure trim for HTS Valve</p> <p>SV0018-005 Oil-free Gr.B (For stainless steel body) and Water-free treatment</p> <p><b>&lt;Finish&gt;</b></p> <p>Body:</p> <p>Diaph. Case:</p> <p>Yoke:</p> <p>Paint:</p>																																																																																												
<p><b>&lt;Operating condition&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th colspan="3">CH4 from K-303to P-301A/B [ GAS ]</th> <th></th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>19500</td> <td>18950</td> <td>13200</td> <td>m3/h[N]</td> </tr> <tr> <td>Inlet pressure</td> <td>3</td> <td>3</td> <td>3</td> <td>barA</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>barA</td> </tr> <tr> <td>Diff. pressure</td> <td></td> <td></td> <td></td> <td>bar</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>3</td> <td></td> <td>bar</td> </tr> <tr> <td>Temperature</td> <td>-148.3</td> <td>-148.3</td> <td>-148.3</td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td>0.72</td> <td>0.72</td> <td>0.72</td> <td>air=1</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dba</td> </tr> <tr> <td>Calculated Cv</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	CH4 from K-303to P-301A/B [ GAS ]					MAX	NOR	MIN	UNIT	Flow rate	19500	18950	13200	m3/h[N]	Inlet pressure	3	3	3	barA	Outlet pressure				barA	Diff. pressure				bar	Shut-off press.		3		bar	Temperature	-148.3	-148.3	-148.3	degC	Sp.Gr. (liq.)				water=1	Sp.Gr.(gas,vapor)	0.72	0.72	0.72	air=1	Viscosity				cP	Flash				%	Velocity				Mach	S.P.L.				dba	Calculated Cv					Travel				%	<p><b>&lt;Seat Leakage&gt;</b></p> <p>CLASS IV-S1 (SV0201-009)</p> <p><b>&lt;Note&gt;</b> Tokumi -</p> <p>Air piping: Stainless steel (316ss)</p> <p><b>&lt;Line spec&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Design press.</td> <td>15</td> <td>barG</td> </tr> <tr> <td>Design temp.</td> <td>-196 ~65</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>6</td> <td>6 inch</td> </tr> <tr> <td>Line Sch. / Thick.</td> <td>40S</td> <td>7.1 mm</td> </tr> </table>	Design press.	15	barG	Design temp.	-196 ~65	degC	Line size in/out	6	6 inch	Line Sch. / Thick.	40S	7.1 mm
Fluid name	CH4 from K-303to P-301A/B [ GAS ]																																																																																												
	MAX	NOR	MIN	UNIT																																																																																									
Flow rate	19500	18950	13200	m3/h[N]																																																																																									
Inlet pressure	3	3	3	barA																																																																																									
Outlet pressure				barA																																																																																									
Diff. pressure				bar																																																																																									
Shut-off press.		3		bar																																																																																									
Temperature	-148.3	-148.3	-148.3	degC																																																																																									
Sp.Gr. (liq.)				water=1																																																																																									
Sp.Gr.(gas,vapor)	0.72	0.72	0.72	air=1																																																																																									
Viscosity				cP																																																																																									
Flash				%																																																																																									
Velocity				Mach																																																																																									
S.P.L.				dba																																																																																									
Calculated Cv																																																																																													
Travel				%																																																																																									
Design press.	15	barG																																																																																											
Design temp.	-196 ~65	degC																																																																																											
Line size in/out	6	6 inch																																																																																											
Line Sch. / Thick.	40S	7.1 mm																																																																																											

# Specification Sheet

<p>No.: 2 QTY: 1</p> <p>Tag no. HV-3711B</p> <p>Service</p> <p><b>&lt; Specification &gt;</b></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1/2 inch</p> <p>Port size Cv=2.5 inch</p> <p>Rated Cv 2.5</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection BW</p> <p>Body material A351CF3</p> <p>Trim material SUS316L STELLITE</p> <p>Flow characteristic LINEAR</p> <p>Bonnet type EXTENTION-2W</p> <p>Actuator HA2</p> <p>Manual operator</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V-PTFE</p> <p>Gasket V544(PTFE), V564(PTFE)</p> <p>Grease</p> <p>Air supply 2.7bar</p> <p>Spring range 0.8-2.4bar</p> <p><b>&lt; Accesories &gt;</b></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal On-Off action</p> <p>Regurator KZ03-2B-1B</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve with</p> <p style="padding-left: 20px;">Action</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><b>&lt;Option&gt;</b></p> <p>SV0703-102 Indicating unit : "bar"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0018-005 Oil-free Gr.B (For stainless steel body) and Water-free treatment</p> <p><b>&lt;Finish&gt;</b></p> <p>Body:</p> <p>Diaph. Case:</p> <p>Yoke:</p> <p>Paint:</p>																																																																																																																				
<p><b>&lt;Operating condition&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Fluid name</td> <td style="width: 35%;">P-301A/Bblowdown(cooling down [</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;">UNIT</td> </tr> <tr> <td></td> <td style="text-align: center;">MAX NOR MIN</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Flow rate</td> <td></td> <td></td> <td></td> <td></td> <td>l/h</td> </tr> <tr> <td>Inlet pressure</td> <td></td> <td></td> <td></td> <td></td> <td>barA</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td></td> <td>barA</td> </tr> <tr> <td>Diff. pressure</td> <td></td> <td></td> <td></td> <td></td> <td>bar</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">39</td> <td></td> <td></td> <td>bar</td> </tr> <tr> <td>Temperature</td> <td></td> <td></td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td></td> <td>dBa</td> </tr> <tr> <td>Calculated Cv</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td></td> <td>%</td> </tr> </table>	Fluid name	P-301A/Bblowdown(cooling down [				UNIT		MAX NOR MIN					Flow rate					l/h	Inlet pressure					barA	Outlet pressure					barA	Diff. pressure					bar	Shut-off press.		39			bar	Temperature					degC	Sp.Gr. (liq.)					water=1	Sp.Gr.(gas,vapor)					kg/m3[N]	Viscosity					cP	Flash					%	Velocity					m/s	S.P.L.					dBa	Calculated Cv						Travel					%	<p><b>&lt;Seat Leakage&gt;</b></p> <p style="text-align: center;">CLASS IV-S1 (SV0201-009)</p> <p><b>&lt;Note&gt;</b> Tokumi -</p> <p>Air piping: Stainless steel (316ss)</p> <p><b>&lt;Line spec&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Design press.</td> <td style="width: 20%;">39</td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;">barG</td> </tr> <tr> <td>Design temp.</td> <td>-196 ~65</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>1/2</td> <td style="text-align: center;">//</td> <td>1/2</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick.</td> <td>10S</td> <td style="text-align: center;">//</td> <td>2.11</td> <td>mm</td> </tr> </table>	Design press.	39			barG	Design temp.	-196 ~65			degC	Line size in/out	1/2	//	1/2	inch	Line Sch. / Thick.	10S	//	2.11	mm
Fluid name	P-301A/Bblowdown(cooling down [				UNIT																																																																																																																
	MAX NOR MIN																																																																																																																				
Flow rate					l/h																																																																																																																
Inlet pressure					barA																																																																																																																
Outlet pressure					barA																																																																																																																
Diff. pressure					bar																																																																																																																
Shut-off press.		39			bar																																																																																																																
Temperature					degC																																																																																																																
Sp.Gr. (liq.)					water=1																																																																																																																
Sp.Gr.(gas,vapor)					kg/m3[N]																																																																																																																
Viscosity					cP																																																																																																																
Flash					%																																																																																																																
Velocity					m/s																																																																																																																
S.P.L.					dBa																																																																																																																
Calculated Cv																																																																																																																					
Travel					%																																																																																																																
Design press.	39			barG																																																																																																																	
Design temp.	-196 ~65			degC																																																																																																																	
Line size in/out	1/2	//	1/2	inch																																																																																																																	
Line Sch. / Thick.	10S	//	2.11	mm																																																																																																																	

# Specification Sheet

<p>No.: 3 QTY: 1</p> <p>Tag no. HV-3721A</p> <p>Service</p> <p><b>&lt; Specification &gt;</b></p> <p>Model HTS</p> <p>Description Top-Guided Single Seated Control Valves</p> <p>Valve size 6 inch</p> <p>Port size 5 inch</p> <p>Rated Cv 275</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection BW</p> <p>Body material A351CF3</p> <p>Trim material SUS316L STELLITE</p> <p>Flow characteristic LINEAR</p> <p>Bonnet type EXTENTION-2W</p> <p>Actuator PSA6</p> <p>Manual operator</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V-PTFE</p> <p>Gasket V544(PTFE), V564(PTFE)</p> <p>Grease</p> <p>Air supply 5.0bar</p> <p>Spring range 2.0-3.9bar</p> <p><b>&lt; Accesories &gt;</b></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal On-Off action</p> <p>Regurator KZ03-2B-1B</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve with</p> <p style="padding-left: 20px;">Action En. : Control , De-en.: CV Close</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><b>&lt;Option&gt;</b></p> <p>SV0703-102 Indicating unit : "bar"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0210 High differential pressure trim for HTS Valve</p> <p>SV0018-005 Oil-free Gr.B (For stainless steel body) and Water-free treatment</p> <p><b>&lt;Finish&gt;</b></p> <p>Body:</p> <p>Diaph. Case:</p> <p>Yoke:</p> <p>Paint:</p>																																																																																												
<p><b>&lt;Operating condition&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th colspan="3">CH4 from K-303to P-301A/B [ GAS ]</th> <th></th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>19500</td> <td>18950</td> <td>13200</td> <td>m3/h[N]</td> </tr> <tr> <td>Inlet pressure</td> <td>3</td> <td>3</td> <td>3</td> <td>barA</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>barA</td> </tr> <tr> <td>Diff. pressure</td> <td></td> <td></td> <td></td> <td>bar</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>3</td> <td></td> <td>bar</td> </tr> <tr> <td>Temperature</td> <td>-148.3</td> <td>-148.3</td> <td>-148.3</td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td>0.72</td> <td>0.72</td> <td>0.72</td> <td>air=1</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	CH4 from K-303to P-301A/B [ GAS ]					MAX	NOR	MIN	UNIT	Flow rate	19500	18950	13200	m3/h[N]	Inlet pressure	3	3	3	barA	Outlet pressure				barA	Diff. pressure				bar	Shut-off press.		3		bar	Temperature	-148.3	-148.3	-148.3	degC	Sp.Gr. (liq.)				water=1	Sp.Gr.(gas,vapor)	0.72	0.72	0.72	air=1	Viscosity				cP	Flash				%	Velocity				Mach	S.P.L.				dBA	Calculated Cv					Travel				%	<p><b>&lt;Seat Leakage&gt;</b></p> <p>CLASS IV-S1 (SV0201-009)</p> <p><b>&lt;Note&gt;</b> Tokumi -</p> <p>Air piping: Stainless steel (316ss)</p> <p><b>&lt;Line spec&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Design press.</td> <td>15</td> <td>barG</td> </tr> <tr> <td>Design temp.</td> <td>-196 ~65</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>6</td> <td>6 inch</td> </tr> <tr> <td>Line Sch. / Thick.</td> <td>40S</td> <td>7.1 mm</td> </tr> </table>	Design press.	15	barG	Design temp.	-196 ~65	degC	Line size in/out	6	6 inch	Line Sch. / Thick.	40S	7.1 mm
Fluid name	CH4 from K-303to P-301A/B [ GAS ]																																																																																												
	MAX	NOR	MIN	UNIT																																																																																									
Flow rate	19500	18950	13200	m3/h[N]																																																																																									
Inlet pressure	3	3	3	barA																																																																																									
Outlet pressure				barA																																																																																									
Diff. pressure				bar																																																																																									
Shut-off press.		3		bar																																																																																									
Temperature	-148.3	-148.3	-148.3	degC																																																																																									
Sp.Gr. (liq.)				water=1																																																																																									
Sp.Gr.(gas,vapor)	0.72	0.72	0.72	air=1																																																																																									
Viscosity				cP																																																																																									
Flash				%																																																																																									
Velocity				Mach																																																																																									
S.P.L.				dBA																																																																																									
Calculated Cv																																																																																													
Travel				%																																																																																									
Design press.	15	barG																																																																																											
Design temp.	-196 ~65	degC																																																																																											
Line size in/out	6	6 inch																																																																																											
Line Sch. / Thick.	40S	7.1 mm																																																																																											

# Specification Sheet

<p>No.: 4 QTY: 1</p> <p>Tag no. HV-3721B</p> <p>Service</p> <p><b>&lt; Specification &gt;</b></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1/2 inch</p> <p>Port size Cv=2.5 inch</p> <p>Rated Cv 2.5</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection BW</p> <p>Body material A351CF3</p> <p>Trim material SUS316L STELLITE</p> <p>Flow characteristic LINEAR</p> <p>Bonnet type EXTENTION-2W</p> <p>Actuator HA2</p> <p>Manual operator</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V-PTFE</p> <p>Gasket V544(PTFE), V564(PTFE)</p> <p>Grease</p> <p>Air supply 2.7bar</p> <p>Spring range 0.8-2.4bar</p> <p><b>&lt; Accesories &gt;</b></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal On-Off action</p> <p>Regurator KZ03-2B-1B</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve with</p> <p style="padding-left: 20px;">Action</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><b>&lt;Option&gt;</b></p> <p>SV0703-102 Indicating unit : "bar"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0018-005 Oil-free Gr.B (For stainless steel body) and Water-free treatment</p> <p><b>&lt;Finish&gt;</b></p> <p>Body:</p> <p>Diaph. Case:</p> <p>Yoke:</p> <p>Paint:</p>																																																																																																																				
<p><b>&lt;Operating condition&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Fluid name</td> <td style="width: 35%;">P-301A/Bblowdown(cooling down [</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;">UNIT</td> </tr> <tr> <td></td> <td style="text-align: center;">MAX NOR MIN</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Flow rate</td> <td></td> <td></td> <td></td> <td></td> <td>l/h</td> </tr> <tr> <td>Inlet pressure</td> <td></td> <td></td> <td></td> <td></td> <td>barA</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td></td> <td>barA</td> </tr> <tr> <td>Diff. pressure</td> <td></td> <td></td> <td></td> <td></td> <td>bar</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">39</td> <td></td> <td></td> <td>bar</td> </tr> <tr> <td>Temperature</td> <td></td> <td></td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td></td> <td>dBa</td> </tr> <tr> <td>Calculated Cv</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td></td> <td>%</td> </tr> </table>	Fluid name	P-301A/Bblowdown(cooling down [				UNIT		MAX NOR MIN					Flow rate					l/h	Inlet pressure					barA	Outlet pressure					barA	Diff. pressure					bar	Shut-off press.		39			bar	Temperature					degC	Sp.Gr. (liq.)					water=1	Sp.Gr.(gas,vapor)					kg/m3[N]	Viscosity					cP	Flash					%	Velocity					m/s	S.P.L.					dBa	Calculated Cv						Travel					%	<p><b>&lt;Seat Leakage&gt;</b></p> <p style="text-align: center;">CLASS IV-S1 (SV0201-009)</p> <p><b>&lt;Note&gt;</b> Tokumi -</p> <p>Air piping: Stainless steel (316ss)</p> <p><b>&lt;Line spec&gt;</b></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Design press.</td> <td style="width: 20%;">39</td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;">barG</td> </tr> <tr> <td>Design temp.</td> <td>-196 ~65</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>1/2</td> <td style="text-align: center;">//</td> <td>1/2</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick.</td> <td>10S</td> <td style="text-align: center;">//</td> <td>2.11</td> <td>mm</td> </tr> </table>	Design press.	39			barG	Design temp.	-196 ~65			degC	Line size in/out	1/2	//	1/2	inch	Line Sch. / Thick.	10S	//	2.11	mm
Fluid name	P-301A/Bblowdown(cooling down [				UNIT																																																																																																																
	MAX NOR MIN																																																																																																																				
Flow rate					l/h																																																																																																																
Inlet pressure					barA																																																																																																																
Outlet pressure					barA																																																																																																																
Diff. pressure					bar																																																																																																																
Shut-off press.		39			bar																																																																																																																
Temperature					degC																																																																																																																
Sp.Gr. (liq.)					water=1																																																																																																																
Sp.Gr.(gas,vapor)					kg/m3[N]																																																																																																																
Viscosity					cP																																																																																																																
Flash					%																																																																																																																
Velocity					m/s																																																																																																																
S.P.L.					dBa																																																																																																																
Calculated Cv																																																																																																																					
Travel					%																																																																																																																
Design press.	39			barG																																																																																																																	
Design temp.	-196 ~65			degC																																																																																																																	
Line size in/out	1/2	//	1/2	inch																																																																																																																	
Line Sch. / Thick.	10S	//	2.11	mm																																																																																																																	