

1 2 3 4 5

改番 REV.	来 RECORD	歴 DATE	担当 BY	検閲 APPD.

A
B
C
D
E

130.5





Tag No. PRODUCT	MODEL DETECTOR FACTOR	DATE	TYPE 4X °C max FLUID TEMP.
○		CL. I, II, III, DIV. 1, GP. B, C, D, E, F, G	○
Honeywell		ASSOCIATED EQUIPMENT-APPAREILLAGE CONNEXE WARNING: SUBSTITUTION OF COMPONENTS MAY IMPAIR INTRINSIC SAFETY. AVERTISSEMENT: LA SUBSTITUTION DE COMPOSANTS PEUT COMPROMETTRE LA SÉCURITÉ INSEQUE.	
ELECTRODE CIRCUIT IS INTRINSICALLY SAFE AMBIENT TEMP 60°C max WORK PRESS. kPa max INSTALL PER DWG: 80390309			

図 DWG NO. 80395023

Detector
 Model NO. MGG17D
 MGG17F
 MGG17U

秘 YAMATAKE PROPRIETARY						名称 TITLE	
記入のない許容差 TOLERANCE UNLESS NOTED	表面粗さ SURFACE ROUGHNESS	設計 DR.	水鳥	05-2-10	-	-	NAME PLATE (MGG17)
~	~	検図 CHK.	鈴木	05-2-10	-	-	
材料 MATERIAL	鋭角除去 CHAMFER	認可 APPD.	川井	05-2-10	角谷	05-2-10	
AISI304 t0.5	処理 TREATMENT/FINISH	尺度 SCALE			組立図 ASS'Y ~		改番 REV.
		YAMATAKE		図番 DWG.NO. 80395023		00	シート SHT. A4