

MagneW PLUS Sanitary Detector (15~125mm, PFA liner)

Issued : Oct. 31, 2001	Page : 2-163
Effective : Oct. 31, 2001	UNIT : 1000YEN

MGS28U-I II III IV V VI VII VIII - IX- YW/Options (some options can be selected per each model.

List Price is the sum of the price of all selections made.

Option "Y" must be specified for Yamatake Version.

Option "W" must be specified for clamp.

Lead time: after receipt of order(s), ex-factory basis

Basic Model No.	MGS28U -	Diameter	Basic price							Lead time (Weeks)	
			15mm	25mm	40mm	50mm	80mm	100mm	125mm		
I	Diameter	15mm (0.5in.)	015	323							4
		25mm (1in.)	025		338						4
		40mm (1.5in.)	040			353					4
		50mm (2in.)	050				408				4
		80mm (3in.)	080					483			4
		100mm (4in.)	100						607		4
		125mm (5in.)	125							885	4

		Additional price								
		0	0	0	0	0	0	0		
II	Lining	PFA	P							
III	Pipe connection	IDF clamp	C1							
		Tri clamp	C2							
IV	Electrodes	SUS316L	L							
		Hastelloy C	C	36	36	36	36	36	36	
		Titanium	K	41	41	41	41	41	41	
V	Ferrule for welding	SUS 304	E	12	12	12	12	17	22	
		SUS 316L	S	30	30	30	30	35	40	
VI	Electrical connection/ Watertight gland	Integral type	1	0	0	0	0	0	0	
		Remote type	G1/2 internal thread/without watertight gland	2	0	0	0	0	0	0
			G1/2 internal thread/ with brass(Ni-plated) watertight	3	5	5	5	5	5	5
			G1/2 internal thread/with plastic watertight gland	4	2	2	2	2	2	2
			1/2NPT internal thread/without watertight	5	0	0	0	0	0	0
			CM20 internal thread/without watertight gland	6	0	0	0	0	0	0
			Pg13.5 internal thread/without watertight gland	7	0	0	0	0	0	0
			G1/2 internal thread/with SUS304 watertight gland	8	30	30	30	30	30	50
VII	Installation/ Wiring direction	Integral style	H	0	0	0	0	0	0	
		Remote style	Upstream side (Horizontal/Vertical piping)	A	0	0	0	0	0	0
			Downstream side (Horizontal/Vertical piping)	B	0	0	0	0	0	0
			Horizontal piping mounting Left side viewed from upstream	C	0	0	0	0	0	0
			Horizontal piping mounting Right side viewed from upstream	D	0	0	0	0	0	0
VIII	Calibration	Standard calibration	A	0	0	0	0	0	0	
		3 point (0, 50, 100%) w/ master converter		0	0	0	0	0	0	
		Others		Refer to table 104						
IX	Finish	Standard (corrosion-proof) finish	Z	0	0	0	0	0	0	

Remote style			Additional Price
Option	Y	Yamatake Version (Must be selected)	0
	A	Calibration certificate (sent to ordering location separately)	2
	B	Traceability Certificate	10
	K	Attaching the TAG number plate to the terminal box (remote type detector) Note 1	4
	L	Attaching the TAG number plate to the neck section Note 1	8
	V	Spare silicone gasket for ferrule (2 pcs.)	Refer to table 301
	W	with clamp (2 pcs.)	0

Integral style			Additional Price
Option	Y	Yamatake Version	0
	A	Calibration certificate (sent to ordering location)	2
	B	Traceability Certificate	10
	L	Attaching the TAG number plate to the neck section Note 1	8
	V	Spare silicone gasket for ferrule (2 pcs.)	Refer to table 301
	W	with clamp (2 pcs.)	0

Note 1. Must be selected for Tag No. requirement.

			Additional price	Lead time (weeks)
Calibration	P	3 point (0, 50, 100%) w/ master converter	0	
	Q	5 point (0, 25, 50, 75, 100%) w/ master converter	100	10
	J	2 point (0, 100%) w/ customer's specific converter	0	
	R	2 point (0, 50%) w/ master converter	0	
	E	5 point (0, 25, 50, 75, 100%) w/ customer's specific converter	100	10

		15mm	25mm	40mm	50mm	80mm	100mm	125mm
V	Spare silicone gasket for ferrule (2 pcs.)	7	7	8	9	10	12	15