

MTG15A-I II III IV V VI VII VIII IX - X XI - options (Some options can be selected per each model.)

Basic model No.	MTG15A-	Size	Wafer	Code	Basic Price (JP 1000 Yen)											Lead time (week)				
					2.5	5	10	15	25	40	50	65	80	100	150		200			
I	Size	2.5mm *1	002		595														4	
		5mm *1	005			595														4
		10mm *1	010				595													4
		15mm *1	015					595												4
		25mm	025						424											4
		40mm	040							440										4
		50mm	050								475									4
		65mm	065									580								4
		80mm	080										580							4
		100mm	100											645						4
150mm	150												1,020					4		
200mm	200													1,335				4		
					Additional Price (JP 1000 Yen)															
II	Lining	PFA	P		0															
III	Pipe connection	Wafer JIS10K	11		0															
		Wafer JIS16/20K	12		0															
		Wafer JIS30K	13		0															
		Wafer ANSI150	21		0															
		Wafer ANSI300	22		0															
		Wafer JPI150	61		0															
		Wafer JPI300	62		0															
		Flange JIS10K	J1		0	0	0	0	100	100	128	52	52	52	0	0				
		Flange JIS20K	J2		14	14	14	14	116	117	148	76	76	81	24	29			7	
		Flange JIS30K	J3		34	34	34	34	136	142	171	108	110	119	115	208			7	
		Flange JIS10K for 10mm size flange *2	J4		0	0	0												7	
		Flange JIS20K for 10mm size flange *2	J5		0	0	0												7	
		Flange ANSI150	A1		0	0	0	0	100	100	128	52	52	52	0	0			7	
		Flange ANSI300	A2		23	23	23	23	116	117	148	101	101	101	47	64			7	
Flange JPI150	P1		0	0	0	0	100	100	128	52	52	52	0	0			7			
Flange JPI300	P2		23	23	23	23	116	117	148	101	101	101	47	64			7			
IV	Electrode	SUS316L	L		0															
		Hastelloy C	C		36											5				
		Titanium	K		41											5				
		Zirconium	H		170											5				
		Tantalum	T		103											5				
		Nickel	N		150											5				
		Platinum-iridium	P		175											5				
V	Grounding ring	SUS316	S		0	0	0	0	0	0	0	0	0	0	0					
		Hastelloy C	C		57	57	57	57	57	57	57	72	72	93	134	170		5		
		Titanium	K		52	52	52	52	52	52	52	67	67	82	124	155		5		
		Zirconium	H		104	104	104	104	104	104	104	134	134	164	248	305		5		
		Tantalum	T		103	103	103	103	103	103	113	113	134	206	258		5			
		Platinum	P		149	149	149	149	149	149	149	160	160	185	256	338		5		
		VI	Wiring connection	G1/2 right side conduit w/ 1-piece flameproof gland	F		9													
G1/2 left side conduit w/ 1-piece flameproof gland	G				9															
G1/2 with 2-piece flameproof glands	H				18															
VII	Face to face dimension	Standard	A		0															
		Yamatake SMT3000 wafer type (40, 50, 80, 100mm)	S								42	40		44	71			6		
VIII	Installation/ Display direction	Horizontal piping mounting/ Display right side direction viewed from upstream	A																	
		Horizontal piping mounting/ Display left side direction viewed from upstream	B																	
		Horizontal piping mounting/ Display downstream side direction	C																	
		Horizontal piping mounting/ Display upstream side direction	D																	
		Vertical piping mounting/ Display right side of piping/Flow direction:Upward	E																	
		Vertical piping mounting/ Display left side of piping/Flow direction:Upward	F																	
IX	Calibration	Standard calibration (3 points 0, 50, 100%)	A																	
			-																	
X	Finish/paint	Standard paint	X		0															
		Corrosion-proof paint	2		10															
XI	Bolts/nuts	None	X		0															
		SUS304 bolts/nuts (for wafer style only)	2								5	5	5	5	5	20				
XII	Options	None	X		0															
		Test report	A		2															
		Traceability certificate	B		10															
		Material certificate (electrode/grounding ring)	C		45															
		Water free treatment	E		40															
		Oil free treatment	F		50															
		Gasket for plastic piping	G		10	10	10	10	10	14	19	24	35	45	80	120				
		All units (including Non SI units) available	H		5															
		Tropical treatment	J		52															
		with the Tag number plate on the converter housing *3	K		4															

Note \*1 Flange of size 2.5 to 15mm detector is 15 mm flange.  
\*2 Available for size 2.5 to 10 mm detector.  
\*3 Must be selected if tagging is required.