

Specification Sheet

<p>No.: 1 QTY: 1</p> <p>Tag no. 10-FV-045</p> <p>Service</p> <p>< Specification ></p> <p>Model HTS</p> <p>Description Top-Guided Single Seated Control Valves</p> <p>Valve size 3 inch</p> <p>Port size 3 inch</p> <p>Rated Cv 99</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE FACE</p> <p>Flow characteristic EQ%</p> <p>Bonnet type PLAIN</p> <p>Actuator HA4</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 2.8kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve 3-Way Solenoid Valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																								
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">Residue</th> <th style="text-align: center;">[</th> <th style="text-align: center;">LIQUID</th> <th style="text-align: center;">]</th> </tr> <tr> <th></th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th style="text-align: center;">UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td style="text-align: center;">102</td> <td></td> <td></td> <td style="text-align: center;">m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td style="text-align: center;">13.32</td> <td></td> <td></td> <td style="text-align: center;">kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td style="text-align: center;">kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td style="text-align: center;">7.38</td> <td></td> <td></td> <td style="text-align: center;">kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">18.0</td> <td></td> <td style="text-align: center;">kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td style="text-align: center;">151</td> <td></td> <td></td> <td style="text-align: center;">degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td style="text-align: center;">0.867</td> <td></td> <td></td> <td style="text-align: center;">water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td></td> <td style="text-align: center;">MW</td> </tr> <tr> <td>Viscosity</td> <td style="text-align: center;">4.77</td> <td></td> <td></td> <td style="text-align: center;">cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td style="text-align: center;">%</td> </tr> <tr> <td>Velocity</td> <td style="text-align: center;">6.21</td> <td></td> <td></td> <td style="text-align: center;">m/s</td> </tr> <tr> <td>S.P.L.</td> <td style="text-align: center;">85</td> <td></td> <td></td> <td style="text-align: center;">dBA</td> </tr> <tr> <td>Calculated Cv</td> <td style="text-align: center;">40.81</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td style="text-align: center;">73</td> <td></td> <td></td> <td style="text-align: center;">%</td> </tr> </tbody> </table>	Fluid name	Residue	[LIQUID]		MAX	NOR	MIN	UNIT	Flow rate	102			m3/h	Inlet pressure	13.32			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	7.38			kgf/cm2	Shut-off press.		18.0		kgf/cm2	Temperature	151			degC	Sp.Gr. (liq.)	0.867			water=1	Sp.Gr. (gas,vapor)				MW	Viscosity	4.77			cP	Flash				%	Velocity	6.21			m/s	S.P.L.	85			dBA	Calculated Cv	40.81				Travel	73			%	<p><Seat Leakage></p> <p style="text-align: center;">CLASS IV (SV0201-003)</p> <p><Note> Tokumi: V93-8666-00 - 1</p> <p>Existing Valve Prod No. 416-8299-1700</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Design press.</td> <td style="text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">/ inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">/ mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/ inch	Line Sch. / Thick	/ mm
Fluid name	Residue	[LIQUID]																																																																																					
	MAX	NOR	MIN	UNIT																																																																																					
Flow rate	102			m3/h																																																																																					
Inlet pressure	13.32			kgf/cm2A																																																																																					
Outlet pressure				kgf/cm2A																																																																																					
Diff. pressure	7.38			kgf/cm2																																																																																					
Shut-off press.		18.0		kgf/cm2																																																																																					
Temperature	151			degC																																																																																					
Sp.Gr. (liq.)	0.867			water=1																																																																																					
Sp.Gr. (gas,vapor)				MW																																																																																					
Viscosity	4.77			cP																																																																																					
Flash				%																																																																																					
Velocity	6.21			m/s																																																																																					
S.P.L.	85			dBA																																																																																					
Calculated Cv	40.81																																																																																								
Travel	73			%																																																																																					
Design press.	kPaG																																																																																								
Design temp.	degC																																																																																								
Line size in/out	/ inch																																																																																								
Line Sch. / Thick	/ mm																																																																																								

Specification Sheet

<p>No.: 2 QTY: 1</p> <p>Tag no. 10-FV-047</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1-1/2 inch</p> <p>Port size 1-1/2 inch</p> <p>Rated Cv 30</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type PLAIN</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply</p> <p>Spring range 0.2-1.0kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal</p> <p>Regurator</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve</p> <p style="padding-left: 20px;">Action</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																																												
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">Caustic Solution</th> <th colspan="3" style="text-align: center;">[LIQUID]</th> <th style="text-align: left;">UNIT</th> </tr> <tr> <th></th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>10.7</td> <td></td> <td></td> <td>m3/h</td> <td></td> </tr> <tr> <td>Inlet pressure</td> <td>3.98</td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Diff. pressure</td> <td>2.42</td> <td></td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">5.0</td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Temperature</td> <td></td> <td style="text-align: center;">40</td> <td></td> <td>degC</td> <td></td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>1.250</td> <td style="text-align: center;">1.250</td> <td></td> <td>water=1</td> <td></td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> <td></td> </tr> <tr> <td>Viscosity</td> <td>4.0</td> <td style="text-align: center;">4.0</td> <td></td> <td>cP</td> <td></td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> <tr> <td>Velocity</td> <td>2.6</td> <td></td> <td></td> <td>m/s</td> <td></td> </tr> <tr> <td>S.P.L.</td> <td>71</td> <td></td> <td></td> <td>dBA</td> <td></td> </tr> <tr> <td>Calculated Cv</td> <td>8.977</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> </tbody> </table>	Fluid name	Caustic Solution	[LIQUID]			UNIT		MAX	NOR	MIN			Flow rate	10.7			m3/h		Inlet pressure	3.98			kgf/cm2A		Outlet pressure				kgf/cm2A		Diff. pressure	2.42			kgf/cm2		Shut-off press.		5.0		kgf/cm2		Temperature		40		degC		Sp.Gr. (liq.)	1.250	1.250		water=1		Sp.Gr.(gas,vapor)				MW		Viscosity	4.0	4.0		cP		Flash				%		Velocity	2.6			m/s		S.P.L.	71			dBA		Calculated Cv	8.977					Travel				%		<p><Seat Leakage></p> <p><Note> Tokumi:V933-8666-0C - 2</p> <p>Existing Valve Prod No. 416-8299-1800</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Design press.</td> <td style="text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">/</td> </tr> <tr> <td></td> <td style="text-align: right;">inch</td> </tr> <tr> <td></td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/		inch		mm
Fluid name	Caustic Solution	[LIQUID]			UNIT																																																																																																								
	MAX	NOR	MIN																																																																																																										
Flow rate	10.7			m3/h																																																																																																									
Inlet pressure	3.98			kgf/cm2A																																																																																																									
Outlet pressure				kgf/cm2A																																																																																																									
Diff. pressure	2.42			kgf/cm2																																																																																																									
Shut-off press.		5.0		kgf/cm2																																																																																																									
Temperature		40		degC																																																																																																									
Sp.Gr. (liq.)	1.250	1.250		water=1																																																																																																									
Sp.Gr.(gas,vapor)				MW																																																																																																									
Viscosity	4.0	4.0		cP																																																																																																									
Flash				%																																																																																																									
Velocity	2.6			m/s																																																																																																									
S.P.L.	71			dBA																																																																																																									
Calculated Cv	8.977																																																																																																												
Travel				%																																																																																																									
Design press.	kPaG																																																																																																												
Design temp.	degC																																																																																																												
Line size in/out	/																																																																																																												
Line Sch. / Thick	/																																																																																																												
	inch																																																																																																												
	mm																																																																																																												

Specification Sheet

<p>No.: 3 QTY: 1</p> <p>Tag no. 10-HV-003</p> <p>Service</p> <p>< Specification ></p> <p>Model HTS</p> <p>Description Top-Guided Single Seated Control Valves</p> <p>Valve size 6 inch</p> <p>Port size 5 inch</p> <p>Rated Cv 275</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 Stellite Sheath</p> <p>Flow characteristic EQ%</p> <p>Bonnet type EXT-1 HIGH</p> <p>Actuator HA3</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Air fail open)</p> <p>Gland packing TK397</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																								
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Superheated Steam</th> <th>[STEAM]</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>MAX 3745</td> <td>NOR MIN</td> <td>kg/h</td> </tr> <tr> <td>Inlet pressure</td> <td>3.43</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>2.4</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>5.0</td> <td>kPa</td> </tr> <tr> <td>Temperature</td> <td>350</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.29</td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>117.9</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>74</td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Superheated Steam	[STEAM]	UNIT	Flow rate	MAX 3745	NOR MIN	kg/h	Inlet pressure	3.43		kgf/cm2A	Outlet pressure			kgf/cm2A	Diff. pressure	2.4		kgf/cm2	Shut-off press.		5.0	kPa	Temperature	350		degC	Sp.Gr. (liq.)			water=1	Sp.Gr. (gas,vapor)			MW	Viscosity			cP	Flash			%	Velocity	0.29		Mach	S.P.L.			dBA	Calculated Cv	117.9			Travel	74		%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 3</p> <p>Existing Valve Prod No. 416-8299-4200</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td></td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> <td>mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	Superheated Steam	[STEAM]	UNIT																																																																						
Flow rate	MAX 3745	NOR MIN	kg/h																																																																						
Inlet pressure	3.43		kgf/cm2A																																																																						
Outlet pressure			kgf/cm2A																																																																						
Diff. pressure	2.4		kgf/cm2																																																																						
Shut-off press.		5.0	kPa																																																																						
Temperature	350		degC																																																																						
Sp.Gr. (liq.)			water=1																																																																						
Sp.Gr. (gas,vapor)			MW																																																																						
Viscosity			cP																																																																						
Flash			%																																																																						
Velocity	0.29		Mach																																																																						
S.P.L.			dBA																																																																						
Calculated Cv	117.9																																																																								
Travel	74		%																																																																						
Design press.		kPaG																																																																							
Design temp.		degC																																																																							
Line size in/out	/	inch																																																																							
Line Sch. / Thick	/	mm																																																																							

Specification Sheet

<p>No.: 4 QTY: 1</p> <p>Tag no. 15-FV-007</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1-1/2 inch</p> <p>Port size 1 inch</p> <p>Rated Cv 15</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 Stellite Sheath</p> <p>Flow characteristic %C</p> <p>Bonnet type FIN</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V1290</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply</p> <p>Spring range 0.2-1.0kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal</p> <p>Regulator</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve</p> <p style="padding-left: 20px;">Action</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																																		
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Fluid name</td> <td style="width: 15%;">MP Steam</td> <td style="width: 15%;">MAX</td> <td style="width: 15%;">NOR</td> <td style="width: 15%;">MIN</td> <td style="width: 20%;">[STEAM]</td> </tr> <tr> <td>Flow rate</td> <td>610.5</td> <td></td> <td></td> <td></td> <td>kg/h</td> </tr> <tr> <td>Inlet pressure</td> <td>16.0</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>10</td> <td></td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td></td> <td>18.2</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>270</td> <td></td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td>0.02</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.11</td> <td></td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>3.521</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td></td> <td>%</td> </tr> </table>	Fluid name	MP Steam	MAX	NOR	MIN	[STEAM]	Flow rate	610.5				kg/h	Inlet pressure	16.0				kgf/cm2A	Outlet pressure					kgf/cm2A	Diff. pressure	10				kgf/cm2	Shut-off press.			18.2		kgf/cm2	Temperature	270				degC	Sp.Gr. (liq.)					water=1	Sp.Gr.(gas,vapor)					MW	Viscosity	0.02				cP	Flash					%	Velocity	0.11				Mach	S.P.L.					dBA	Calculated Cv	3.521					Travel					%	<p><Seat Leakage></p> <p style="text-align: center;">CLASS II (SV0201-007)</p> <p><Note> Tokumi: V93-8666-00 - 4</p> <p>Existing Valve Prod No. 416-8304-0200</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 40%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">// inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">// mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	// inch	Line Sch. / Thick	// mm
Fluid name	MP Steam	MAX	NOR	MIN	[STEAM]																																																																																														
Flow rate	610.5				kg/h																																																																																														
Inlet pressure	16.0				kgf/cm2A																																																																																														
Outlet pressure					kgf/cm2A																																																																																														
Diff. pressure	10				kgf/cm2																																																																																														
Shut-off press.			18.2		kgf/cm2																																																																																														
Temperature	270				degC																																																																																														
Sp.Gr. (liq.)					water=1																																																																																														
Sp.Gr.(gas,vapor)					MW																																																																																														
Viscosity	0.02				cP																																																																																														
Flash					%																																																																																														
Velocity	0.11				Mach																																																																																														
S.P.L.					dBA																																																																																														
Calculated Cv	3.521																																																																																																		
Travel					%																																																																																														
Design press.	kPaG																																																																																																		
Design temp.	degC																																																																																																		
Line size in/out	// inch																																																																																																		
Line Sch. / Thick	// mm																																																																																																		

Specification Sheet

<p>No.: 5 QTY: 1</p> <p>Tag no. 15-FV-019</p> <p>Service</p> <p>< Specification ></p> <p>Model HTS</p> <p>Description Top-Guided Single Seated Control Valves</p> <p>Valve size 3 inch</p> <p>Port size 2 inch</p> <p>Rated Cv 44</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 Stellite Sheath</p> <p>Flow characteristic %C</p> <p>Bonnet type EXT-1 HIGH</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing TK397</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 2.8kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regulator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																																												
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Fluid name</td> <td style="width: 20%;">Superheated Steam</td> <td style="width: 10%;"></td> <td style="width: 10%;">[STEAM]</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td>MAX</td> <td>NOR</td> <td>MIN</td> <td>UNIT</td> <td></td> </tr> <tr> <td>Flow rate</td> <td>484</td> <td></td> <td></td> <td>kg/h</td> <td></td> </tr> <tr> <td>Inlet pressure</td> <td>4.13</td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Diff. pressure</td> <td>2.8</td> <td></td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>5.0</td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Temperature</td> <td>350</td> <td></td> <td></td> <td>degC</td> <td></td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> <td></td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> <td></td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> <td></td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> <tr> <td>Velocity</td> <td>0.11</td> <td></td> <td></td> <td>Mach</td> <td></td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> <td></td> </tr> <tr> <td>Calculated Cv</td> <td>12.54</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> </table>	Fluid name	Superheated Steam		[STEAM]				MAX	NOR	MIN	UNIT		Flow rate	484			kg/h		Inlet pressure	4.13			kgf/cm2A		Outlet pressure				kgf/cm2A		Diff. pressure	2.8			kgf/cm2		Shut-off press.		5.0		kgf/cm2		Temperature	350			degC		Sp.Gr. (liq.)				water=1		Sp.Gr. (gas,vapor)				MW		Viscosity				cP		Flash				%		Velocity	0.11			Mach		S.P.L.				dBA		Calculated Cv	12.54					Travel				%		<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 5</p> <p>Existing Valve Prod No. 416-8304-0600</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 40%;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: center;">//</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: center;">//</td> </tr> <tr> <td></td> <td style="text-align: right;">inch</td> </tr> <tr> <td></td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	//	Line Sch. / Thick	//		inch		mm
Fluid name	Superheated Steam		[STEAM]																																																																																																										
	MAX	NOR	MIN	UNIT																																																																																																									
Flow rate	484			kg/h																																																																																																									
Inlet pressure	4.13			kgf/cm2A																																																																																																									
Outlet pressure				kgf/cm2A																																																																																																									
Diff. pressure	2.8			kgf/cm2																																																																																																									
Shut-off press.		5.0		kgf/cm2																																																																																																									
Temperature	350			degC																																																																																																									
Sp.Gr. (liq.)				water=1																																																																																																									
Sp.Gr. (gas,vapor)				MW																																																																																																									
Viscosity				cP																																																																																																									
Flash				%																																																																																																									
Velocity	0.11			Mach																																																																																																									
S.P.L.				dBA																																																																																																									
Calculated Cv	12.54																																																																																																												
Travel				%																																																																																																									
Design press.	kPaG																																																																																																												
Design temp.	degC																																																																																																												
Line size in/out	//																																																																																																												
Line Sch. / Thick	//																																																																																																												
	inch																																																																																																												
	mm																																																																																																												

Specification Sheet

<p>No.: 6 QTY: 1</p> <p>Tag no. 15-LV-005</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 3 inch</p> <p>Port size 3 inch</p> <p>Rated Cv 110</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE</p> <p>Flow characteristic</p> <p>Bonnet type</p> <p>Actuator HA3</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																								
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Fluid name</td> <td style="width: 20%;">HVGO</td> <td style="width: 20%;"></td> <td style="width: 20%;">[LIQUID]</td> </tr> <tr> <td></td> <td>MAX</td> <td>NOR</td> <td>MIN</td> </tr> <tr> <td>Flow rate</td> <td>75.8</td> <td></td> <td>UNIT</td> </tr> <tr> <td>Inlet pressure</td> <td>15.52</td> <td></td> <td>m3/h</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>2.1</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>22.0</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>210</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.823</td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td>3.0</td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>4.61</td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td>65</td> <td></td> <td>dBa</td> </tr> <tr> <td>Calculated Cv</td> <td>55.39</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td>%</td> </tr> </table>	Fluid name	HVGO		[LIQUID]		MAX	NOR	MIN	Flow rate	75.8		UNIT	Inlet pressure	15.52		m3/h	Outlet pressure			kgf/cm2A	Diff. pressure	2.1		kgf/cm2	Shut-off press.		22.0	kgf/cm2	Temperature	210		degC	Sp.Gr. (liq.)	0.823		water=1	Sp.Gr.(gas,vapor)			MW	Viscosity	3.0		cP	Flash			%	Velocity	4.61		m/s	S.P.L.	65		dBa	Calculated Cv	55.39			Travel			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 6</p> <p>Existing Valve Prod No. 416-8304-1500</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 40%;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/
Fluid name	HVGO		[LIQUID]																																																																						
	MAX	NOR	MIN																																																																						
Flow rate	75.8		UNIT																																																																						
Inlet pressure	15.52		m3/h																																																																						
Outlet pressure			kgf/cm2A																																																																						
Diff. pressure	2.1		kgf/cm2																																																																						
Shut-off press.		22.0	kgf/cm2																																																																						
Temperature	210		degC																																																																						
Sp.Gr. (liq.)	0.823		water=1																																																																						
Sp.Gr.(gas,vapor)			MW																																																																						
Viscosity	3.0		cP																																																																						
Flash			%																																																																						
Velocity	4.61		m/s																																																																						
S.P.L.	65		dBa																																																																						
Calculated Cv	55.39																																																																								
Travel			%																																																																						
Design press.	kPaG																																																																								
Design temp.	degC																																																																								
Line size in/out	/																																																																								
Line Sch. / Thick	/																																																																								

Specification Sheet

<p>No.: 7 QTY: 1</p> <p>Tag no. 15-LV-006</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1-1/2 inch</p> <p>Port size 1-1/2 inch</p> <p>Rated Cv 30</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH11</p> <p>Trim material SUS316 Stellite Sheath</p> <p>Flow characteristic %C</p> <p>Bonnet type FIN</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing TK397</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 1.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regulator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																																		
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Fluid name</td> <td style="width: 15%;">HC Liquid</td> <td style="width: 15%;">NOR</td> <td style="width: 15%;">MIN</td> <td style="width: 15%;">[LIQUID]</td> <td style="width: 20%;"></td> </tr> <tr> <td>Flow rate</td> <td>MAX 27.0</td> <td></td> <td></td> <td>UNIT m3/h</td> <td></td> </tr> <tr> <td>Inlet pressure</td> <td>23.5</td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Diff. pressure</td> <td>7.6</td> <td></td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>31.0</td> <td></td> <td>kPa</td> <td></td> </tr> <tr> <td>Temperature</td> <td>386</td> <td></td> <td></td> <td>degC</td> <td></td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.721</td> <td></td> <td></td> <td>water=1</td> <td></td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> <td></td> </tr> <tr> <td>Viscosity</td> <td>0.6</td> <td></td> <td></td> <td>cP</td> <td></td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> <tr> <td>Velocity</td> <td>6.58</td> <td></td> <td></td> <td>m/s</td> <td></td> </tr> <tr> <td>S.P.L.</td> <td>64</td> <td></td> <td></td> <td>dBA</td> <td></td> </tr> <tr> <td>Calculated Cv</td> <td>9.708</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> </table>	Fluid name	HC Liquid	NOR	MIN	[LIQUID]		Flow rate	MAX 27.0			UNIT m3/h		Inlet pressure	23.5			kgf/cm2A		Outlet pressure				kgf/cm2A		Diff. pressure	7.6			kgf/cm2		Shut-off press.		31.0		kPa		Temperature	386			degC		Sp.Gr. (liq.)	0.721			water=1		Sp.Gr.(gas,vapor)				MW		Viscosity	0.6			cP		Flash				%		Velocity	6.58			m/s		S.P.L.	64			dBA		Calculated Cv	9.708					Travel				%		<p><Seat Leakage></p> <p style="text-align: center;">CLASS II (SV0201-007)</p> <p><Note> Tokumi: V93-8666-00 - 7</p> <p>SV0801-EXX : Material Certification in English on Valve Body, Bonnet and Lower Cover.</p> <p>Existing Valve Prod No. 416-8304-1600</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 40%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">/ / inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">/ / mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/ / inch	Line Sch. / Thick	/ / mm
Fluid name	HC Liquid	NOR	MIN	[LIQUID]																																																																																															
Flow rate	MAX 27.0			UNIT m3/h																																																																																															
Inlet pressure	23.5			kgf/cm2A																																																																																															
Outlet pressure				kgf/cm2A																																																																																															
Diff. pressure	7.6			kgf/cm2																																																																																															
Shut-off press.		31.0		kPa																																																																																															
Temperature	386			degC																																																																																															
Sp.Gr. (liq.)	0.721			water=1																																																																																															
Sp.Gr.(gas,vapor)				MW																																																																																															
Viscosity	0.6			cP																																																																																															
Flash				%																																																																																															
Velocity	6.58			m/s																																																																																															
S.P.L.	64			dBA																																																																																															
Calculated Cv	9.708																																																																																																		
Travel				%																																																																																															
Design press.	kPaG																																																																																																		
Design temp.	degC																																																																																																		
Line size in/out	/ / inch																																																																																																		
Line Sch. / Thick	/ / mm																																																																																																		

Specification Sheet

<p>No.: 8 QTY: 1</p> <p>Tag no. 15-HV-001</p> <p>Service</p> <p>< Specification ></p> <p>Model HTS</p> <p>Description Top-Guided Single Seated Control Valves</p> <p>Valve size 2 inch</p> <p>Port size 1-1/2 inch</p> <p>Rated Cv 24</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 Stellite Sheath</p> <p>Flow characteristic EQ%</p> <p>Bonnet type EXT-1 HIGH</p> <p>Actuator HA2</p> <p>Manual operator TOP</p> <p>Valve action DIRECT(Air fail open)</p> <p>Gland packing TK397</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																												
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">Steam</th> <th style="text-align: center;">[</th> <th style="text-align: left;">STEAM</th> <th style="text-align: center;">]</th> </tr> <tr> <th></th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th style="text-align: left;">UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td style="text-align: center;">339</td> <td></td> <td></td> <td>kg/h</td> </tr> <tr> <td>Inlet pressure</td> <td style="text-align: center;">3.50</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td style="text-align: center;">2.5</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">5.0</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td style="text-align: center;">350</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas, vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td style="text-align: center;">0.24</td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td style="text-align: center;">10.45</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td style="text-align: center;">74</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Steam	[STEAM]		MAX	NOR	MIN	UNIT	Flow rate	339			kg/h	Inlet pressure	3.50			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	2.5			kgf/cm2	Shut-off press.		5.0		kgf/cm2	Temperature	350			degC	Sp.Gr. (liq.)				water=1	Sp.Gr. (gas, vapor)				MW	Viscosity				cP	Flash				%	Velocity	0.24			Mach	S.P.L.				dBA	Calculated Cv	10.45				Travel	74			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 8</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 20%;"></td> <td style="width: 20%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: center;">/</td> <td style="text-align: right;">inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: center;">/</td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	Steam	[STEAM]																																																																																									
	MAX	NOR	MIN	UNIT																																																																																									
Flow rate	339			kg/h																																																																																									
Inlet pressure	3.50			kgf/cm2A																																																																																									
Outlet pressure				kgf/cm2A																																																																																									
Diff. pressure	2.5			kgf/cm2																																																																																									
Shut-off press.		5.0		kgf/cm2																																																																																									
Temperature	350			degC																																																																																									
Sp.Gr. (liq.)				water=1																																																																																									
Sp.Gr. (gas, vapor)				MW																																																																																									
Viscosity				cP																																																																																									
Flash				%																																																																																									
Velocity	0.24			Mach																																																																																									
S.P.L.				dBA																																																																																									
Calculated Cv	10.45																																																																																												
Travel	74			%																																																																																									
Design press.		kPaG																																																																																											
Design temp.		degC																																																																																											
Line size in/out	/	inch																																																																																											
Line Sch. / Thick	/	mm																																																																																											

Specification Sheet

<p>No.: 9 QTY: 1</p> <p>Tag no. 15-PDV-005</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=6.3 inch</p> <p>Rated Cv</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE FACE</p> <p>Flow characteristic EQ%</p> <p>Bonnet type EXT-1 HIGH</p> <p>Actuator HA2</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Air fail open)</p> <p>Gland packing V1290</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																			
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Fluid name</td> <td style="width: 20%;">MP Steam</td> <td style="width: 20%;">NOR</td> <td style="width: 20%;">MIN</td> <td style="width: 20%;">[STEAM]</td> </tr> <tr> <td>Flow rate</td> <td>MAX 574</td> <td></td> <td></td> <td>UNIT kg/h</td> </tr> <tr> <td>Inlet pressure</td> <td>16.02</td> <td>16.02</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>6.8</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>18.2</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>270</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas, vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.15</td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>3.502</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </table>	Fluid name	MP Steam	NOR	MIN	[STEAM]	Flow rate	MAX 574			UNIT kg/h	Inlet pressure	16.02	16.02		kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	6.8			kgf/cm2	Shut-off press.		18.2		kgf/cm2	Temperature	270			degC	Sp.Gr. (liq.)				water=1	Sp.Gr. (gas, vapor)				MW	Viscosity				cP	Flash				%	Velocity	0.15			Mach	S.P.L.				dBA	Calculated Cv	3.502				Travel				%	<p><Seat Leakage></p> <p style="text-align: center;">CLASS IV (SV0201-003)</p> <p><Note> Tokumi: V93-8666-00 - 9</p> <p>Existing Valve Prod No. 416-8304-1200</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 40%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">/ inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">/ mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/ inch	Line Sch. / Thick	/ mm
Fluid name	MP Steam	NOR	MIN	[STEAM]																																																																																
Flow rate	MAX 574			UNIT kg/h																																																																																
Inlet pressure	16.02	16.02		kgf/cm2A																																																																																
Outlet pressure				kgf/cm2A																																																																																
Diff. pressure	6.8			kgf/cm2																																																																																
Shut-off press.		18.2		kgf/cm2																																																																																
Temperature	270			degC																																																																																
Sp.Gr. (liq.)				water=1																																																																																
Sp.Gr. (gas, vapor)				MW																																																																																
Viscosity				cP																																																																																
Flash				%																																																																																
Velocity	0.15			Mach																																																																																
S.P.L.				dBA																																																																																
Calculated Cv	3.502																																																																																			
Travel				%																																																																																
Design press.	kPaG																																																																																			
Design temp.	degC																																																																																			
Line size in/out	/ inch																																																																																			
Line Sch. / Thick	/ mm																																																																																			

Specification Sheet

<p>No.: 10 QTY: 1</p> <p>Tag no. 29-LV-005</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 3 inch</p> <p>Port size 3 inch</p> <p>Rated Cv 110</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type PLAIN</p> <p>Actuator HA3</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																								
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Water</th> <th></th> <th>[WATER]</th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>62.3</td> <td></td> <td>m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>8.5</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>0.7</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>12.5</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>82</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.9707</td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>3.79</td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td>61</td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>85.64</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Water		[WATER]		MAX	NOR	MIN	Flow rate	62.3		m3/h	Inlet pressure	8.5		kgf/cm2A	Outlet pressure			kgf/cm2A	Diff. pressure	0.7		kgf/cm2	Shut-off press.		12.5	kgf/cm2	Temperature	82		degC	Sp.Gr. (liq.)	0.9707		water=1	Sp.Gr.(gas,vapor)			MW	Viscosity			cP	Flash			%	Velocity	3.79		m/s	S.P.L.	61		dBA	Calculated Cv	85.64			Travel			%	<p><Seat Leakage></p> <p>CLASS II (SV0201-007)</p> <p><Note> Tokumi: V93-8666-00 - 10</p> <p>Existing Valve Prod No. 416-8319-1500</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	inch	Line Sch. / Thick	mm
Fluid name	Water		[WATER]																																																																						
	MAX	NOR	MIN																																																																						
Flow rate	62.3		m3/h																																																																						
Inlet pressure	8.5		kgf/cm2A																																																																						
Outlet pressure			kgf/cm2A																																																																						
Diff. pressure	0.7		kgf/cm2																																																																						
Shut-off press.		12.5	kgf/cm2																																																																						
Temperature	82		degC																																																																						
Sp.Gr. (liq.)	0.9707		water=1																																																																						
Sp.Gr.(gas,vapor)			MW																																																																						
Viscosity			cP																																																																						
Flash			%																																																																						
Velocity	3.79		m/s																																																																						
S.P.L.	61		dBA																																																																						
Calculated Cv	85.64																																																																								
Travel			%																																																																						
Design press.	kPaG																																																																								
Design temp.	degC																																																																								
Line size in/out	inch																																																																								
Line Sch. / Thick	mm																																																																								

Specification Sheet

<p>No.: 11 QTY: 1</p> <p>Tag no. 29-PV-001A</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=4.0 inch</p> <p>Rated Cv 4.0</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material MONEL K-500</p> <p>Flow characteristic EQ%</p> <p>Bonnet type PLAIN</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 400</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.6-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																							
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Acid Gas</th> <th></th> <th>[GAS]</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>MAX</td> <td>NOR</td> <td>MIN</td> <td>m3/h[N]</td> </tr> <tr> <td>Inlet pressure</td> <td>33.6</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td>1.73</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>0.2</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>3.0</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>85</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td>1.05</td> <td></td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.03</td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>2.61</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>88</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Acid Gas		[GAS]	UNIT	Flow rate	MAX	NOR	MIN	m3/h[N]	Inlet pressure	33.6			kgf/cm2A	Outlet pressure	1.73			kgf/cm2A	Diff. pressure	0.2			kgf/cm2	Shut-off press.		3.0		kgf/cm2	Temperature	85			degC	Sp.Gr. (liq.)				water=1	Sp.Gr. (gas,vapor)	1.05			kg/m3[N]	Viscosity				cP	Flash				%	Velocity	0.03			Mach	S.P.L.				dBA	Calculated Cv	2.61				Travel	88			%	<p><Seat Leakage></p> <p>CLASS IV (SV0201-003)</p> <p><Note> Tokumi: V93-8666-00 - 11</p> <p>Existing Valve Prod No. 416-8319-0500</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td></td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> <td>mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	Acid Gas		[GAS]	UNIT																																																																																				
Flow rate	MAX	NOR	MIN	m3/h[N]																																																																																				
Inlet pressure	33.6			kgf/cm2A																																																																																				
Outlet pressure	1.73			kgf/cm2A																																																																																				
Diff. pressure	0.2			kgf/cm2																																																																																				
Shut-off press.		3.0		kgf/cm2																																																																																				
Temperature	85			degC																																																																																				
Sp.Gr. (liq.)				water=1																																																																																				
Sp.Gr. (gas,vapor)	1.05			kg/m3[N]																																																																																				
Viscosity				cP																																																																																				
Flash				%																																																																																				
Velocity	0.03			Mach																																																																																				
S.P.L.				dBA																																																																																				
Calculated Cv	2.61																																																																																							
Travel	88			%																																																																																				
Design press.		kPaG																																																																																						
Design temp.		degC																																																																																						
Line size in/out	/	inch																																																																																						
Line Sch. / Thick	/	mm																																																																																						

Specification Sheet

<p>No.: 12 QTY: 1</p> <p>Tag no. 29-PV-002A</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=4.0 inch</p> <p>Rated Cv 4.0</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material MONEL K-500</p> <p>Flow characteristic EQ%</p> <p>Bonnet type</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 400</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.6-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																							
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Acid Gas</th> <th></th> <th>[GAS]</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>MAX</td> <td>NOR</td> <td>MIN</td> <td>m3/h[N]</td> </tr> <tr> <td>Inlet pressure</td> <td>1.73</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>0.2</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>3.0</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>85</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td>1.020</td> <td></td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.03</td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>2.297</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>85</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Acid Gas		[GAS]	UNIT	Flow rate	MAX	NOR	MIN	m3/h[N]	Inlet pressure	1.73			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	0.2			kgf/cm2	Shut-off press.		3.0		kgf/cm2	Temperature	85			degC	Sp.Gr. (liq.)				water=1	Sp.Gr.(gas,vapor)	1.020			kg/m3[N]	Viscosity				cP	Flash				%	Velocity	0.03			Mach	S.P.L.				dBA	Calculated Cv	2.297				Travel	85			%	<p><Seat Leakage></p> <p>CLASS IV (SV0201-003)</p> <p><Note> Tokumi: V93-8666-00 - 12</p> <p>Existing Valve Prod No. 416-8319-0700</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td></td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> <td>mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	Acid Gas		[GAS]	UNIT																																																																																				
Flow rate	MAX	NOR	MIN	m3/h[N]																																																																																				
Inlet pressure	1.73			kgf/cm2A																																																																																				
Outlet pressure				kgf/cm2A																																																																																				
Diff. pressure	0.2			kgf/cm2																																																																																				
Shut-off press.		3.0		kgf/cm2																																																																																				
Temperature	85			degC																																																																																				
Sp.Gr. (liq.)				water=1																																																																																				
Sp.Gr.(gas,vapor)	1.020			kg/m3[N]																																																																																				
Viscosity				cP																																																																																				
Flash				%																																																																																				
Velocity	0.03			Mach																																																																																				
S.P.L.				dBA																																																																																				
Calculated Cv	2.297																																																																																							
Travel	85			%																																																																																				
Design press.		kPaG																																																																																						
Design temp.		degC																																																																																						
Line size in/out	/	inch																																																																																						
Line Sch. / Thick	/	mm																																																																																						

Specification Sheet

<p>No.: 13 QTY: 1</p> <p>Tag no. 11-LV-007</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 2 inch</p> <p>Port size 2 inch</p> <p>Rated Cv 50</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type PLAIN</p> <p>Actuator VA2</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																												
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>LPG</th> <th></th> <th>[LIQUID]</th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>22.3</td> <td></td> <td>m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>24.87</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>0.8</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>28.5</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>40</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.5</td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas, vapor)</td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td>0.11</td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>3.05</td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td>53</td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>20.58</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	LPG		[LIQUID]		MAX	NOR	MIN	Flow rate	22.3		m3/h	Inlet pressure	24.87		kgf/cm2A	Outlet pressure			kgf/cm2A	Diff. pressure	0.8		kgf/cm2	Shut-off press.		28.5	kgf/cm2	Temperature	40		degC	Sp.Gr. (liq.)	0.5		water=1	Sp.Gr. (gas, vapor)			MW	Viscosity	0.11		cP	Flash			%	Velocity	3.05		m/s	S.P.L.	53		dBA	Calculated Cv	20.58			Travel			%	<p><Seat Leakage></p> <p>CLASS II (SV0201-007)</p> <p><Note> Tokumi: V93-8666-00 - 13</p> <p>Existing Valve Prod No. 416-8300-2300</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td></td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> <td>mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	LPG		[LIQUID]																																																																										
	MAX	NOR	MIN																																																																										
Flow rate	22.3		m3/h																																																																										
Inlet pressure	24.87		kgf/cm2A																																																																										
Outlet pressure			kgf/cm2A																																																																										
Diff. pressure	0.8		kgf/cm2																																																																										
Shut-off press.		28.5	kgf/cm2																																																																										
Temperature	40		degC																																																																										
Sp.Gr. (liq.)	0.5		water=1																																																																										
Sp.Gr. (gas, vapor)			MW																																																																										
Viscosity	0.11		cP																																																																										
Flash			%																																																																										
Velocity	3.05		m/s																																																																										
S.P.L.	53		dBA																																																																										
Calculated Cv	20.58																																																																												
Travel			%																																																																										
Design press.		kPaG																																																																											
Design temp.		degC																																																																											
Line size in/out	/	inch																																																																											
Line Sch. / Thick	/	mm																																																																											

Specification Sheet

<p>No.: 14 QTY: 1</p> <p>Tag no. 11-PV-002A</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1-1/2 inch</p> <p>Port size 1-1/2 inch</p> <p>Rated Cv 30</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type PLAIN</p> <p>Actuator VA2</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.6-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																								
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>HC</th> <th></th> <th>[GAS]</th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>387</td> <td></td> <td>UNIT m3/h[N]</td> </tr> <tr> <td>Inlet pressure</td> <td>2.53</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>1.00</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>3.0</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>40</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td>kg/m3</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td>2.295</td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.27</td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>16.66</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	HC		[GAS]		MAX	NOR	MIN	Flow rate	387		UNIT m3/h[N]	Inlet pressure	2.53		kgf/cm2A	Outlet pressure			kgf/cm2A	Diff. pressure	1.00		kgf/cm2	Shut-off press.		3.0	kgf/cm2	Temperature	40		degC	Sp.Gr. (liq.)			kg/m3	Sp.Gr.(gas,vapor)	2.295		kg/m3[N]	Viscosity			cP	Flash			%	Velocity	0.27		Mach	S.P.L.			dBA	Calculated Cv	16.66			Travel			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 14</p> <p>Existing Valve Prod No. 416-8300-0900</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/
Fluid name	HC		[GAS]																																																																						
	MAX	NOR	MIN																																																																						
Flow rate	387		UNIT m3/h[N]																																																																						
Inlet pressure	2.53		kgf/cm2A																																																																						
Outlet pressure			kgf/cm2A																																																																						
Diff. pressure	1.00		kgf/cm2																																																																						
Shut-off press.		3.0	kgf/cm2																																																																						
Temperature	40		degC																																																																						
Sp.Gr. (liq.)			kg/m3																																																																						
Sp.Gr.(gas,vapor)	2.295		kg/m3[N]																																																																						
Viscosity			cP																																																																						
Flash			%																																																																						
Velocity	0.27		Mach																																																																						
S.P.L.			dBA																																																																						
Calculated Cv	16.66																																																																								
Travel			%																																																																						
Design press.	kPaG																																																																								
Design temp.	degC																																																																								
Line size in/out	/																																																																								
Line Sch. / Thick	/																																																																								

Specification Sheet

<p>No.: 15 QTY: 1</p> <p>Tag no. 11-PDV-014</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1-1/2 inch</p> <p>Port size 1 inch</p> <p>Rated Cv 13</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE FACE</p> <p>Flow characteristic %C</p> <p>Bonnet type FIN</p> <p>Actuator VA2</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V1290</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply</p> <p>Spring range 0.2-1.0kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal Explosion-proof Signal</p> <p>Regurator Regulator 2</p> <p>Limit Switch Action</p> <p>Solenoid valve Action Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																												
<p><Operating condition></p> <table border="1"> <tr> <td>Fluid name</td> <td>MP Steam</td> <td></td> <td>[STEAM]</td> </tr> <tr> <td></td> <td>MAX</td> <td>NOR</td> <td>MIN</td> </tr> <tr> <td>Flow rate</td> <td>774</td> <td></td> <td>kg/h</td> </tr> <tr> <td>Inlet pressure</td> <td>16.03</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>7.0</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>18.2</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>270</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.09</td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>4.671</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td>%</td> </tr> </table>	Fluid name	MP Steam		[STEAM]		MAX	NOR	MIN	Flow rate	774		kg/h	Inlet pressure	16.03		kgf/cm2A	Outlet pressure			kgf/cm2A	Diff. pressure	7.0		kgf/cm2	Shut-off press.		18.2	kgf/cm2	Temperature	270		degC	Sp.Gr. (liq.)			water=1	Sp.Gr.(gas,vapor)			MW	Viscosity			cP	Flash			%	Velocity	0.09		Mach	S.P.L.			dBA	Calculated Cv	4.671			Travel			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 15 Existing Valve Prod No. 416-8300-1800</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td></td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> <td>mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	MP Steam		[STEAM]																																																																										
	MAX	NOR	MIN																																																																										
Flow rate	774		kg/h																																																																										
Inlet pressure	16.03		kgf/cm2A																																																																										
Outlet pressure			kgf/cm2A																																																																										
Diff. pressure	7.0		kgf/cm2																																																																										
Shut-off press.		18.2	kgf/cm2																																																																										
Temperature	270		degC																																																																										
Sp.Gr. (liq.)			water=1																																																																										
Sp.Gr.(gas,vapor)			MW																																																																										
Viscosity			cP																																																																										
Flash			%																																																																										
Velocity	0.09		Mach																																																																										
S.P.L.			dBA																																																																										
Calculated Cv	4.671																																																																												
Travel			%																																																																										
Design press.		kPaG																																																																											
Design temp.		degC																																																																											
Line size in/out	/	inch																																																																											
Line Sch. / Thick	/	mm																																																																											

Specification Sheet

<p>No.: 16 QTY: 1</p> <p>Tag no. 12-PV-007</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=4.0 inch</p> <p>Rated Cv 4.0</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic EQ%</p> <p>Bonnet type PLAIN</p> <p>Actuator HA2</p> <p>Manual operator SIDE</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply</p> <p>Spring range 0.2-1.0kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal</p> <p>Explosion-proof</p> <p>Signal</p> <p>Regurator</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																								
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Fuel Oil</th> <th></th> <th>[LIQUID]</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>MAX 3.60</td> <td>NOR</td> <td>UNIT m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>15.02</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>7.8</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>14.0</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>70</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.995</td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>1.97</td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td>70</td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>1.501</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>73</td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Fuel Oil		[LIQUID]	Flow rate	MAX 3.60	NOR	UNIT m3/h	Inlet pressure	15.02		kgf/cm2A	Outlet pressure			kgf/cm2A	Diff. pressure	7.8		kgf/cm2	Shut-off press.		14.0	kgf/cm2	Temperature	70		degC	Sp.Gr. (liq.)	0.995		water=1	Sp.Gr.(gas,vapor)			MW	Viscosity			cP	Flash			%	Velocity	1.97		m/s	S.P.L.	70		dBA	Calculated Cv	1.501			Travel	73		%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 16</p> <p>Existing Valve Prod No. 416-8301-1200</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td></td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> <td>inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> <td>mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	Fuel Oil		[LIQUID]																																																																						
Flow rate	MAX 3.60	NOR	UNIT m3/h																																																																						
Inlet pressure	15.02		kgf/cm2A																																																																						
Outlet pressure			kgf/cm2A																																																																						
Diff. pressure	7.8		kgf/cm2																																																																						
Shut-off press.		14.0	kgf/cm2																																																																						
Temperature	70		degC																																																																						
Sp.Gr. (liq.)	0.995		water=1																																																																						
Sp.Gr.(gas,vapor)			MW																																																																						
Viscosity			cP																																																																						
Flash			%																																																																						
Velocity	1.97		m/s																																																																						
S.P.L.	70		dBA																																																																						
Calculated Cv	1.501																																																																								
Travel	73		%																																																																						
Design press.		kPaG																																																																							
Design temp.		degC																																																																							
Line size in/out	/	inch																																																																							
Line Sch. / Thick	/	mm																																																																							

Specification Sheet

<p>No.: 18 QTY: 1</p> <p>Tag no. 12-PDV-020</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=10 inch</p> <p>Rated Cv 10</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE FACE</p> <p>Flow characteristic EQ%</p> <p>Bonnet type</p> <p>Actuator HA2</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Air fail open)</p> <p>Gland packing V1290</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																																								
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Fluid name</td> <td style="width: 20%;">MP Steam</td> <td style="width: 10%;"></td> <td style="width: 10%;">[STEAM]</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td>MAX</td> <td>NOR</td> <td>MIN</td> <td>UNIT</td> <td></td> </tr> <tr> <td>Flow rate</td> <td>511</td> <td></td> <td></td> <td>kg/h</td> <td></td> </tr> <tr> <td>Inlet pressure</td> <td>16.01</td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Diff. pressure</td> <td>6.8</td> <td></td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>18.2</td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Temperature</td> <td>270</td> <td></td> <td></td> <td>degC</td> <td></td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> <td></td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> <td></td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> <td></td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> <tr> <td>Velocity</td> <td>0.13</td> <td></td> <td></td> <td>Mach</td> <td></td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dba</td> <td></td> </tr> <tr> <td>Calculated Cv</td> <td>3.119</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>68</td> <td></td> <td></td> <td>%</td> <td></td> </tr> </table>	Fluid name	MP Steam		[STEAM]				MAX	NOR	MIN	UNIT		Flow rate	511			kg/h		Inlet pressure	16.01			kgf/cm2A		Outlet pressure				kgf/cm2A		Diff. pressure	6.8			kgf/cm2		Shut-off press.		18.2		kgf/cm2		Temperature	270			degC		Sp.Gr. (liq.)				water=1		Sp.Gr.(gas,vapor)				MW		Viscosity				cP		Flash				%		Velocity	0.13			Mach		S.P.L.				dba		Calculated Cv	3.119					Travel	68			%		<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 18</p> <p>Existing Valve Prod No. 416-8301-1900</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 40%;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/ / inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/ / mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/ / inch	Line Sch. / Thick	/ / mm
Fluid name	MP Steam		[STEAM]																																																																																																						
	MAX	NOR	MIN	UNIT																																																																																																					
Flow rate	511			kg/h																																																																																																					
Inlet pressure	16.01			kgf/cm2A																																																																																																					
Outlet pressure				kgf/cm2A																																																																																																					
Diff. pressure	6.8			kgf/cm2																																																																																																					
Shut-off press.		18.2		kgf/cm2																																																																																																					
Temperature	270			degC																																																																																																					
Sp.Gr. (liq.)				water=1																																																																																																					
Sp.Gr.(gas,vapor)				MW																																																																																																					
Viscosity				cP																																																																																																					
Flash				%																																																																																																					
Velocity	0.13			Mach																																																																																																					
S.P.L.				dba																																																																																																					
Calculated Cv	3.119																																																																																																								
Travel	68			%																																																																																																					
Design press.	kPaG																																																																																																								
Design temp.	degC																																																																																																								
Line size in/out	/ / inch																																																																																																								
Line Sch. / Thick	/ / mm																																																																																																								

Specification Sheet

<p>No.: 19 QTY: 1</p> <p>Tag no. 12-PDV-038</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=4.0 inch</p> <p>Rated Cv 4.0</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS304 STELLITE FACE</p> <p>Flow characteristic EQ%</p> <p>Bonnet type EXT-1 HIGH</p> <p>Actuator HA2</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Air fail open)</p> <p>Gland packing V1290</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																							
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: center;">MP Steam</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th style="text-align: center;">[STEAM]</th> </tr> <tr> <th style="text-align: left;">Flow rate</th> <th style="text-align: center;">MAX</th> <th></th> <th></th> <th style="text-align: center;">UNIT</th> </tr> </thead> <tbody> <tr> <td>Inlet pressure</td> <td style="text-align: center;">232</td> <td></td> <td></td> <td style="text-align: center;">kg/h</td> </tr> <tr> <td>Outlet pressure</td> <td style="text-align: center;">16.01</td> <td style="text-align: center;">16.01</td> <td></td> <td style="text-align: center;">kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td style="text-align: center;">6.8</td> <td style="text-align: center;">6.8</td> <td></td> <td style="text-align: center;">kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">18.2</td> <td></td> <td style="text-align: center;">kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td style="text-align: center;">270</td> <td></td> <td></td> <td style="text-align: center;">degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td style="text-align: center;">water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td></td> <td style="text-align: center;">MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td style="text-align: center;">cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td style="text-align: center;">%</td> </tr> <tr> <td>Velocity</td> <td style="text-align: center;">0.06</td> <td></td> <td></td> <td style="text-align: center;">Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td style="text-align: center;">dBA</td> </tr> <tr> <td>Calculated Cv</td> <td style="text-align: center;">1.416</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td style="text-align: center;">72</td> <td></td> <td></td> <td style="text-align: center;">%</td> </tr> </tbody> </table>	Fluid name	MP Steam	NOR	MIN	[STEAM]	Flow rate	MAX			UNIT	Inlet pressure	232			kg/h	Outlet pressure	16.01	16.01		kgf/cm2A	Diff. pressure	6.8	6.8		kgf/cm2	Shut-off press.		18.2		kgf/cm2	Temperature	270			degC	Sp.Gr. (liq.)				water=1	Sp.Gr. (gas,vapor)				MW	Viscosity				cP	Flash				%	Velocity	0.06			Mach	S.P.L.				dBA	Calculated Cv	1.416				Travel	72			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 19</p> <p>Existing Valve Prod No. 416-8301-2800</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 20%;"></td> <td style="width: 20%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: center;">/</td> <td style="text-align: right;">inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: center;">/</td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	MP Steam	NOR	MIN	[STEAM]																																																																																				
Flow rate	MAX			UNIT																																																																																				
Inlet pressure	232			kg/h																																																																																				
Outlet pressure	16.01	16.01		kgf/cm2A																																																																																				
Diff. pressure	6.8	6.8		kgf/cm2																																																																																				
Shut-off press.		18.2		kgf/cm2																																																																																				
Temperature	270			degC																																																																																				
Sp.Gr. (liq.)				water=1																																																																																				
Sp.Gr. (gas,vapor)				MW																																																																																				
Viscosity				cP																																																																																				
Flash				%																																																																																				
Velocity	0.06			Mach																																																																																				
S.P.L.				dBA																																																																																				
Calculated Cv	1.416																																																																																							
Travel	72			%																																																																																				
Design press.		kPaG																																																																																						
Design temp.		degC																																																																																						
Line size in/out	/	inch																																																																																						
Line Sch. / Thick	/	mm																																																																																						

Specification Sheet

<p>No.: 20 QTY: 1</p> <p>Tag no. 14-LV-001</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1 inch</p> <p>Port size 1 inch</p> <p>Rated Cv 15</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE FACE</p> <p>Flow characteristic %C</p> <p>Bonnet type PLAIN</p> <p>Actuator VA2</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Rich DEA Solution</th> <th>[LIQUID]</th> </tr> <tr> <th></th> <th>MAX NOR MIN</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>6.80</td> <td>m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>15.93</td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>10.84</td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td>23</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>47</td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>1.042</td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>3.73</td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td>73</td> <td>dB</td> </tr> <tr> <td>Calculated Cv</td> <td>2.461</td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Rich DEA Solution	[LIQUID]		MAX NOR MIN	UNIT	Flow rate	6.80	m3/h	Inlet pressure	15.93	kgf/cm2A	Outlet pressure		kgf/cm2A	Diff. pressure	10.84	kgf/cm2	Shut-off press.	23	kgf/cm2	Temperature	47	degC	Sp.Gr. (liq.)	1.042	water=1	Sp.Gr.(gas,vapor)		MW	Viscosity		cP	Flash		%	Velocity	3.73	m/s	S.P.L.	73	dB	Calculated Cv	2.461		Travel		%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 20 Existing Valve Prod No. 416-8303-2600</p> <p><Line spec></p> <table border="1"> <thead> <tr> <th>Design press.</th> <th>kPaG</th> </tr> <tr> <th>Design temp.</th> <th>degC</th> </tr> <tr> <th>Line size in/out</th> <th>inch</th> </tr> <tr> <th>Line Sch. / Thick</th> <th>mm</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> </tbody> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	inch	Line Sch. / Thick	mm								
Fluid name	Rich DEA Solution	[LIQUID]																																																															
	MAX NOR MIN	UNIT																																																															
Flow rate	6.80	m3/h																																																															
Inlet pressure	15.93	kgf/cm2A																																																															
Outlet pressure		kgf/cm2A																																																															
Diff. pressure	10.84	kgf/cm2																																																															
Shut-off press.	23	kgf/cm2																																																															
Temperature	47	degC																																																															
Sp.Gr. (liq.)	1.042	water=1																																																															
Sp.Gr.(gas,vapor)		MW																																																															
Viscosity		cP																																																															
Flash		%																																																															
Velocity	3.73	m/s																																																															
S.P.L.	73	dB																																																															
Calculated Cv	2.461																																																																
Travel		%																																																															
Design press.	kPaG																																																																
Design temp.	degC																																																																
Line size in/out	inch																																																																
Line Sch. / Thick	mm																																																																

Specification Sheet

<p>No.: 21 QTY: 1</p> <p>Tag no. 14-LV-003</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=0.04 inch</p> <p>Rated Cv 0.04</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 Stellite Sheath</p> <p>Flow characteristic LINEAR</p> <p>Bonnet type PLAIN</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease ---</p> <p>Air supply</p> <p>Spring range 0.2-1.0kfg/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal</p> <p>Regurator</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve</p> <p style="padding-left: 20px;">Action</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																								
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Fluid name</td> <td style="width: 20%;">Caustic Solution</td> <td style="width: 10%;"></td> <td style="width: 10%;">[LIQUID]</td> <td style="width: 30%;"></td> </tr> <tr> <td></td> <td>MAX</td> <td>NOR</td> <td>MIN</td> <td>UNIT</td> </tr> <tr> <td>Flow rate</td> <td>0.054</td> <td></td> <td></td> <td>m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>20.3</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>19.99</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>28.5</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>40</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>1.110</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.02</td> <td></td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td>58</td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>0.01485</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>33</td> <td></td> <td></td> <td>%</td> </tr> </table>	Fluid name	Caustic Solution		[LIQUID]			MAX	NOR	MIN	UNIT	Flow rate	0.054			m3/h	Inlet pressure	20.3			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	19.99			kgf/cm2	Shut-off press.		28.5		kgf/cm2	Temperature	40			degC	Sp.Gr. (liq.)	1.110			water=1	Sp.Gr.(gas,vapor)				MW	Viscosity				cP	Flash				%	Velocity	0.02			m/s	S.P.L.	58			dBA	Calculated Cv	0.01485				Travel	33			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 21</p> <p>Existing Valve Prod No. 416-8303-2800</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">Design press.</td> <td style="width: 30%;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: center;">/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: center;">/</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/
Fluid name	Caustic Solution		[LIQUID]																																																																																						
	MAX	NOR	MIN	UNIT																																																																																					
Flow rate	0.054			m3/h																																																																																					
Inlet pressure	20.3			kgf/cm2A																																																																																					
Outlet pressure				kgf/cm2A																																																																																					
Diff. pressure	19.99			kgf/cm2																																																																																					
Shut-off press.		28.5		kgf/cm2																																																																																					
Temperature	40			degC																																																																																					
Sp.Gr. (liq.)	1.110			water=1																																																																																					
Sp.Gr.(gas,vapor)				MW																																																																																					
Viscosity				cP																																																																																					
Flash				%																																																																																					
Velocity	0.02			m/s																																																																																					
S.P.L.	58			dBA																																																																																					
Calculated Cv	0.01485																																																																																								
Travel	33			%																																																																																					
Design press.	kPaG																																																																																								
Design temp.	degC																																																																																								
Line size in/out	/																																																																																								
Line Sch. / Thick	/																																																																																								

Specification Sheet

<p>No.: 22 QTY: 1</p> <p>Tag no. 17-PV-003</p> <p>Service</p> <p>< Specification ></p> <p>Model VBZ</p> <p>Description Special Butterfly Valve</p> <p>Valve size 250 mm inch</p> <p>Port size inch</p> <p>Rated Cv 1700</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SCPH2/SUS316/SUS316 ST</p> <p>Flow characteristic</p> <p>Bonnet type PLAIN</p> <p>Actuator VA4D</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Air fail open)</p> <p>Gland packing V7132Y</p> <p>Gasket ---</p> <p>Grease 650</p> <p>Air supply 2.7kgf/cm2</p> <p>Spring range 0.4-2.0kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0505-003 Minimum and maximum flow stopper for actuator</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																								
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>Treated Gas</th> <th></th> <th>[GAS]</th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>19881</td> <td></td> <td>UNIT m3/h[N]</td> </tr> <tr> <td>Inlet pressure</td> <td>4.12</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>0.14</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>4.5</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>40</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td>0.594</td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>823.7</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Treated Gas		[GAS]		MAX	NOR	MIN	Flow rate	19881		UNIT m3/h[N]	Inlet pressure	4.12		kgf/cm2A	Outlet pressure			kgf/cm2A	Diff. pressure	0.14		kgf/cm2	Shut-off press.		4.5	kgf/cm2	Temperature	40		degC	Sp.Gr. (liq.)			water=1	Sp.Gr.(gas,vapor)	0.594		kg/m3[N]	Viscosity			cP	Flash			%	Velocity				S.P.L.			dBA	Calculated Cv	823.7			Travel			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 22</p> <p>Existing Valve Prod No. 416-8306-0400</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/
Fluid name	Treated Gas		[GAS]																																																																						
	MAX	NOR	MIN																																																																						
Flow rate	19881		UNIT m3/h[N]																																																																						
Inlet pressure	4.12		kgf/cm2A																																																																						
Outlet pressure			kgf/cm2A																																																																						
Diff. pressure	0.14		kgf/cm2																																																																						
Shut-off press.		4.5	kgf/cm2																																																																						
Temperature	40		degC																																																																						
Sp.Gr. (liq.)			water=1																																																																						
Sp.Gr.(gas,vapor)	0.594		kg/m3[N]																																																																						
Viscosity			cP																																																																						
Flash			%																																																																						
Velocity																																																																									
S.P.L.			dBA																																																																						
Calculated Cv	823.7																																																																								
Travel			%																																																																						
Design press.	kPaG																																																																								
Design temp.	degC																																																																								
Line size in/out	/																																																																								
Line Sch. / Thick	/																																																																								

Specification Sheet

<p>No.: 23 QTY: 1</p> <p>Tag no. 16-PV-013</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 1-1/2 inch</p> <p>Port size 1-1/2 inch</p> <p>Rated Cv 30</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type PLAIN</p> <p>Actuator VA2</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 400</p> <p>Air supply</p> <p>Spring range 0.2-1.0kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal</p> <p style="padding-left: 20px;">Explosion-proof</p> <p style="padding-left: 20px;">Signal</p> <p>Regurator</p> <p>Regulator 2</p> <p>Limit Switch</p> <p style="padding-left: 20px;">Action</p> <p>Solenoid valve</p> <p style="padding-left: 20px;">Action</p> <p style="padding-left: 20px;">Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																																												
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Fluid name</td> <td style="width: 25%;">Acid Gas</td> <td style="width: 10%;"></td> <td style="width: 10%;">[</td> <td style="width: 15%;">GAS</td> <td style="width: 25%;">]</td> </tr> <tr> <td></td> <td>MAX</td> <td>NOR</td> <td>MIN</td> <td>UNIT</td> <td></td> </tr> <tr> <td>Flow rate</td> <td>378</td> <td></td> <td></td> <td>m3/h[N]</td> <td></td> </tr> <tr> <td>Inlet pressure</td> <td>2.27</td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Diff. pressure</td> <td>0.4</td> <td></td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>3.0</td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Temperature</td> <td>93</td> <td></td> <td></td> <td>degC</td> <td></td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> <td></td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td>0.995</td> <td></td> <td></td> <td>kg/m3[N]</td> <td></td> </tr> <tr> <td>Viscosity</td> <td>0.02</td> <td></td> <td></td> <td>cP</td> <td></td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> <tr> <td>Velocity</td> <td>0.15</td> <td></td> <td></td> <td>Mach</td> <td></td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> <td></td> </tr> <tr> <td>Calculated Cv</td> <td>18.14</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> </table>	Fluid name	Acid Gas		[GAS]		MAX	NOR	MIN	UNIT		Flow rate	378			m3/h[N]		Inlet pressure	2.27			kgf/cm2A		Outlet pressure				kgf/cm2A		Diff. pressure	0.4			kgf/cm2		Shut-off press.		3.0		kgf/cm2		Temperature	93			degC		Sp.Gr. (liq.)				water=1		Sp.Gr. (gas,vapor)	0.995			kg/m3[N]		Viscosity	0.02			cP		Flash				%		Velocity	0.15			Mach		S.P.L.				dBA		Calculated Cv	18.14					Travel				%		<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 23 Existing Valve Prod No. 416-8305-4500</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">Design press.</td> <td style="width: 30%;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: center;">/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: center;">/</td> </tr> <tr> <td></td> <td style="text-align: right;">inch</td> </tr> <tr> <td></td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/		inch		mm
Fluid name	Acid Gas		[GAS]																																																																																																								
	MAX	NOR	MIN	UNIT																																																																																																									
Flow rate	378			m3/h[N]																																																																																																									
Inlet pressure	2.27			kgf/cm2A																																																																																																									
Outlet pressure				kgf/cm2A																																																																																																									
Diff. pressure	0.4			kgf/cm2																																																																																																									
Shut-off press.		3.0		kgf/cm2																																																																																																									
Temperature	93			degC																																																																																																									
Sp.Gr. (liq.)				water=1																																																																																																									
Sp.Gr. (gas,vapor)	0.995			kg/m3[N]																																																																																																									
Viscosity	0.02			cP																																																																																																									
Flash				%																																																																																																									
Velocity	0.15			Mach																																																																																																									
S.P.L.				dBA																																																																																																									
Calculated Cv	18.14																																																																																																												
Travel				%																																																																																																									
Design press.	kPaG																																																																																																												
Design temp.	degC																																																																																																												
Line size in/out	/																																																																																																												
Line Sch. / Thick	/																																																																																																												
	inch																																																																																																												
	mm																																																																																																												

Specification Sheet

<p>No.: 24 QTY: 2</p> <p>Tag no. 16-FV-071, 16-FV-072</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=6.3 inch</p> <p>Rated Cv 6.3</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE</p> <p>Flow characteristic EQ%</p> <p>Bonnet type PLAIN</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 1.4kgf/cm2</p> <p>Spring range 0.2-1.0kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal Explosion-proof Signal</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch Action</p> <p>Solenoid valve 3-Way Solenoid Valve Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																								
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">Fuel Gas</th> <th style="text-align: center;">[</th> <th style="text-align: left;">GAS</th> <th style="text-align: center;">]</th> </tr> <tr> <th></th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th style="text-align: left;">UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td style="text-align: center;">145</td> <td></td> <td></td> <td>m3/h[N]</td> </tr> <tr> <td>Inlet pressure</td> <td style="text-align: center;">3.53</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td style="text-align: center;">1.24</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td style="text-align: center;">4.0</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td style="text-align: center;">45</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td style="text-align: center;">11.50</td> <td></td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td style="text-align: center;">0.01</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Fuel Gas	[GAS]		MAX	NOR	MIN	UNIT	Flow rate	145			m3/h[N]	Inlet pressure	3.53			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	1.24			kgf/cm2	Shut-off press.		4.0		kgf/cm2	Temperature	45			degC	Sp.Gr. (liq.)				water=1	Sp.Gr.(gas,vapor)	11.50			kg/m3[N]	Viscosity	0.01			cP	Flash				%	Velocity				Mach	S.P.L.				dBA	Calculated Cv					Travel				%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 24,5 Existing Valve Prod No. 416-8352-1000 and No. 416-8352-1100</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 40%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">// inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">// mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	// inch	Line Sch. / Thick	// mm
Fluid name	Fuel Gas	[GAS]																																																																																					
	MAX	NOR	MIN	UNIT																																																																																					
Flow rate	145			m3/h[N]																																																																																					
Inlet pressure	3.53			kgf/cm2A																																																																																					
Outlet pressure				kgf/cm2A																																																																																					
Diff. pressure	1.24			kgf/cm2																																																																																					
Shut-off press.		4.0		kgf/cm2																																																																																					
Temperature	45			degC																																																																																					
Sp.Gr. (liq.)				water=1																																																																																					
Sp.Gr.(gas,vapor)	11.50			kg/m3[N]																																																																																					
Viscosity	0.01			cP																																																																																					
Flash				%																																																																																					
Velocity				Mach																																																																																					
S.P.L.				dBA																																																																																					
Calculated Cv																																																																																									
Travel				%																																																																																					
Design press.	kPaG																																																																																								
Design temp.	degC																																																																																								
Line size in/out	// inch																																																																																								
Line Sch. / Thick	// mm																																																																																								

Specification Sheet

<p>No.: 25 QTY: 1</p> <p>Tag no. 16-PDV-004</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=6.3 inch</p> <p>Rated Cv 6.3</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE FACE</p> <p>Flow characteristic EQ%</p> <p>Bonnet type EXT-1 HIGH</p> <p>Actuator HA2</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Air fail open)</p> <p>Gland packing V1290</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																							
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">Steam</th> <th style="text-align: center;">NOR</th> <th style="text-align: center;">MIN</th> <th style="text-align: left;">[STEAM]</th> </tr> <tr> <th style="text-align: left;">Flow rate</th> <th style="text-align: left;">MAX</th> <th></th> <th></th> <th style="text-align: left;">UNIT</th> </tr> </thead> <tbody> <tr> <td>Inlet pressure</td> <td>15.0</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>7.2</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>18.2</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>270</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.15</td> <td></td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>2.998</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>80</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	Steam	NOR	MIN	[STEAM]	Flow rate	MAX			UNIT	Inlet pressure	15.0			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	7.2			kgf/cm2	Shut-off press.		18.2		kgf/cm2	Temperature	270			degC	Sp.Gr. (liq.)				water=1	Sp.Gr.(gas,vapor)				MW	Viscosity				cP	Flash				%	Velocity	0.15			Mach	S.P.L.				dBA	Calculated Cv	2.998				Travel	80			%	<p><Seat Leakage></p> <p style="text-align: center;">CLASS IV (SV0201-003)</p> <p><Note> Tokumi: V93-8666-00 - 26</p> <p>Existing Valve Prod No. 416-8352-1210</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 20%;"></td> <td style="width: 20%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: center;">/</td> <td style="text-align: right;">inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: center;">/</td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	Steam	NOR	MIN	[STEAM]																																																																																				
Flow rate	MAX			UNIT																																																																																				
Inlet pressure	15.0			kgf/cm2A																																																																																				
Outlet pressure				kgf/cm2A																																																																																				
Diff. pressure	7.2			kgf/cm2																																																																																				
Shut-off press.		18.2		kgf/cm2																																																																																				
Temperature	270			degC																																																																																				
Sp.Gr. (liq.)				water=1																																																																																				
Sp.Gr.(gas,vapor)				MW																																																																																				
Viscosity				cP																																																																																				
Flash				%																																																																																				
Velocity	0.15			Mach																																																																																				
S.P.L.				dBA																																																																																				
Calculated Cv	2.998																																																																																							
Travel	80			%																																																																																				
Design press.		kPaG																																																																																						
Design temp.		degC																																																																																						
Line size in/out	/	inch																																																																																						
Line Sch. / Thick	/	mm																																																																																						

Specification Sheet

<p>No.: 26 QTY: 1</p> <p>Tag no. 16-PV-010</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 4 inch</p> <p>Port size 2-1/2 inch</p> <p>Rated Cv 75</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type FIN</p> <p>Actuator HA3</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																																												
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Fluid name</td> <td style="width: 20%;">Fuel Gas</td> <td style="width: 10%;"></td> <td style="width: 10%;">[GAS]</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td>MAX</td> <td>NOR</td> <td>MIN</td> <td>UNIT</td> <td></td> </tr> <tr> <td>Flow rate</td> <td>8587</td> <td></td> <td></td> <td>m3/h[N]</td> <td></td> </tr> <tr> <td>Inlet pressure</td> <td>13.72</td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> <td></td> </tr> <tr> <td>Diff. pressure</td> <td>7.49</td> <td></td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>14.80</td> <td></td> <td>kgf/cm2</td> <td></td> </tr> <tr> <td>Temperature</td> <td>38</td> <td></td> <td></td> <td>degC</td> <td></td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> <td></td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td>0.988</td> <td></td> <td></td> <td>kg/m3[N]</td> <td></td> </tr> <tr> <td>Viscosity</td> <td>0.1</td> <td></td> <td></td> <td>cP</td> <td></td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> <tr> <td>Velocity</td> <td>0.13</td> <td></td> <td></td> <td>Mach</td> <td></td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> <td></td> </tr> <tr> <td>Calculated Cv</td> <td>40.98</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> <td></td> </tr> </table>	Fluid name	Fuel Gas		[GAS]				MAX	NOR	MIN	UNIT		Flow rate	8587			m3/h[N]		Inlet pressure	13.72			kgf/cm2A		Outlet pressure				kgf/cm2A		Diff. pressure	7.49			kgf/cm2		Shut-off press.		14.80		kgf/cm2		Temperature	38			degC		Sp.Gr. (liq.)				water=1		Sp.Gr.(gas,vapor)	0.988			kg/m3[N]		Viscosity	0.1			cP		Flash				%		Velocity	0.13			Mach		S.P.L.				dBA		Calculated Cv	40.98					Travel				%		<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 27</p> <p>Existing Valve Prod No. 416-8305-4000</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Design press.</td> <td style="width: 20%;"></td> <td style="width: 20%; text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td></td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: center;">/</td> <td style="text-align: right;">inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: center;">/</td> <td style="text-align: right;">mm</td> </tr> </table>	Design press.		kPaG	Design temp.		degC	Line size in/out	/	inch	Line Sch. / Thick	/	mm
Fluid name	Fuel Gas		[GAS]																																																																																																										
	MAX	NOR	MIN	UNIT																																																																																																									
Flow rate	8587			m3/h[N]																																																																																																									
Inlet pressure	13.72			kgf/cm2A																																																																																																									
Outlet pressure				kgf/cm2A																																																																																																									
Diff. pressure	7.49			kgf/cm2																																																																																																									
Shut-off press.		14.80		kgf/cm2																																																																																																									
Temperature	38			degC																																																																																																									
Sp.Gr. (liq.)				water=1																																																																																																									
Sp.Gr.(gas,vapor)	0.988			kg/m3[N]																																																																																																									
Viscosity	0.1			cP																																																																																																									
Flash				%																																																																																																									
Velocity	0.13			Mach																																																																																																									
S.P.L.				dBA																																																																																																									
Calculated Cv	40.98																																																																																																												
Travel				%																																																																																																									
Design press.		kPaG																																																																																																											
Design temp.		degC																																																																																																											
Line size in/out	/	inch																																																																																																											
Line Sch. / Thick	/	mm																																																																																																											

Specification Sheet

<p>No.: 27 QTY: 1</p> <p>Tag no. 16-HV-004</p> <p>Service</p> <p>< Specification ></p> <p>Model HLS</p> <p>Description Small-Port Single Seated Control Valves</p> <p>Valve size 1 inch</p> <p>Port size Cv=4.0 inch</p> <p>Rated Cv 4.0</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 STELLITE</p> <p>Flow characteristic EQ%</p> <p>Bonnet type PLAIN</p> <p>Actuator HA2</p> <p>Manual operator ---</p> <p>Valve action REVERSE(Air fail close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.4-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																								
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">WBL</th> <th style="text-align: left;">NOR</th> <th style="text-align: left;">MIN</th> <th style="text-align: left;">[LIQUID]</th> </tr> <tr> <th style="text-align: left;">Flow rate</th> <th style="text-align: left;">MAX</th> <th></th> <th></th> <th style="text-align: left;">UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>4.0</td> <td></td> <td></td> <td>m3/h</td> </tr> <tr> <td>Inlet pressure</td> <td>8.73</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>3.26</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>10</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>125</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td>0.938</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas, vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td>0.18</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>2.19</td> <td></td> <td></td> <td>m/s</td> </tr> <tr> <td>S.P.L.</td> <td>68</td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>2.505</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td>87</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	WBL	NOR	MIN	[LIQUID]	Flow rate	MAX			UNIT	Flow rate	4.0			m3/h	Inlet pressure	8.73			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	3.26			kgf/cm2	Shut-off press.		10		kgf/cm2	Temperature	125			degC	Sp.Gr. (liq.)	0.938			water=1	Sp.Gr. (gas, vapor)				MW	Viscosity	0.18			cP	Flash				%	Velocity	2.19			m/s	S.P.L.	68			dBA	Calculated Cv	2.505				Travel	87			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 28</p> <p>Existing Valve Prod No. 416-8305-5100</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Design press.</td> <td style="text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">/ inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">/ mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/ inch	Line Sch. / Thick	/ mm
Fluid name	WBL	NOR	MIN	[LIQUID]																																																																																					
Flow rate	MAX			UNIT																																																																																					
Flow rate	4.0			m3/h																																																																																					
Inlet pressure	8.73			kgf/cm2A																																																																																					
Outlet pressure				kgf/cm2A																																																																																					
Diff. pressure	3.26			kgf/cm2																																																																																					
Shut-off press.		10		kgf/cm2																																																																																					
Temperature	125			degC																																																																																					
Sp.Gr. (liq.)	0.938			water=1																																																																																					
Sp.Gr. (gas, vapor)				MW																																																																																					
Viscosity	0.18			cP																																																																																					
Flash				%																																																																																					
Velocity	2.19			m/s																																																																																					
S.P.L.	68			dBA																																																																																					
Calculated Cv	2.505																																																																																								
Travel	87			%																																																																																					
Design press.	kPaG																																																																																								
Design temp.	degC																																																																																								
Line size in/out	/ inch																																																																																								
Line Sch. / Thick	/ mm																																																																																								

Specification Sheet

<p>No.: 28 QTY: 1</p> <p>Tag no. 16-HV-008</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 6 inch</p> <p>Port size 4 inch</p> <p>Rated Cv 215</p> <p>Connection size inch</p> <p>Body rating ANSI300</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316 Stellite Sheath</p> <p>Flow characteristic %C</p> <p>Bonnet type</p> <p>Actuator HA4</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing TK397</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																								
<p><Operating condition></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Fluid name</th> <th style="text-align: left;">SM</th> <th style="text-align: left;">NOR</th> <th style="text-align: left;">MIN</th> <th style="text-align: left;">[LIQUID]</th> </tr> <tr> <th></th> <th>MAX</th> <th></th> <th></th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate.</td> <td>21296</td> <td></td> <td></td> <td>kg/h</td> </tr> <tr> <td>Inlet pressure</td> <td>16.03</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>12.43</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>18.2</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>380</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td>0.023</td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dba</td> </tr> <tr> <td>Calculated Cv</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	SM	NOR	MIN	[LIQUID]		MAX			UNIT	Flow rate.	21296			kg/h	Inlet pressure	16.03			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	12.43			kgf/cm2	Shut-off press.		18.2		kgf/cm2	Temperature	380			degC	Sp.Gr. (liq.)				water=1	Sp.Gr. (gas,vapor)				MW	Viscosity	0.023			cP	Flash				%	Velocity					S.P.L.				dba	Calculated Cv					Travel				%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 29 Existing Valve Prod No. 416-8352-0900</p> <p><Line spec></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Design press.</td> <td style="text-align: right;">kPaG</td> </tr> <tr> <td>Design temp.</td> <td style="text-align: right;">degC</td> </tr> <tr> <td>Line size in/out</td> <td style="text-align: right;">/ inch</td> </tr> <tr> <td>Line Sch. / Thick</td> <td style="text-align: right;">/ mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/ inch	Line Sch. / Thick	/ mm
Fluid name	SM	NOR	MIN	[LIQUID]																																																																																					
	MAX			UNIT																																																																																					
Flow rate.	21296			kg/h																																																																																					
Inlet pressure	16.03			kgf/cm2A																																																																																					
Outlet pressure				kgf/cm2A																																																																																					
Diff. pressure	12.43			kgf/cm2																																																																																					
Shut-off press.		18.2		kgf/cm2																																																																																					
Temperature	380			degC																																																																																					
Sp.Gr. (liq.)				water=1																																																																																					
Sp.Gr. (gas,vapor)				MW																																																																																					
Viscosity	0.023			cP																																																																																					
Flash				%																																																																																					
Velocity																																																																																									
S.P.L.				dba																																																																																					
Calculated Cv																																																																																									
Travel				%																																																																																					
Design press.	kPaG																																																																																								
Design temp.	degC																																																																																								
Line size in/out	/ inch																																																																																								
Line Sch. / Thick	/ mm																																																																																								

Specification Sheet

<p>No.: 29 QTY: 1</p> <p>Tag no. 16-FV-009</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 4 inch</p> <p>Port size 4 inch</p> <p>Rated Cv 195</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type PLAIN</p> <p>Actuator HA3</p> <p>Manual operator ---</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y</p> <p>Gasket V543</p> <p>Grease PS6</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																																												
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>SL</th> <th></th> <th></th> <th>[LIQUID]</th> </tr> <tr> <th></th> <th>MAX</th> <th>NOR</th> <th>MIN</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>3630</td> <td></td> <td></td> <td>kg/h</td> </tr> <tr> <td>Inlet pressure</td> <td>4.29</td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Outlet pressure</td> <td></td> <td></td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>0.9</td> <td></td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>5.0</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>230</td> <td></td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr. (gas,vapor)</td> <td></td> <td></td> <td></td> <td>MW</td> </tr> <tr> <td>Viscosity</td> <td></td> <td></td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	SL			[LIQUID]		MAX	NOR	MIN	UNIT	Flow rate	3630			kg/h	Inlet pressure	4.29			kgf/cm2A	Outlet pressure				kgf/cm2A	Diff. pressure	0.9			kgf/cm2	Shut-off press.		5.0		kgf/cm2	Temperature	230			degC	Sp.Gr. (liq.)				water=1	Sp.Gr. (gas,vapor)				MW	Viscosity				cP	Flash				%	Velocity					S.P.L.				dBA	Calculated Cv					Travel				%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 30 Existing Valve Prod No. 416-8305-3200</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td>kPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> </tr> <tr> <td></td> <td>inch</td> </tr> <tr> <td></td> <td>mm</td> </tr> </table>	Design press.	kPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/		inch		mm
Fluid name	SL			[LIQUID]																																																																																									
	MAX	NOR	MIN	UNIT																																																																																									
Flow rate	3630			kg/h																																																																																									
Inlet pressure	4.29			kgf/cm2A																																																																																									
Outlet pressure				kgf/cm2A																																																																																									
Diff. pressure	0.9			kgf/cm2																																																																																									
Shut-off press.		5.0		kgf/cm2																																																																																									
Temperature	230			degC																																																																																									
Sp.Gr. (liq.)				water=1																																																																																									
Sp.Gr. (gas,vapor)				MW																																																																																									
Viscosity				cP																																																																																									
Flash				%																																																																																									
Velocity																																																																																													
S.P.L.				dBA																																																																																									
Calculated Cv																																																																																													
Travel				%																																																																																									
Design press.	kPaG																																																																																												
Design temp.	degC																																																																																												
Line size in/out	/																																																																																												
Line Sch. / Thick	/																																																																																												
	inch																																																																																												
	mm																																																																																												

Specification Sheet

<p>No.: 30 QTY: 1</p> <p>Tag no. 16-FV-051</p> <p>Service</p> <p>< Specification ></p> <p>Model VDP</p> <p>Description Top and Bottom-Guided Double Seated Control Valve</p> <p>Valve size 4 inch</p> <p>Port size 4 inch</p> <p>Rated Cv 195</p> <p>Connection size inch</p> <p>Body rating ANSI150</p> <p>End connection RF</p> <p>Body material SCPH2</p> <p>Trim material SUS316</p> <p>Flow characteristic %V</p> <p>Bonnet type PLAIN</p> <p>Actuator HA3</p> <p>Manual operator SIDE</p> <p>Valve action DIRECT(Push down to close)</p> <p>Gland packing V7132Y+SM636</p> <p>Gasket V543</p> <p>Grease 650</p> <p>Air supply 4.0kgf/cm2</p> <p>Spring range 0.8-2.4kgf/cm2</p> <p>< Accesories ></p> <p>Positioner / Signal HTP</p> <p>Explosion-proof</p> <p>Signal 0.2-1.0 kgf/cm2</p> <p>Regurator KZ03-2B-XX</p> <p>Regulator 2</p> <p>Limit Switch</p> <p>Action</p> <p>Solenoid valve</p> <p>Action</p> <p>Power supply</p> <p>Others</p>	<p>Product no.:</p> <p><Option></p> <p>SV0703-105 Indicating unit : "kgf/cm2"</p> <p>SV0601-001 Air piping Connection: 1/4 NPT</p> <p>SV0602-002 Air piping: Vinyl covered copper tube. Joint:Cr plated with vinyl cap</p> <p>SV0101-004 Flange facing finish : Serration ANSI B16.5 (Spiral)</p> <p><Finish></p> <p>Body: Silver</p> <p>Diaph. Case: Silver</p> <p>Yoke: Silver</p> <p>Paint: Standard</p>																																																																				
<p><Operating condition></p> <table border="1"> <thead> <tr> <th>Fluid name</th> <th>HC Vapor</th> <th></th> <th>[GAS]</th> </tr> </thead> <tbody> <tr> <td>Flow rate</td> <td>MAX</td> <td>NOR</td> <td>MIN UNIT</td> </tr> <tr> <td>Inlet pressure</td> <td>16457</td> <td></td> <td>m3/h[N]</td> </tr> <tr> <td>Outlet pressure</td> <td>14.03</td> <td></td> <td>kgf/cm2A</td> </tr> <tr> <td>Diff. pressure</td> <td>7.55</td> <td></td> <td>kgf/cm2</td> </tr> <tr> <td>Shut-off press.</td> <td></td> <td>17.6</td> <td>kgf/cm2</td> </tr> <tr> <td>Temperature</td> <td>99</td> <td></td> <td>degC</td> </tr> <tr> <td>Sp.Gr. (liq.)</td> <td></td> <td></td> <td>water=1</td> </tr> <tr> <td>Sp.Gr.(gas,vapor)</td> <td>1.8</td> <td></td> <td>kg/m3[N]</td> </tr> <tr> <td>Viscosity</td> <td>0.02</td> <td></td> <td>cP</td> </tr> <tr> <td>Flash</td> <td></td> <td></td> <td>%</td> </tr> <tr> <td>Velocity</td> <td>0.37</td> <td></td> <td>Mach</td> </tr> <tr> <td>S.P.L.</td> <td></td> <td></td> <td>dBA</td> </tr> <tr> <td>Calculated Cv</td> <td>113.4</td> <td></td> <td></td> </tr> <tr> <td>Travel</td> <td></td> <td></td> <td>%</td> </tr> </tbody> </table>	Fluid name	HC Vapor		[GAS]	Flow rate	MAX	NOR	MIN UNIT	Inlet pressure	16457		m3/h[N]	Outlet pressure	14.03		kgf/cm2A	Diff. pressure	7.55		kgf/cm2	Shut-off press.		17.6	kgf/cm2	Temperature	99		degC	Sp.Gr. (liq.)			water=1	Sp.Gr.(gas,vapor)	1.8		kg/m3[N]	Viscosity	0.02		cP	Flash			%	Velocity	0.37		Mach	S.P.L.			dBA	Calculated Cv	113.4			Travel			%	<p><Seat Leakage></p> <p><Note> Tokumi: V93-8666-00 - 31</p> <p>Existing Valve Prod No. 416-8352-0400</p> <p><Line spec></p> <table border="1"> <tr> <td>Design press.</td> <td>KPaG</td> </tr> <tr> <td>Design temp.</td> <td>degC</td> </tr> <tr> <td>Line size in/out</td> <td>/</td> </tr> <tr> <td>Line Sch. / Thick</td> <td>/</td> </tr> </table>	Design press.	KPaG	Design temp.	degC	Line size in/out	/	Line Sch. / Thick	/
Fluid name	HC Vapor		[GAS]																																																																		
Flow rate	MAX	NOR	MIN UNIT																																																																		
Inlet pressure	16457		m3/h[N]																																																																		
Outlet pressure	14.03		kgf/cm2A																																																																		
Diff. pressure	7.55		kgf/cm2																																																																		
Shut-off press.		17.6	kgf/cm2																																																																		
Temperature	99		degC																																																																		
Sp.Gr. (liq.)			water=1																																																																		
Sp.Gr.(gas,vapor)	1.8		kg/m3[N]																																																																		
Viscosity	0.02		cP																																																																		
Flash			%																																																																		
Velocity	0.37		Mach																																																																		
S.P.L.			dBA																																																																		
Calculated Cv	113.4																																																																				
Travel			%																																																																		
Design press.	KPaG																																																																				
Design temp.	degC																																																																				
Line size in/out	/																																																																				
Line Sch. / Thick	/																																																																				