

MagneW PLUS Sanitary Detector (15~125 mm, PFA liner)

MGS28U-I II III IV V VI VII VIII - IX- YW/Options (some options can be selected per each model.)

List Price is the sum of the price of all selections made.

Option "Y" must be specified for Yamatake Version.

Option "W" must be specified for clamp.

Lead time: after receipt of order(s), ex-factory basis.

Basic Model No.		MGS28U -		Basic price							Lead time (Weeks)		
				15 mm	25 mm	40 mm	50 mm	80 mm	100 mm	125 mm			
I	Diameter	15 mm (0.5 inch)	015	323								4	
		25 mm (1 inch)	025		338							4	
		40 mm (1.5 inch)	040			358						4	
		50 mm (2 inches)	050				408					4	
		80 mm (3 inches)	080					483				4	
		100 mm (4 inches)	100						607			4	
		125 mm (5 inches)	125							885		4	
				Additional price									
II	Lining	PFA	P										
III	Pipe connection	IDF clamp	C1										
		Tri clamp	C2										
IV	Electrodes	SUS316L	L										
		Hastelloy C	C										
		Titanium	K										
		SUS 304	E										
V	Ferrule for welding	SUS 316L	S										
VI	Electrical connection / Watertight gland	Integral type		1									
		Remote type	G1/2 internal thread / without watertight gland		2								
			G1/2 internal thread / with brass (Ni-plated) watertight gland		3								
			G1/2 internal thread / with plastic watertight gland		4								
			1/2NPT internal thread / without watertight gland		5								
			CM20 internal thread / without watertight gland		6								
			Pg13.5 internal thread / without watertight gland		7								
			G1/2 internal thread / with SUS304 watertight gland		8								
VII	Installation/ Wiring direction	Integral style	H										
		Remote style	Upstream side (Horizontal / Vertical piping mounting)	A									
			Downstream side (Horizontal / Vertical piping mounting)	B									
			Horizontal piping mounting Left side viewed from upstream	C									
			Horizontal piping mounting Right side viewed from upstream	D									
VIII	Calibration	Standard calibration											
		3 point (0, 50, 100%) w/ master converter	A										
		+/- 0.35% of rate calibration	U										
Others												Refer to table 104	
IX Finish				Standard (corrosion-proof) finish									

Remote style			Additional Price
Option	Y	Yamatake Version (Must be selected)	0
	B	Traceability Certificate	10
	K	Attaching the TAG number plate to the terminal box (remote type detector) Note1	4
	L	Attaching the TAG number plate to the neck section (Note 1)	8
	V	Spare silicone gasket for ferrule (2 pcs.)	Refer to table 301
	W	with clamp (2 pcs.)	0

Integral style			Additional Price
Option	Y	Yamatake Version (Must be selected)	0
	B	Traceability certificate	10
	L	Attaching the TAG number plate to the neck section (Note 1)	8
	V	Spare silicone gasket for ferrule (2 pcs.)	Refer to table 301
	W	with clamp (2 pcs.)	0

Note 1. Must be selected for Tag No. requirement.

Table 104				Additional price	Lead time (weeks)
Calibration	P	3 point (0, 50, 100%) w/ master converter		0	
	Q	5 point (0, 25, 50, 75, 100%) w/ master converter		100	10
	J	2 point (0, 100%) w/ customer's specific converter		0	
	R	2 point (0, 50%) w/ master converter		0	
	E	5 point (0, 25, 50, 75, 100%) w/ customer's specific converter		100	10

Table 301		15 mm	25 mm	40 mm	50 mm	80 mm	100 mm	125 mm
V	Spare silicone gasket for ferrule (2 pcs.)	7	7	8	9	10	12	15