

## Accessories

### 14-2. Pressure regulator with filter & 1-1/2in. (40mm) Pressure Gauge (with assembling fee)

#### 14-2-1. Pressure regulator with filter

Attention to quote the Accessories.

\*1 Painting: Y138A as standard

\*2 Stainless Filters (SH4040) are available (ex.: KZ03Z-2A-XX)

Model No.	Selections		Optional selections	Selection condition , Specification of Pressure gauge , Others	List price
KZ03	- I	- II	- III, IV		

Model No.	Pressure setting	Pressure connections	Pressure gauge	Selection condition , Specification of Pressure gauge , Others	Base price (1000YEN)
KZ03					
	-2			Available supply pressure(Ps) : Ps ≤ 400 kPa	20
	-3			Available supply pressure(Ps) : 400 < Ps ≤ 700 kPa	29
		A		Rc1/4 inch (internal)	+
		B		1/4 inch NPT Thread (internal)	

	-XX Without Pressure Gauge			Additional price	
	1½ inch (40 mm) with Pressure Gauge (Scale)				
	Primary maximum scale	Secondly unit	Recommended supply		
-1A	2	kgf/cm <sup>2</sup>	none	Ps ≤ 1.5kgf/cm <sup>2</sup>	5
-1B	4			1.5 < Ps ≤ 3.0kgf/cm <sup>2</sup>	5
-1N	6			3.0 < Ps ≤ 4.5kgf/cm <sup>2</sup>	5
-1C	10			4.5 < Ps ≤ 7.0kgf/cm <sup>2</sup>	5
-1D	30	psi	none	Ps ≤ 22psi	8
-1E	60			22 < Ps ≤ 45psi	8
-1P	100			45 < Ps ≤ 65psi	8
-1F	150			65 < Ps ≤ 100psi	8
-1G	2	bar	none	Ps ≤ 1.5bar	8
-1H	4			1.5 < Ps ≤ 3.0bar	8
-1Q	6			3.0 < Ps ≤ 4.5bar	8
-1J	10			4.5 < Ps ≤ 7.0bar	8
-1K	200	kPa	none	Ps ≤ 150kPa	5
-1L	400			150 < Ps ≤ 300kPa	5
-1R	600			300 < Ps ≤ 450kPa	5
-1M	1000			450 < Ps ≤ 700kPa	5
-1S	0.2	MPa	none	Ps ≤ 0.15MPa	5
-1T	0.4			0.15 < Ps ≤ 0.3MPa	5
-1U	0.6			0.3 < Ps ≤ 0.45MPa	5
-1V	1			0.45 < Ps ≤ 0.7MPa	5
-2A	2	kgf/cm <sup>2</sup>	kPa	Ps ≤ 1.5kgf/cm <sup>2</sup>	8
-2B	4			1.5 < Ps ≤ 3.0kgf/cm <sup>2</sup>	8
-2N	6			3.0 < Ps ≤ 4.5kgf/cm <sup>2</sup>	8
-2C	10			4.5 < Ps ≤ 7.0kgf/cm <sup>2</sup>	8
-3A	2	kgf/cm <sup>2</sup>	MPa	Ps ≤ 1.5kgf/cm <sup>2</sup>	8
-3B	4			1.5 < Ps ≤ 3.0kgf/cm <sup>2</sup>	8
-3N	6			3.0 < Ps ≤ 4.5kgf/cm <sup>2</sup>	8
-3C	10			4.5 < Ps ≤ 7.0kgf/cm <sup>2</sup>	8
-4K	200	kPa	kgf/cm <sup>2</sup>	Ps ≤ 150kPa	8
-4L	400			150 < Ps ≤ 300kPa	8
-4R	600			300 < Ps ≤ 450kPa	8
-4M	1000			450 < Ps ≤ 700kPa	8
-5S	0.2	MPa	kgf/cm <sup>2</sup>	Ps ≤ 0.15MPa	8
-5T	0.4			0.15 < Ps ≤ 0.3kPa	8
-5U	0.6			0.3 < Ps ≤ 0.45MPa	8
-5V	1			0.45 < Ps ≤ 0.7MPa	8

**Accessories****14-2-2 1-1/2 inch (40 mm) Pressure Gauge**

Model No.	Selections	Optional selections	Selection condition , Specification of Pressure gauge , Others	List Price
40A	- I	- II , III		

Model No.				Base price (1000YEN)
40A				4
	-X		Without Joint	0
	-T		With Tee Joint (Rc1/4 inch)	2
	-K		With Joint (Rc1/4 inch + Rc1/2 inch)	1

+

Scale & unit				Additional price	
Primary maximum scale & unit	Secondly unit	Recommended supply pressure			
-1A	2	kgf/cm <sup>2</sup>	none	Ps ≤ 1.5kgf/cm <sup>2</sup>	0
-1B	4			1.5 < Ps ≤ 3.0kgf/cm <sup>2</sup>	0
-1N	6			3.0 < Ps ≤ 4.5kgf/cm <sup>2</sup>	0
-1C	10			4.5 < Ps ≤ 7.0kgf/cm <sup>2</sup>	0
-1D	30	psi	none	Ps ≤ 22psi	3
-1E	60			22 < Ps ≤ 45psi	3
-1P	100			45 < Ps ≤ 65psi	3
-1F	150			65 < Ps ≤ 100psi	3
-1G	2	bar	none	Ps ≤ 1.5bar	3
-1H	4			1.5 < Ps ≤ 3.0bar	3
-1Q	6			3.0 < Ps ≤ 4.5bar	3
-1J	10			4.5 < Ps ≤ 7.0bar	3
-1K	200	kPa	none	Ps ≤ 150kPa	0
-1L	400			150 < Ps ≤ 300kPa	0
-1R	600			300 < Ps ≤ 450kPa	0
-1M	1000			450 < Ps ≤ 700kPa	0
-1S	0.2	MPa	none	Ps ≤ 0.15MPa	0
-1T	0.4			0.15 < Ps ≤ 0.3MPa	0
-1U	0.6			0.3 < Ps ≤ 0.45MPa	0
-1V	1			0.45 < Ps ≤ 0.7MPa	0
-2A	2	kgf/cm <sup>2</sup>	kPa	Ps ≤ 1.5kgf/cm <sup>2</sup>	3
-2B	4			1.5 < Ps ≤ 3.0kgf/cm <sup>2</sup>	3
-2N	6			3.0 < Ps ≤ 4.5kgf/cm <sup>2</sup>	3
-2C	10			4.5 < Ps ≤ 7.0kgf/cm <sup>2</sup>	3
-3A	2	kgf/cm <sup>2</sup>	MPa	Ps ≤ 1.5kgf/cm <sup>2</sup>	3
-3B	4			1.5 < Ps ≤ 3.0kgf/cm <sup>2</sup>	3
-3N	6			3.0 < Ps ≤ 4.5kgf/cm <sup>2</sup>	3
-3C	10			4.5 < Ps ≤ 7.0kgf/cm <sup>2</sup>	3
-4K	200	kPa	kgf/cm <sup>2</sup>	Ps ≤ 150kPa	3
-4L	400			150 < Ps ≤ 300kPa	3
-4R	600			300 < Ps ≤ 450kPa	3
-4M	1000			450 < Ps ≤ 700kPa	3
-5S	0.2	MPa	kgf/cm <sup>2</sup>	Ps ≤ 0.15MPa	3
-5T	0.4			0.15 < Ps ≤ 0.3kPa	3
-5U	0.6			0.3 < Ps ≤ 0.45MPa	3
-5V	1			0.45 < Ps ≤ 0.7MPa	3