

## YAMATAKE Europe

Bosdellestraat 120/2 B-1933 Zaventel Belgium  
TEL: 00 32 2 785 07 10 FAX: 00 32 2 785 07 11  
<http://www.yamatake-europe.com>

# PROPOSAL

PROPOSAL NO.: Q20061706 YEU-06-903

14-juil-06

**To:** Alberto Dorado  
Honeywell  
IM&C - Process Solutions  
\* (34-91) 3136179 direct line  
\* (34-91) 3136278 fax  
\* [alberto.dorado@honeywell.com](mailto:alberto.dorado@honeywell.com)

Dear Sir,  
We have pleasure in quoting you as follows:

End User : Unknown through Honeywell  
inquiry No. : xxx by E-mail dated by 6 Jul., 2006

Item	Description	Q'ty	Unit	Unit Price	Amount (euro)
I	Pneumatic Temperature controller *Refer to the next page for the detail specifications .	1	lot		€2 974
II	Total FOB Japan	1	lot		€2 974

Delivery Time : 3.5 months after receipt of order (Ex-factory basis )

Manufacturer : Yamatake Corporation  
Packing Information : N/W kg, G/W kg, x x cm,

Very truly yours,

\_\_\_\_\_  
Regis Houllier

Item	Description	Q'ty	Unit	Unit Price (euro)	Amount (euro)
------	-------------	------	------	-------------------	---------------

1	KF Series Temperature Indicating controller	1 set	€2 974	€2 974
1-1	Temperature Indicating controller	Unit price	€2 840	

Model No. : KFTA13Z-06XXXB2T-7

Code Feature/Option

KFTA13 Basic Model No. : Temperature Indicating Controller (PID)

Z Special processing : 1) Special range (25 -- 75 Deg.C), 2) Capillary length : 3 m

-06 Liquid-fill type

XXX Range : 25 - 75 Deg.C (Special)

B Air Piping Connection : 1/4 NPT Internal Thread

2 Output Pressure Unit : 3 - 15 PSI

T Mounting : 2 inch pipe mounting

-7 Option 1 : Air set

\*See Note 1 below, and refer to the specification sheet (SS2-KFT100-0100) attached .

1-2	Well for above temperature transmitter	Unit price	€134	
-----	--	------------	------	--

Model No. : KFZ1-1612-15

Code Feature/Option

KFZ1 Basic Model No. : Well for temperature element

-1 Type : For Liquid-fill type (drilled)

61 Process Connection : Screw connection 13/4" NPT, Max press 60 kgf/cm2

2 Material : SUS316

-15 Others : Insertion length 150 mm

\*Refer to the specification sheet (SS2-KFT100-0100) attached .

Sub Total €2 974

Note 1. Because of the special narrow range (25 -75 Cent. Degree),  
the Indicating capacity (accuracy) is +/- 3 % FS, and the repeatability is within 1 % FS .