

Specifications according to data sheet SP 10.01
 Power supply DC 10.8 ... 45 V
 Signal output 4 ... 20 mA, 2-wire, HART
 Measuring span adjustable with Turn down to 1 : 133
 Material of flange Stainless Steel
 Process connection 2 x 1/4 NPT female
 Maximum of static pressure 200 bar for bolts and nuts of carbon steel
 70 bar for bolts and nuts of stainless steel



| Explosion protection | Digital indicator | External zero and span adjustment | Material of bolts and nuts | Measuring span | Ordering No. | Price EUR |
|---|-------------------|-----------------------------------|----------------------------|--------------------|--------------|----------------|
| without | without | without | carbon steel | 7.5 mbar ... 1 bar | 7265097 Lg | 797.10 |
| | | | | 350 mbar ... 7 bar | 12009938 | 826.90 |
| ATEX EEx ia II C | with | with | carbon steel | 7.5 mbar ... 1 bar | 12010014 | 962.90 |
| | | | | 350 mbar ... 7 bar | 12010006 | 992.60 |
| FM Intrinsically safe, explosion proof | with | with | stainless steel | 7.5 mbar ... 1 bar | 7193070 Lg | 1169.30 |
| ATEX EEx ia II C | with | with | stainless steel | 7.5 mbar ... 1 bar | 7209146 Lg | 1169.30 |

Quantity discount factor (QDF)

| | | |
|------|-------|------------|
| from | 1 pcs | 1.00 |
| from | 3 pcs | 0.80 |
| from | 5 pcs | 0.75 |
| from | 7 pcs | on inquiry |

Specifications according to leaflet SP 10.01
 Power supply DC 10,8 ... 45 V
 Output Signal 4...20 mA, 2-wire, HART
 Measuring span adjustable with Turn down to 1 : 133



| Field No. | Code | Features | Price EUR | Carryover |
|--|------|--|--------------------|---------------|
| | | | Basic price | 896.00 |
| | | | Add. Price | |
| Measuring span | | | | |
| | 2 | 7,5 mbar ... 1 bar (Default: 0...5000 mmH2O) | without | |
| | 3 | 350 mbar ... 7 bar (Default: 0...3,5 kg/cm2) | 35.00 | |
| | 6 | 2,5 bar ... 140 bar (Default: 0...70 kg/cm2) | 657.00 | |
| 1 | ? | other | on inquiry | |
| Static pressure | | | | |
| | 0 | 200 bar | without | |
| 2 | 1 | 420 bar | 747.50 | |
| Material of flange | | | | |
| | A | Carbon steel | without | |
| 3 | E | Stainless Steel | 41.80 | |
| Fill fluid | | | | |
| | 1 | Silicone oil | without | |
| 4 | ? | other | on inquiry | |
| Process connection | | | | |
| | P | 2 x 1/4 NPT female | without | |
| | 5 | 2 x 1/2 NPT female | without | |
| | 3 | 2 x 1/4 NPT male | 34.20 | |
| | 4 | 2 x 1/2 NPT male | 34.20 | |
| | 1 | 2 x G 1/4 B male | 34.20 | |
| | 2 | 2 x G 1/2 B male | 34.20 | |
| 5 | ? | others | on inquiry | |
| Material of bolts and nuts | | | | |
| | 1 | Carbon steel | without | |
| 6 | U | Stainless Steel | 98.00 | |
| Explosion protection | | | | |
| | Z | without | without | |
| | 3 | FM Explosion proof | 31.00 | |
| | 4 | FM Intrinsically safe | 31.00 | |
| 7 | 7 | ATEX Intrinsically safe | 31.00 | |
| Electrical connection | | | | |
| | E | 1/2 NPT female | without | |
| 8 | F | Cable gland M20x1,5 <i>not with FM Explosion proof</i> | 40.00 | |
| Digital indicator | | | | |
| | Z | without | without | |
| | P | 4 1/2-digit (0 to 100% linear scales) | 81.00 | |
| 9 | ? | other | on inquiry | |
| External zero and span adjustment | | | | |
| | ZZ | without | without | |
| 10 | E5 | with | 83.00 | |
| Mounting accessories | | | | |
| | ZZ | without | without | |
| | E9 | Mounting bracket for pipe 2" (Carbon Steel) | 117.00 | |
| 11 | ES | Mounting bracket for pipe 2" (Stainless Steel) | 149.00 | |
| Configuration | | | | |
| | ZZ | Standard | without | |
| 12 | C7 | Custom calibration | 46.80 | |
| Manifold | | | | |
| | Z | without | without | |
| | 3 | 3-way manifold, stainless steel 316L | 186.00 | |
| 13 | 5 | 5-way manifold, stainless steel 316L | 306.00 | |
| Printed operating instructions | | | | |
| | ZZ | without | without | |
| 14 | ME | english | 20.00 | |

Total:



TRONIC

Differential Pressure Transmitter DPT9
Model Series STD9XX

Quantity discount factor (QDF)

from 1 pcs. 1.00
from 3 pcs. 0.80
from 5 pcs. 0.75
from 7 pcs. on inquiry

| Total | Quantity | QDF | Total price |
|----------------------|------------------------|------------------------|------------------------|
| <input type="text"/> | x <input type="text"/> | x <input type="text"/> | = <input type="text"/> |

Additional order info

| | YES | NO | |
|----|-----|----|----------------------|
| 15 | 1 | Z | quality certificates |
| 16 | T | Z | additional text |

Order code:

| | | | | | | | | | | | | | | | | | | | | | |
|----------------------|----------------------|----------------------|---|----------------------|----------------------|----------------------|---|----------------------|----------------------|----------------------|----------------------|---|----------------------|----------------------|----------------------|---|----------------------|----------------------|---|----------------------|----------------------|
| DPT9 | 1 | 2 | - | 3 | 4 | 5 | - | 6 | 7 | 8 | 9 | - | 10 | 11 | 12 | - | 13 | 14 | - | 15 | 16 |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | <input type="text"/> |

Additional text: _____



TRONIC

Pressure Transmitter PT9
Model Series STG9XX/STA9XX

| Field No. | Code | Features | Price EUR | Carryover |
|-----------|------|---|-------------|-----------|
| | | | Basic price | 827.00 |
| | | | Add. Price | |
| | | Measuring span/Overload Resistant Value | | |
| | G940 | 350 mbar ... 3,5 bar (Default: 0...17,5 kg/cm2) | 0.00 | |
| | G960 | 7 bar ... 140 bar (Default: 0...70 kg/cm2) | 0.00 | |
| | G981 | 7 bar ... 420 bar (Default: 0...210 kg/cm2) | 434.00 | |
| | A923 | 40 ... 1004 mbar abs. (Default: 0...100 mmHg abs) | 490.00 | |
| 1 | A940 | 0,35...35 bar abs. (Default: 0...17,5 kg/cm2 abs) | 490.00 | |
| | | Material of flange | | |
| | A | Carbon steel | without | |
| 2 | E | Stainless Steel | 67.00 | |
| | | Fill fluid | | |
| | 1 | Silicone oil | without | |
| 3 | ? | other | on inquiry | |
| | | Process connection | | |
| | B | 1/4-18 NPT female | without | |
| | A | 1/4-18 NPT female with oval flange | 34.20 | |
| | 5 | 2 x 1/2 NPT female | 34.20 | |
| | G | 2 x 1/2 NPT female, with oval flange | 34.20 | |
| | 1 | 2 x G 1/4 B male | 34.20 | |
| | 2 | 2 x G 1/2 B male | 34.20 | |
| | 3 | 2 x 1/4 NPT male | 34.20 | |
| | 4 | 2 x 1/2 NPT male | 34.20 | |
| 4 | ? | others | on inquiry | |
| | | Material of bolts and nuts | | |
| | 1 | Carbon steel | without | |
| 5 | U | Stainless Steel | 98.00 | |
| | | Explosion protection | | |
| | Z | without | without | |
| | 3 | FM Explosion proof | 31.00 | |
| | 4 | FM Intrinsically safe | 31.00 | |
| 6 | 7 | ATEX Intrinsically safe | 31.00 | |
| | | Electrical connection | | |
| | E | 1/2 NPT female | without | |
| 7 | F | Cable gland M20x1,5 | 40.00 | |
| | | Digital indicator | | |
| | Z | without | without | |
| | P | 4 1/2-digit (0 to 100% linear scales) | 81.00 | |
| 8 | ? | other | on inquiry | |
| | | Output signals | | |
| | D7ZZ | 4...20 mA, 2-wire, HART | without | |
| | D6L1 | Foundation Fieldbus | 560.00 | |
| 9 | ???? | others | on inquiry | |
| | | External zero and span adjustment | | |
| | ZZ | without | without | |
| 10 | E5 | with | 83.00 | |
| | | Mounting accessories | | |
| | ZZ | without | without | |
| | E9 | Mounting bracket for pipe 2" (Carbon Steel) | 117.00 | |
| 11 | ES | Mounting bracket for pipe 2" (Stainless Steel) | 149.00 | |
| | | Configuration | | |
| | ZZ | Standard | without | |
| 12 | C7 | Custom calibration | 46.80 | |
| | | Printed operating instructions | | |
| | ZZ | without | without | |
| 13 | ME | english | 20.00 | |

Total:

Quantity discount factor (QDF)

from 1 pcs. 1.00
 from 3 pcs. 0.80
 from 5 pcs. 0.75
 from 7 pcs. on inquiry

Total **Quantity** **QDF** **Total price**
 × × =

Additional order info

| | YES | NO | |
|----|-----|----|-------------------------------|
| 14 | 4 | Z | Certificates product specific |
| 15 | T | Z | additional text |



TRONIC

Pressure Transmitter PT9
Model Series STG9XX/STA9XX

Order code:

| | | | | | | | | | | | | | | | | | | | | |
|----|----------------------|---|----------------------|----------------------|----------------------|---|----------------------|----------------------|----------------------|----------------------|---|----------------------|----------------------|----------------------|----------------------|---|----------------------|---|----------------------|----------------------|
| | 1 | | 2 | 3 | 4 | | 5 | 6 | 7 | 8 | | 9 | 10 | 11 | 12 | | 13 | | 14 | 15 |
| PT | <input type="text"/> | - | <input type="text"/> | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | - | <input type="text"/> | - | <input type="text"/> | <input type="text"/> |

Additional text: _____



TRONIC

Differential Pressure Transmitter DPT2

Modell Series 265DS

Specifications according to leaflet
Measuring span
Accuracy

DS 265DS
adjustable with Turn down to 1 : 100
0,04% of adjusted span up to turndown of 10:1

| Field No. | Code | Features | Price EUR | Carryover |
|-----------------------------------|------|--|--------------------|-----------|
| | | | Basic price | 1361.00 |
| | | | Add. Price | |
| Measuring span | | | | |
| 1 | C | 2 mbar ... 60 mbar (Default: 0...60 mbar) | without | |
| | F | 4 mbar ... 400 mbar (Default: 0...400 mbar) | without | |
| | L | 25 mbar ... 2500 mbar (Default: 0...2500 mbar) | without | |
| | N | 0,2 bar ... 20 bar (Default: 0...20 bar) | without | |
| | R | 1 bar ... 100 bar (Default: 0...100 bar) | 71.00 | |
| Static pressure | | | | |
| 2 | C | 160 bar | without | |
| | Z | 250 bar | 52.00 | |
| | T | 410 bar | 95.00 | |
| Fill fluid | | | | |
| 3 | S | Silicone oil | without | |
| | ? | other | on inquiry | |
| Process connection | | | | |
| 4 | A | 2 x 1/4-18 NPT female | without | |
| | 1 | 2 x G 1/4 B male | 34.20 | |
| | 2 | 2 x G 1/2 B male | 34.20 | |
| | 3 | 2 x 1/4 NPT male | 34.20 | |
| | 4 | 2 x 1/2 NPT male | 34.20 | |
| | 5 | 2 x 1/2 NPT female | 34.20 | |
| | ? | others | on inquiry | |
| Material of bolts and nuts | | | | |
| 5 | 5 | Stainless Steel (washer EPDM) | 14.20 | |
| | ? | others | on inquiry | |
| Electrical connection | | | | |
| 6 | A | 1/2 NPT female | without | |
| | B | Cable gland M20x1,5 | without | |
| | ? | others | on inquiry | |
| Signal output | | | | |
| 7 | 1 | 4...20 mA, 2-wire design, HART | without | |
| | 2 | PROFIBUS PA | 159.00 | |
| | 3 | FOUNDATION-Fieldbus | 159.00 | |
| Explosion protection | | | | |
| 8 | ZZ | without | without | |
| | E1 | ATEX EEx ia II 1/2-GD | 10.50 | |
| | E2 | ATEX EEx d II 1/2-G | 10.50 | |
| | ?? | others | on inquiry | |
| Digital Display | | | | |
| 9 | ZZ | without | without | |
| | L1 | LCD-Display 6-digits | 89.50 | |
| | ?? | others | on inquiry | |
| Mounting accessories | | | | |
| 10 | ZZ | without | without | |
| | B2 | Mounting kit for 2" pipe mounting (st. steel) | 42.50 | |
| | B4 | Mounting kit for wall mounting (st. steel) | 28.30 | |
| Configuration | | | | |
| 11 | ZZ | Standard | without | |
| | C7 | Custom calibration | 46.80 | |
| Manifold | | | | |
| 12 | Z | without | without | |
| | 3 | 3-way manifold, stainless steel 316L | 186.00 | |
| | 5 | 5-way manifold, stainless steel 316L | 306.00 | |

Total:
Quantity discount factor (QDF)

from 1 pcs. 1.00
 from 3 pcs. 0.80
 from 5 pcs. 0.75
 from 7 pcs. on inquiry

Total
Quantity
QDF
Total price
 × × =
Additional order info

| | YES | NO | |
|----|--------------------------|--------------------------|-------------------------------|
| 13 | <input type="checkbox"/> | <input type="checkbox"/> | Certificates product specific |
| 14 | <input type="checkbox"/> | <input type="checkbox"/> | additional text |



TRONIC

Differential Pressure Transmitter DPT2
Modell Series 265DS

Order code:

| | | | | | | | | | | | | | | | | | |
|----------|---|---|---|---|---|---|---|---|---|---|---|----|----|----|---|----|----|
| DPT265DS | - | 1 | 2 | 3 | 4 | 5 | 6 | 7 | - | 8 | 9 | 10 | 11 | 12 | - | 13 | 14 |
|----------|---|---|---|---|---|---|---|---|---|---|---|----|----|----|---|----|----|

Additional text: _____



TRONIC

Pressure Transmitter PT2 Model Series 265GS/265AS

Specifications according to leaflet
Measuring span
Accuracy

DS 265GS/265AS
adjustable with Turn down to 1 : 100
0,04% of adjusted span up to turndown of 10:1

| Field No. | Code | Features | Price EUR | Carryover |
|--------------------------------------|------|---|--------------------|---------------|
| | | | Basic price | 913.60 |
| | | | Add. Price | |
| Measuring span | | | | |
| 1 | ASD | 0,5 bar ... 10 bar (Default: 0...10 bar) | 123.00 | |
| | ASL | 125 mbar ... 2500 mbar (Default: 0...2500 mbar) | 123.00 | |
| | ??? | others | on inquiry | |
| Material Diaphragm/Fill fluid | | | | |
| 2 | K | Hastelloy C276 / Siliconoil | without | |
| | ? | others | on inquiry | |
| Process connection | | | | |
| 3 | B | 1/2 NPT female | without | |
| | T | 1/2 NPT male | without | |
| | P | G 1/2 B female | without | |
| | ? | others | on inquiry | |
| Material of gasket | | | | |
| 4 | 8 | Perbunan | without | |
| | ? | Others | on inquiry | |
| Electrical connection | | | | |
| 5 | A | 1/2 NPT female | without | |
| | B | Cable gland M20x1,5 | without | |
| | ? | others | on inquiry | |
| Output signal | | | | |
| 6 | 1 | 4...20 mA, 2-wire design, HART | without | |
| | 2 | PROFIBUS PA | 159.00 | |
| | 3 | FOUNDATION-Fieldbus | 159.00 | |
| Explosion protection | | | | |
| 7 | ZZ | without | without | |
| | E1 | ATEX EEx ia II 1/2-GD | 10.50 | |
| | E2 | ATEX EEx d II 1/2-G | 10.50 | |
| | ?? | others | on inquiry | |
| Digital Display | | | | |
| 8 | ZZ | without | without | |
| | L1 | LCD-Display 6-digits | 100.00 | |
| | ?? | others | on inquiry | |
| Mounting accessories | | | | |
| 9 | ZZ | without | without | |
| | B2 | Mounting kit for 2" pipe mounting (st. steel) | 42.50 | |
| | B4 | Mounting kit for wall mounting (st. steel) | 28.50 | |
| Configuration | | | | |
| 10 | ZZ | Standard | without | |
| | KK | Customer's configuration | 46.80 | |

Total:

Quantity discount factor (QDF)

from 1 pcs. 1.00
 from 3 pcs. 0.80
 from 5 pcs. 0.75
 from 7 pcs. on inquiry

| | | | |
|----------------------|----------------------|----------------------|----------------------|
| Total | Quantity | QDF | Total price |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| | x | x | = |

Additional order info

| | YES | NO | |
|----|-----|----|-------------------------------|
| 11 | 4 | Z | Certificates product specific |
| 12 | T | Z | additional text |

Order code:

PT265 1 - 2 3 4 5 6 - 7 8 9 10 - 11 12

Additional text:



TRONIC

Differential Pressure Transmitter DPT1

Model Series EJA110A

Static pressure 160 bar
 Measuring span adjustable with Turn down to 1 : 100
 Accuracy 0,075% of span

| Field No. | Code | Features | Price EUR | Carryover |
|--------------------------------------|------|--|--------------------|----------------|
| | | | Basic price | 1168.00 |
| | | | Add. Price | |
| Signal output | | | | |
| 1 | E | 4...20 mA, 2-wire design, HART | without | |
| | F | FOUNDATION-Fieldbus | 217.00 | |
| Measuring span | | | | |
| 2 | L | 5 mbar ... 100 mbar (Default: 0...10 kPa) | 111.00 | |
| | M | 10 mbar ... 1000 mbar (Default: 0...100 kPa) | without | |
| | H | 50 mbar ... 5000 mbar (Default: 0...500 kPa) | without | |
| | V | 1,4 bar ... 140 bar (Default: 0...14 MPa) | 217.00 | |
| Wetted parts material | | | | |
| 3 | S | Stainless Steel | without | |
| Process connection | | | | |
| 4 | 3 | 2 x 1/4 NPT female with adapter flange | 26.00 | |
| | 4 | 2 x 1/2 NPT female, with adapter flange | 26.00 | |
| | 5 | 2 x 1/4-18 NPT female | without | |
| | ? | others | on inquiry | |
| Material of bolts and nuts | | | | |
| 5 | A | SCM435 | without | |
| | B | SUS630 (Stainless Steel) | 58.00 | |
| | C | SUH660 | 130.00 | |
| Installation | | | | |
| 6 | 9 | Horizontal impulse piping, left side high pressure | 26.00 | |
| Electrical connection | | | | |
| 7 | 2 | 1/2 NPT female, without blind plug | without | |
| | 4 | M20x1,5 innen, without blind plug | without | |
| Digital indicator | | | | |
| 8 | N | without | without | |
| | E | 5 1/2-digits with range setting switch | 173.50 | |
| | ? | other | on inquiry | |
| Mounting accessories | | | | |
| 9 | N | without | without | |
| | A | Mounting kit for 2" pipe mounting (Carbon Steel) | 16.50 | |
| | B | Mounting kit for 2" pipe mountin (Stainless Steel) | 42.50 | |
| Explosion protection | | | | |
| 10 | ZZZ | without | without | |
| | KS2 | II 1G EEx ia IIC T4, ATEX Intrinsically safe | 18.50 | |
| | KF2 | II 2G EExd IIC T4, T5, T6, ATEX Flameproof | 18.50 | |
| | KU2 | KF2, KS2 and II 3G Ex nL IIC T4 ATEX Type n | 18.50 | |
| Material of amplifier housing | | | | |
| 11 | AL | Low copper cast-aluminium alloy with polyurethane | without | |
| | X1 | Stainless Steel | 52.00 | |
| | E1 | Epoxy resin-baked coating | 380.00 | |
| Configuration | | | | |
| 12 | ZZ | Standard | without | |
| | KK | Customer's configuration | 46.80 | |
| Manifold | | | | |
| 13 | Z | without | without | |
| | 3 | 3-way manifold, stainless steel 316L | 186.00 | |
| | 5 | 5-way manifold, stainless steel 316L | 306.00 | |

Total:
Quantity discount factor (QDF)

from 1 pcs. 1.00
 from 3 pcs. 0.80
 from 5 pcs. 0.75
 from 7 pcs. on inquiry

| | | | |
|--|-----------------|--|---|
| Total | Quantity | QDF | Total price |
| | x | | = |

Additional order info

| | YES | NO | |
|----|-----|----|-------------------------------|
| 14 | 4 | Z | Certificates product specific |
| 15 | T | Z | additional text |



TRONIC

Differential Pressure Transmitter DPT1
Model Series EJA110A

Order code:

| | | | | | | | | | | | | | | | | | | | | |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|----|---|----|----|----|---|----|----|
| DPT110A | - | 1 | 2 | 3 | 4 | 5 | - | 6 | 7 | 8 | 9 | - | 10 | - | 11 | 12 | 13 | - | 14 | 15 |
| | | | | | | | | | | | | | | | | | | | | |

Additional text: _____



TRONIC

Pressure Transmitter PT4

Model Series EJA430A

| Field No. | Code | Features | Price EUR | Carryover |
|-----------|------|--|-------------------------------|-----------|
| | | | Basic price | 1059.30 |
| | | | Add. Price | |
| 1 | E | Signal output 4...20 mA, 2-wire design, HART | without | |
| | F | FOUNDATION-Fieldbus | 217.00 | |
| | | | Measuring span | |
| 2 | A | 0,3 bar ... 30 bar (Default: 0...3 MPa) | without | |
| | B | 1,4 bar ... 140 bar (Default: 0...14 MPa) | without | |
| | | | Wetted parts material | |
| 3 | S | Stainless Steel | without | |
| | | | Process connection | |
| 4 | 5 | 1/4 NPT female | without | |
| | 3 | 1/4 NPT female with oval flange | 15.50 | |
| | 4 | 1/2 NPT female with oval flange | 15.50 | |
| | ? | others | on inquiry | |
| | | | Material of bolts and nuts | |
| 5 | A | SCM435 | without | |
| | B | SUS630 (Stainless Steel) | 54.20 | |
| | C | SUH660 | 130.10 | |
| | | | Installation | |
| 6 | 9 | Horizontal impulse piping, left side high pressure | 25.00 | |
| | | | Electrical connection | |
| 7 | 2 | 1/2 NPT female, without blind plug | without | |
| | 4 | M20x1,5 innen, without blind plug | without | |
| | | | Digital indicator | |
| 8 | N | without | without | |
| | E | 5 1/2-digits with range setting switch | 161.50 | |
| | ? | other | on inquiry | |
| | | | Mounting accessories | |
| 9 | N | without | without | |
| | A | Mounting kit for 2" pipe mounting (Carbon Steel) | 15.20 | |
| | B | Mounting kit for 2" pipe mountin (Stainless Steel) | 39.00 | |
| | | | Explosion protection | |
| 10 | ZZZ | without | without | |
| | KF2 | II 2G EExd IIC T4, T5, T6, ATEX Flameproof | 18.50 | |
| | KS2 | II 1G EEx ia IIC T4, ATEX Intrinsically safe | 18.50 | |
| | KU2 | KF2, KS2 and II 3G Ex nL IIC T4 ATEX Type n | 18.50 | |
| | | | Material of amplifier housing | |
| 11 | AL | Low copper cast-aluminium alloy with polyurethane | without | |
| | X1 | Stainless Steel | 52.00 | |
| | E1 | Epoxy resin-baked coating | 380.00 | |
| | | | Configuration | |
| 12 | ZZ | Standard | without | |
| | KK | Customer's configuration | without | |

Total: **Quantity discount factor (QDF)**

from 1 pcs. 1.00
 from 3 pcs. 0.80
 from 5 pcs. 0.75
 from 7 pcs. on inquiry

Total

Quantity

QDF

Total price

 × × =
Additional order info

| | YES | NO | |
|----|-----|----|-------------------------------|
| 13 | 4 | Z | Certificates product specific |
| 14 | T | Z | additional text |

Order code:

| | | | | | | | | | | | | | | | | | | | |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|----|---|----|----|---|----|----|
| PT430A | - | 1 | 2 | 3 | 4 | 5 | - | 6 | 7 | 8 | 9 | - | 10 | - | 11 | 12 | - | 13 | 14 |
| | | | | | | | | | | | | | | | | | | | |

Additional text:

| Field No. | Code | Features | Price EUR | Carryover |
|--|------|---|-------------|-----------|
| | | | Basic price | |
| | | | Add. Price | |
| Unit | | | | |
| | L | kPa | without | |
| | E | MPa | without | |
| | B | bar | without | |
| | M | mbar | without | |
| | Y | mH2O | without | |
| | Z | mmH2O | without | |
| 1 | | ? other | on inquiry | |
| Begin of configuration range | | | | |
| 2 | | Begin of configuration range (input e.g. 00100 when specification is 100) | without | |
| End of configuration range | | | | |
| 3 | | End of configuration range (input e.g. 00100 when specification is 100) | without | |
| TAG No. (max. 8 alphanumeric characters) | | | | |
| | Z | without | without | |
| 4 | | ? please state as text | without | |
| M&C description (max. 16 alphanumeric characters) | | | | |
| | Z | without | without | |
| 5 | | ? please state as text | without | |
| Additional order details | | | | |
| | T | additional text | on inquiry | |
| 6 | | Z without | without | |

Total:

Order code:

| | | | | | | | |
|----------|---|---|---|---|---|---|---|
| DPT-KONF | 1 | 2 | 3 | - | 4 | 5 | 6 |
| | <input style="width: 20px;" type="text"/> | <input style="width: 20px;" type="text"/> | <input style="width: 20px;" type="text"/> | | <input style="width: 20px;" type="text"/> | <input style="width: 20px;" type="text"/> | <input style="width: 20px;" type="text"/> |

Additional text: _____



Certification

Test Certificate per EN 10 204 - 2.2

The Factory Certificate EN 10 204-2.2 complies with the Manufacturer's Certificate M DIN 55 350-18-4.1.2.



| Field No. | Code | Features | Price EUR | Carryover |
|---------------------------------------|------|---|--------------------|-----------|
| | | | Basic price | |
| | | | Add. Price | |
| Type of inspection certificate | | | | |
| 1 | 2.2 | Inspection Certificate 2.2 | without | |
| Language | | | | |
| | E | German and English <i>standard</i> | without | |
| | F | German and French | without | |
| 2 | ? | other <i>please state clearly as additional text</i> | without | |
| Formal Certificate | | | | |
| | ZZ | without | without | |
| 3 | K1 | manufacturing according to state of the art | 8.50 | |
| accuracy | | | | |
| | ZZ | without | without | |
| 4 | F1 | certification of class and accuracy | 13.40 | |
| Material Certificate | | | | |
| | ZZ | without | without | |
| | A1 | wetted parts material (metal contents) | 13.40 | |
| 5 | A2 | wetted parts material (metal contents) per NACE MR 0175 latest edition <i>not for copper alloys</i> | 14.50 | |
| pressure and stability test | | | | |
| | ZZ | without | without | |
| 6 | DK | pressure test up to overpressure limit | 8.50 | |
| other certificates | | | | |
| | ZZ | without | without | |
| | S1 | silicone free | 13.40 | |
| | S2 | FDA-approved filling-fluid | 13.40 | |
| | S3 | ingress protection IP65 | 8.40 | |
| 7 | ?? | other | on inquiry | |

Total:

Order code:

ZG - - - - - -

Additional text: _____



| Field No. | Code | Features | Price EUR | Carryover | |
|--------------------------------------|------|--|---------------|-----------------|--------------------|
| | | | Basic price | 24.00 | |
| | | | Add. Price | | |
| Type of certificate | | | see table 1 | | |
| 1 | K | Calibration label | | | |
| | 3 | Acceptance Test Certificate 3.1 accord. EN 10204 with measuring values | | | |
| | D | DKD certification | | | |
| | A | Official verification with certificate | | | |
| | E | Official verification without certificate | | | |
| Accuracy | | | | | |
| 2 | N | > 0.6% | | | |
| | G | => 0.1% ... <= 0.6% | | | |
| | S | => 0.02% ... < 0.1% | | | |
| | E | < 0.02% | | | |
| Measuring range | | | | | |
| 3 | S1 | Standard (relative or differential pressure) up to 1000 bar | | | |
| | H5 | High pressure (relative or differential pressure) up to 5000 bar | | | |
| | A1 | Absolute pressure up to 1000 bar | | | |
| | ?? | other <i>please state as additional text</i> | | | |
| Language | | | | | |
| 4 | D | German | without | | |
| | E | English | without | | |
| | ? | other | on inquiry | | |
| Testing of switching accuracy | | | | | |
| 5 | Z | without | without | | |
| | 1 | 1 switchpoint | 12.00 | | |
| | 2 | 2 switchpoints | 24.00 | | |
| | 3 | 3 switchpoints | 36.00 | | |
| | ? | other | on inquiry | | |
| | | | Total: | | |
| | | | Total | Quantity | Total Price |
| | | | | x | = |

Table 1: Add. Price EUR for Field No. 2, Field No. 1 and Field No. 3

| Field No. 3 Code S1 Measuring range: Standard (relative or differential pressure) up to 1000 bar | | | | | | |
|--|---------------------|----------------------------------|--|-------------------|--|---|
| Field No. 2: Accuracy | | Field No. 1: Type of certificate | | | | |
| Code | | K | 3 | D | A | E |
| | Features | Calibration label | Acceptance Test Certificate 3.1 accord. EN 10204 with measuring values | DKD certification | Official verification with certificate | Official verification without certificate |
| N | > 0.6% | without | 35.00 | 75.00 | 30.00 | 65.00 |
| G | => 0.1% ... <= 0.6% | 12.00 | 72.00 | 137.00 | 42.00 | 102.00 |
| S | => 0.02% ... < 0.1% | on inquiry | 191.00 | 334.00 | on inquiry | on inquiry |
| E | < 0.02% | on inquiry | on inquiry | 771.00 | on inquiry | on inquiry |



Certification

Calibration of Pressure Measuring Instruments at the WIKA DKD-calibration laboratory K-03701

| Field No. 3 Code H5 Measuring range: High pressure (relative or differential pressure) up to 5000 bar | | | | | | |
|---|---------------------|----------------------------------|--|-------------------|--|---|
| Field No. 2: Accuracy | | Field No. 1: Type of certificate | | | | |
| Code | | K | 3 | D | A | E |
| | Features | Calibration label | Acceptance Test Certificate 3.1 accord. EN 10204 with measuring values | DKD certification | Official verification with certificate | Official verification without certificate |
| N | > 0.6% | 5.00 | 48.00 | 95.00 | 35.00 | 78.00 |
| G | => 0.1% ... <= 0.6% | 19.00 | 89.00 | 164.00 | 49.00 | 118.00 |
| S | => 0.02% ... < 0.1% | on inquiry | 234.00 | 406.00 | on inquiry | on inquiry |
| E | < 0.02% | on inquiry | on inquiry | 930.00 | on inquiry | on inquiry |

| Field No. 3 Code A1 Measuring range: Absolute pressure up to 1000 bar | | | | | | |
|---|---------------------|----------------------------------|--|-------------------|--|---|
| Field No. 2: Accuracy | | Field No. 1: Type of certificate | | | | |
| Code | | K | 3 | D | A | E |
| | Features | Calibration label | Acceptance Test Certificate 3.1 accord. EN 10204 with measuring values | DKD certification | Official verification with certificate | Official verification without certificate |
| N | > 0.6% | 5.00 | 48.00 | 95.00 | on inquiry | on inquiry |
| G | => 0.1% ... <= 0.6% | 19.00 | 89.00 | 164.00 | on inquiry | on inquiry |
| S | => 0.02% ... < 0.1% | on inquiry | 234.00 | 406.00 | on inquiry | on inquiry |
| E | < 0.02% | on inquiry | on inquiry | 930.00 | on inquiry | on inquiry |

| Additional order info | | |
|--------------------------|--------------------------|---|
| YES | NO | |
| <input type="checkbox"/> | <input type="checkbox"/> | additional text <i>Please state as clearly understandable text!</i> |

6

Order code:

| | | | | | | | |
|-------|----------------------|----------------------|----------------------|----------------------|----------------------|---|----------------------|
| ZG-P- | 1 | 2 | 3 | 4 | 5 | - | 6 |
| | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | | <input type="text"/> |

Additional text: _____



Certification

Acceptance Test Certificate per EN 10 204 - 3.1B

| Field No. | Code | Features | Price EUR | Carryover |
|-----------|------|-------------------------------------|------------------------------------|-----------|
| | | | Basic price | |
| | | | Add. Price | |
| 1 | E | English | without | |
| | ? | other | on inquiry | |
| | | | Accuracy | |
| 2 | ZZ | without | without | |
| | C1 | certification of class and accuracy | 37.65 | |
| | | | Material Certificate | |
| 3 | ZZ | without | without | |
| | H3 | wetted parts material | 56.50 | |
| | | | Pressure and stability test | |
| 4 | ZZ | without | without | |
| | C5 | pressure and stability test | 37.65 | |
| | | | Leak Rate Certificate | |
| 5 | ZZ | without | without | |
| | C4 | Helium leak test | 84.74 | |
| | | | Total: | |

Order code:

ZG-HW - - - - -

Additional text: _____