

Model No.:GTX__A-Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

			Additional prices
Option	XX	No options	0
	A2	External Zero adjustment*11	30
	G1	One elbow (left)*6*7*10	2
	G2	One elbow (right)*6*7*10	2
	G3	2 elbows*6*7*8*10	4
	G4	Long vent/drain plugs	5
	G6	Side vent/drain top*6	4
	G7	Side vent/drain bottom*6	4
	K1	Oil and water free finish	17
	K3	Oil free finish*4	10
	Q1	Safety Transmitter*5	0
	Q2	NAMUR NE43 Compliant Output signal limits:3.8 to 20.5mA (Output 21.6mA/selected upper limit, 3.6mA/selected lower limit)	20
	Q7	Alarm Output(contact output)	10
	R1	Custom calibration	5
	T1	Test report	2
	T2	Mill certificate	21
	T4	Traceability certificate	10
	T5	NACE certificate*9	5
	W1	Non SI Unit	0

*4 No need to select when Fill Fluid code H, or J is selected.

*5 Not applicable for the combination with code A2, or Q7 of Option

*6 Not applicable for the combination with code A, or B of Process installation.

*7 Not applicable for the combination with code F1 "FM Explosion proof" of Explosion proof.

*8 Not applicable for any Explosion proof. Please select code XX "None" of Explosion proof.

*9 Applicable for "ASTM B575", code B of Material (center body).

*10 Not applicable for the combination with code B "M20 watertight" of Electrical connection.

*11 Not applicable for the combination with code X "None" of Indicator. Please select "With indicator".