

To: Paul Rüster & Co. Produktions GmbH
 Herr Klaus Radmacher Honeywell distributor Ost
 Dorfplatz 11
 D 14532 Stahnsdorf
 Tel: 03329-6124-80
 Fax: 03329-6124-82
E-Mail: ruester@temperatur.com

Reference Exxon Mobile - Saudi Arat
 Quotation No. Q20080298-Rev.4
 Date: 27/04/2010
 Tel: +33 3 22 54 83 47
 Fax: +33 3 22 54 83 29
 Email: regis.houllier@airlitec.com
 Web: <http://eu.azbil.com>

Pos.	Model	Description	QTY	Price unit EURO	Total EURO
1	MGG18F-050PA11CC5AAA-X-Y	<p>Detector MagneW 3000 Plus Weight: 10,5 kg</p> <p><u>Code Description</u> MGG18F Remote type -050 DN 50 (2 Inches) P PFA Liner A1 Flange ANSI 150 1 Flange material standard C Electrode Hastelloy C C Grounding ring Hastelloy C 5 Remote Type: 1/2 NPT internal thread / without watertight gland A Face to face dimensions: standard A Installation/wiring direction: Upstram side A Standard-Calibration -X Finish: Standard backed acrylic -Y Yamatake Standard-Version</p>	10	740,00	7 400,00
3	STD920-E1H-00000-RWAJ-C7E5E9F2	<p>Diff. Pressure Transmitter Model STD 920 - ST3000 Serie 900 Weight: 4,4 kg</p> <p><u>Code Description</u> STD920- Model number E Meterbody cover + Adapter flange: SCS14A (equ. SUS316) Vent/Drain plugs SUS 316 Wetted parts center body: Membrane: SUS316L, Others: SUS316 1 Fill fluid: regular type silicone oil H Process connection: Front NPT 1/2" female thread with adapter flange</p> <p>-00000- R with display (Engineering units) W SUS304 bolts and nuts material A Corrosion resistant finish J Long vent/drain plugs - C7 Custom calibration Please state Span when ordering: LRV, URV E5 External Zero/Span adjustment E9 Mounting bracket F2 Side vent/drain bottom</p>			
		<p>TO BE REPLACED BY: GTX31D-AAAADCBA-AXXABA3-A2G4G7R1</p>			
		DP transmitter	12	590,00	7080
4	---Non Available---	---			
5	STD930-E1H-00000-RWAJ-E5E9F2	<p>Diff. Pressure Transmitter Model STD 930 - ST3000 Serie 900 Weight: 4,4 kg</p> <p><u>Code Description</u> STD920- Model number E Meterbody cover + Adapter flange: SCS14A (equ. SUS316) Vent/Drain plugs SUS 316 Wetted parts center body: Membrane: SUS316L, Others: SUS316 1 Fill fluid: regular type silicone oil</p>			

H Process connection: Front NPT 1/2 female thread with adapter flange
-00000-
 R with display (Engineering units)
 W SUS304 bolts and nuts material
 A Corrosion resistant finish
 J Long vent/drain plugs
 -
 E5 External Zero/Span adjustment
 E9 Mounting bracket
 F2 Side vent/drain bottom

**TO BE REPLACED BY:
 GTX41D-AAAADCB-AXXABA3-A2G4G7R1**

DP transmitter

8

656,00

5248

6 STG960-E1R-00000-RWAJ-E5E9F2

**Gage Pressure Transmitter
 ST3000 Series 900 Model STG960 (100-2000 psi)
 Weight: 4,4 kg**

Code Description

STG960- Medium Gage Pressure Transmitter
 E Meterbody cover + Adapter flange: SCS14A (equ. SUS316)
 Vent/Drain Plugs SUS 316
 Wetted parts center body: Membrane: SUS316L, Others: SUS316
 1 Fill fluid: regular type silicone oil
 R Process connection: Top of bottom: NPT 1/2" female thread with adapter flange
-00000 Code
 R with display (Engineering units)
 W SUS304 bolts and nuts material
 A Corrosion resistant finish
 J Long vent/drain plugs
 -
 E5 External Zero/Span adjustment
 E9 Mounting bracket
 F2 Side vent/drain bottom

**TO BE REPLACED BY:
 GTX71G-AAAADAB-AXXABA3-A2G4G7R1**

GP transmitter

12

623,00

7 476,00

Total	EURO	27 204,00
Minimum Charge	EURO	0,00
* Packing & Handling charges	EURO	0,00
Freight Charge	EURO	1 500,00
Total	EURO	28 704,00

Term of payment

Mode of dispatch Berlin TXL Airport including Transit document T1.

Shipping Route: Air Freight

Term of payment 30 days

Lead time 8 weeks Ex-stock

Validity: 60 days from quotation date

Minimum order amount Euro 150 per order (Packing & Handling and Freight charges excluded).

Cancellation: Not allowed after your order is acknowledged

In addition the Trade Terms are in accordance with Incoterms 2000 and the general trade terms of Yamatake Europe N.V. are valid. – Please request them if needed.

Custom tariff codes

magnetic flowmeter : 9026.10.1906

differential pressure transmitter : 9026.20.1100