

To : O.G.S.

DATE: 17-juin-09

Your reference No. :

Our Quotation No. : Q20080553

Contact person : Regis Houllier

Tel: +32 2 785 0899

Fax: +32 2 785 0711

Email: [rhoullier@yamatake-europe.com](mailto:rhoullier@yamatake-europe.com)

Web: [www.yamatake-europe.com](http://www.yamatake-europe.com)

ATT: S. Sitbon  
Tel.: 01.45.41.25.41  
Fax: 01.40.44.54.81  
Email: [s.sitbon3@wanadoo.fr](mailto:s.sitbon3@wanadoo.fr)  
Web:

ITEM	MODEL	DESCRIPTION	Q'TY	U/PRICE (EURO)	AMOUNT (EURO)
1	HTS 1-1/2 x 1-1/2	Complete Control Valve *See Note1. (replacement model of Prod No 419.8140.5010)	1	3 650,00	3 650,00
2		Valve Stem for Prod No 419.8138.3300	4	174,00	696,00
		Valve Plug for Prod No 419.8138.3300	4	576,00	2 304,00
		Valve Cage for Prod No 419.8138.3300	4	1 270,00	5 080,00
3	V-Teflon	Grand Packing for SLOP760		Decline	
4-1		Valve Stem for Prod No 419.8139.2400	3	174,00	522,00
4-2		Valve Plug for Prod No 419.8139.2400	3	2 184,00	6 552,00
4-3		Valve Cage for Prod No 419.8139.2400	3	3 500,00	10 500,00
5		Bonnet for Prod No 419.8138.6400 old part # 82504054-13300	1	2 811,00	2 811,00
6	250A-11	Air Valve 82510224-00100	2	252,00	504,00
7	KFDB00-222222A1T-7	*See Note2. <u>Code Features/Options</u> KFDB00 Basic model No. : Indicating Transmitter, Non Control -22 Element type : Med range (250 to 5500mmH2O) 2 HP Cover Material : SUS316 2 LP Cover Material : SUS316 2 HP Diaph. Material : SUS316 2 LP Diaph. Material : SUS316 A Air Piping Connect : Rc 1/4 internal 1 Pneumatic Signal : 0.2 to 1.0 kgf/cm2 T Mounting : 2-inch Pipe -7 Option : Pressure Regulator with Filter Scale : 0-50 T/H	4	6 300,00	25 200,00
8	KFPA12Y-02815A1T-M7	*See Note3. <u>Code Features/Options</u> KFPA12 Basic model No. : Indicating Controller (Local type) Control type: PI Y Y-Spec : Y-138A/Corrosion-resistant painting -02 Element type : Bellows 815 Measuring Range : 0 to 1.5 kgf/cm2 A Air Piping Connect : Rc 1/4 internal 1 Pneumatic Signal : 0.2 to 1.0 kgf/cm2 T Mounting : 2-inch Pipe -M Option : With Built-in Manual Controller with Auto/Manual Switch 7 Option : Pressure Regulator with Filter	1	2 666,00	2 666,00
9	MVG1-2SA-X-X	3-way Manifold valve *See Note4.	6	604,00	3 624,00

Code Features/Options

MVG1 Basic model No. : 3-way Manifold Valve  
-2 Body Material : Stainless Steel (SUSF316)  
S Jointing Bolts for Instrument : SUS304  
A Corrosion Finish : Zinc-Plating  
-S With Extension : Extension Pipes  
-X Option : No options

10 82500332-001HK GOP Assy 1 1 239,00 1 239,00

	Minimum Charge	EURO	0,00
	* Packing & Handling charges	EURO	0,00
	Freight Charge	EURO	0,00
	Total FCA Japan	EURO	65 348,00
	Special Discount:		-5%
	Total:		<b>62 080,60</b>

- Note
1. We have quoted the equivalent model HLS instead of obsolete model VST respectively.
  2. Since it is seems requested model number is not correct, please confirm quoted specification.
  3. Requested model number is included Y-Spec (Semi-standard), we guess and quote Y-spec as Y-138A (Corrosion-resistant painting).
  4. Requested model had discontinued.
  5. Please specify full model number of the positionner.

REMARKS:

\* Lead time may be changed depending on the condition of the outstanding orders at our Coordinator

TERMS and CONDITIONS:

Trade Terms: FCA Japan

Payment Terms: Advance payment before shipment

Minimum Order Amount: Euro 150 per order (Packing & Handling and Freight charges excluded)

Lead time: 8 to 12 weeks (Ex-factory)

Shipping Route: By Air

Validity: 60 days from quotation date

Cancellation: Not allowed after your order is acknowledged

End User: Please specify when you place an order

(The Trade Terms are in accordance with Incoterms 2000.)