

YAMATAKE EUROPE N.V.

- rev1

QUOTATION

Bosdellestraat 120/2, B-1933 ZAVENTEM, BELGIUM.
 TEL.: +32-(0)2/ 785.07.10. FAX: +32-(0)2/ 785.07.11.

To : Yorkist (UK) Ltd
 No 11 The Courtyard
 Wellington Street
 Kettering

Att.: Northants, NN16 8SG

Tel.: England

Fax:

Email: Deeanne Dexeter

Web: Tel No: 44 (0) 1536 480011

Fax No: 44 (0) 1536 484445

DATE: 05-mai-09

Your reference No. : ENQUIRY NO 10199

Our Quotation No. : Q20080855

Contact person : Mr. Regis Houllier

Tel: +33 3 22 54 83 47

Fax: +33 3 22 54 83 29

Email: rhoullier@yamatake-europe.com

Web: www.yamatake-europe.com

ITEM MODEL	DESCRIPTION	Q'TY	U/PRICE (EURO)	AMOUNT (EURO)	LEAD TIME (Weeks)
1 MGG18F-050PA11CC5AAA-X-Y	Detector MagneW 3000 Plus Weight: 10,5 kg <u>Code Description</u> MGG18F Remote type -050 DN 50 (2 Inches) P PFA Liner A1 Flange ANSI 150 1 Flange material standard C Electrode Hastelloy C C Grounding ring Hastelloy C 5 Remote Type: 1/2 NPT internal thread / without watertight gland A Face to face dimensions: standard A Installation/wiring direction: Upstream side A Standard-Calibration -X Finish: Standard backed acrylic -Y Yamatake Standard-Version	10	887,00	8 870,00	8
2 MGG18F-100PA11CC5AAA-X-Y	Detector MagneW 3000 Plus Weight: 23,3 kg <u>Code Description</u> MGG18F Remote type -100 DN 100 (4 Inches) P PFA Liner A1 Flange ANSI 150 1 Flange material standard C Electrode Hastelloy C C Grounding ring Hastelloy C 5 Remote Type: 1/2 NPT internal thread / without watertight gland A Face to face dimensions: standard A Installation/wiring direction: Upstream side A Standard-Calibration -X Finish: Standard backed acrylic -Y Yamatake Standard-Version	3	1 268,00	3 804,00	8
2 bis MGG14C-PH5H-2B1X-YJ MGG14C-GH5H-1B1X-YJE (old model)	Flowmeter Converter Dc 24V, Hart communication Electrical connection: CM20 Remote type 2inches pipe Corrosion proof finish display Contacts: 1 input & 1 output Tagging on the terminal box	3	718,00	2 154,00	8
MGG18D-150P22CC6AAA-2X-Y	Flowmeter detector 150 mm Wafer ANSI 3000 type with PFA lining Electrodes & grounding rings: hastelloy C Electrical connection: CM20 Remote type Corrosion proof finish No cable requested between converter & Detector	3	1 579,00	4 737,00	8
3 STD920-E1H-00000-RWAJ-C7E5E9F2	Diff. Pressure Transmitter Model STD 920 - ST3000 Serie 900 Weight: 4,4 kg <u>Code Description</u> STD920- Model number E Meterbody cover + Adapter flange: SCS14A (equ. SUS316) Vent/Drain plugs SUS 316 Wetted parts center body: Membrane: SUS316L, Others: SUS316 1 Fill fluid: regular type silicone oil H Process connection: Front NPT 1/2" female thread with adapter flange -00000- R with display (Engineering units) W SUS304 bolts and nuts material A Corrosion resistant finish J Long vent/drain plugs - C7 Custom calibration Please state Span when ordering: LRV, URV E5 External Zero/Span adjustment E9 Mounting bracket F2 Side vent/drain bottom	12	572,00	6 864,00	8
4 STD920-E1H-00000-P3-C7E9 equ. STD924-A1H-00000-MB-ME	Diff. Pressure Transmitter Model STD 920 - ST3000 Serie 900 Weight: 4,4 kg	20	487,00	9 740,00	8

		<u>Code</u>	<u>Description</u>				
		STD920-	Model number				
		E	Meterbody cover + Adapter flange: SCS14A (equ. SUS316)				
			Vent/Drain plugs SUS 316				
			Wetted parts center body: Membrane: SUS316L, Others: SUS316				
		1	Fill fluid: regular type silicone oi				
		H	Process connection: Front NPT 1/2" female thread with adapter flange				
		-00000-					
		P	with display (0-100% linea scales)				
		3	FM Explosion proof				
			-				
		C7	Custom calibration (with calibration certificate)				
			Please state Span when ordering: LRV, URV				
		E9	Mounting Bracket				
5	STD930-E1H-00000-RWAJ-E5E9F2		Diff. Pressure Transmitter	8	583,00	4 664,00	8
			Model STD 930 - ST3000 Serie 900				
			Gewicht: 4,4 kg				
		<u>Code</u>	<u>Description</u>				
		STD920-	Model number				
		E	Meterbody cover + Adapter flange: SCS14A (equ. SUS316)				
			Vent/Drain plugs SUS 316				
			Wetted parts center body: Membrane: SUS316L, Others: SUS316				
		1	Fill fluid: regular type silicone oi				
		H	Process connection: Front NPT 1/2 female thread with adapter flange				
		-00000-					
		R	with display (Engineering units)				
		W	SUS304 bolts and nuts material				
		A	Corrosion resistant finish				
		J	Long vent/drain plugs				
			-				
		E5	External Zero/Span adjustment				
		E9	Mounting bracket				
		F2	Side vent/drain bottom				
6	STG960-E1R-00000-RWAJ-E5E9F2		Gage Pressure Transmitter	12	568,00	6 816,00	8
			ST3000 Serie 900 Model STG960 (100-2000 psi)				
			Weight: 4,4 kg				
		<u>Code</u>	<u>Description</u>				
		STG960-	Medium Gage Pressure Transmitter				
		E	Meterbody cover + Adapter flange: SCS14A (equ. SUS316)				
			Vent/Drain Plugs SUS 316				
			Wetted parts center body: Membrane: SUS316L, Others: SUS316				
		1	Fill fluid: regular type silicone oi				
		R	Process connection: Top of bottom: NPT 1/2" female thread with adapter flange				
		-00000	Code				
		R	with display (Engineering units)				
		W	SUS304 bolts and nuts material				
		A	Corrosion resistant finish				
		J	Long vent/drain plugs				
			-				
		E5	External Zero/Span adjustment				
		E9	Mounting bracket				
		F2	Side vent/drain bottom				
7	Limit Switch 1LS19-J.		Limit switch	2	25,00	50,00	8

	Total	EURO	47 699,00
	Minimum Charge	EURO	0,00
	* Packing & Handling charges	EURO	0,00
	Freight Charge	EURO	
	Sub-total	EURO	47 699,00
	VAT 21%	EURO	
	Total	EURO	47 699,00

REMARKS:

- * Lead time may be changed depending on the condition of the outstanding orders at our factory side.
- * For our export procedure, End User Name + Country + End Use (company's main activity, product) must be specified on your Purchase Order Sheet.
- * Before shipping the goods please take notice that the payment must be registered in our Bank account.

TERMS and CONDITIONS:

- Trade Terms:** FCA JAPAN / Direct shipment from Japan by Air (Freight collect) by our forwarder, Unless otherwise instructed on your order sheet.
- Payment Terms:** Advance payment by T/T remittance
- Minimum Order Amount:** Euro 150 per order (Packing & Handling and Freight charges excluded).
- Partial Shipment:** Not allowed.
- Shipping Route:** By Air freight
- Validity:** 60 days from quotation date.
- Cancellation:** Not allowed after your order is acknowledged.

(The Trade Terms are in accordance with Incoterms 2000.)

Regis Houllier - Director
Product Division