

**ThermoPLUS Advanced Temperature  
Transmitter Integrated Sensor type  
Field mounted watertight model**

Issued : Jun. 1, 2002	Page : 4-2-3
Effective : May 1, 2008	UNIT : 1000YEN

Basic Model No.		table1	table2	Option	List Price
<b>ATT61</b>					
Output	Analog (4 -20mA)	A			98
	Digital (DE -protocol)	D			98
	Analog output with HART <sup>R</sup>	H			103
Housing	Water-proof and dust -proof structure	1			0
Electrical connection	G1 / 2	1			0
	1 / 2NPT	2			0
	M20x1.5 (with adaptor)	3			10
	Pg13.5 (with adaptor)	4			10
Integral digital meter	Without		X		0
	LCD meter for deg. C		M		20
	LCD meter for deg. F		F		20
Finish	Standard finish		S		0
	Corrosion -resistant finish		A		7
	Corrosion -proof finish		B		10
Burnout feature	Upscale		U		0
	Downscale		D		0
Options *1	No selection			X	0
	Certificate of traceability			A	10
	Mounting bracket			B	15
	Customer configurations (sensor type and measuring range) *2			C	5
	One elbow for electrical conduit			E	5
	Tropical finish			H	10
	Calibration test report			T	2

note: \*1 Up to five options may be selected simultaneously.

\*2 If it is required to configure sensor type, range and tag No. at the ex factory, please select "C" and specified specifications separately. If there is no specified specification, the unit will be configured with the default value.