

Specification

ITEM	Description	
110 -1 08 1 4 E 1 1 1 -X 1 A -6 8	Title : Smart Displacement Type Level Transmitter Model No. : SLX110-10814E111-X1A-68 Basic model : Medium type for specific gravity Output : Analog 4 to 20mA Range (mm) : 0 - 800 Process connection : Side-side flanged(S-S) Element materials : Bonnet/SUS316L, Torque tube housing/SCS16A Other materials : Torque tube/SUS316L(0 to 200 °C) Working pressure : JIS 10K RF Flange size : 1-1/2" Meter body : Left side Electrical conduit : G1/2" Watertight Build-in indicator : 0 to 100% liner scale Finish : Corrosion-resistant finish Option : Test report Material certificate	
	<p>(1)</p> <p>TAG NO. :</p> <p>Scale Range : 0 ~ 100%</p> <p>Specific gravity : 0,997</p> <p>(2)</p> <p>TAG NO. :</p> <p>Scale Range : 0 ~ 100%</p> <p>Specific gravity : 0,997</p> <p>(3)</p> <p>TAG NO. :</p> <p>Scale Range : 0 ~ 100%</p> <p>Specific gravity : 0,997</p> <p>(4)</p> <p>TAG NO. :</p> <p>Scale Range : 0 ~ 100%</p> <p>Specific gravity : 0,997</p> <p>(5)</p> <p>TAG NO. :</p> <p>Scale Range : 0 ~ 100%</p> <p>Specific gravity : 0,997</p>	