

Bosdellestraat 120/2, B-1933 ZAVENTEM, BELGIUM.
 TEL.: +32-(0)2/ 785.07.10. FAX: +32-(0)2/ 785.07.11.

To: Ingenieurbüro Eber GmbH
 Alemannenring 17
 79585 Steinen-Hüsingen
 07627 / 7083-0

Quotation No. Q20090259
 Reference XXXX
 Date: 14/12/2009
 contact Regis Houllier
 Tel: +33 3 22 54 83 47
 Fax: +33 3 22 54 83 29
regis.houllier@airlitec.com
<http://eu.azbil.com>

Item	Model-Code	Description	QTY	Price/Unit (EUR)	Amount (EUR)
1	PTG72G-N6B1G4-M-X	Gauge Pressure Transmitter: Screw connection type with HART Communication <u>Code Description</u> PTG72G Gauge Pressure Transmitter w. HART Communication N Water and dust proof: IEC IP67, Electrical conduit:1/2NPT 6 Measuring span: 1 to 10MPa B1 Material Diaphragm / wetted parts other than diaphragm /fill fluid: SS316L / SS316 / Silicone oil G4 Process connection: G½ male screw M Built-in digital indicator (Set Span 2,5 MPa) Calibration range and display : 0 to 2,5Mpas	3	344,00	1 032,00
2	GTX30D-BAAAFBB-BXXAXAX-R1	Differential-Pressure-Transmitter AT9000 Series Working pressure: 0,02 (abs.)-35 bar, Weight: 3,6 kg <u>Code Description</u> GTX30D- Measuring span: -1 bis +1 bar, Spanne: 5-1000 mbar B Output: 4 to 20mA (HART Communication) A Fill Fluid: Regular type (Silicone oil) A Meterbody cover: SCS14A (equivalent: SUS316) Vent- Drain plugs: 316 SST A Material (centerbody): SUS316, Diaphragm: SUS316L F Process connections: 1/4 NPT internal thread, without adapter flange B Process installation: Vertical piping, bottom connection (gas) B Bolt/nut: SUS304 SST B Electrical connection: M20x1,5 (watertight) XX None no Ex Zone A With indicator X Paint Standard A Failure alarm: upscale X no Mounting bracket R1 Custom calibration : 0 - 5 kPa, Square root output for flow measurement	2	460,00	920,00
3	G5VMPF2	5 ways Manifold SUS316 Process connection 1/2 NPT Including Bolts 7/16 UNF	2	230,00	460,00
TOTAL				EURO	2 412,00
MINIMUM ORDERING CHARGE				EURO	0,00
PACKING				EURO	0,00
FREIGHT				EURO	0,00
TOTAL				EURO	2 412,00

REMARKS: