8) Single - I / P Converter

Basic Model No. Selection Option

Model No. : KUX112 - [I][II][III][IV][V][VI] - [VI]

Description			Selection													
			I Power Source	II Input	III Output				IV Connection		V Mounting	VI Environment			VII Options
Model No. Example KUX112 - X11ASX - X Notes) IV : Air Connection			None	4 to 20mA DC	0.2 to 1.0kgf / cm^2	3 to 15psi	0.2 to 1.0bar	20 to 100kPa	Rc 1 / 4	1 / 4 NPT, internal thread	Wall mount, indoor installation	Standard	For tropical service	Corrosive atmosphere	No option
	Model No.		X	1	1	2	3	4	A	B	S	X	A	B	- X
	Basic Model No.	Price	0	0	0	0	0	0	0	0	0	0	*	*	0
SINGLE - I / P Converter	KUX112	227	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔			✔

* quoted upon request

9) FIELD - TYPE I / P Converter

Basic Model No. Selection Option

Model No. : KUX113 - [I][II][III][IV][V][VI] - [VI]

Description			Selection																											
			I Power source	II Case					III Input	IV Output								V Connection		VI Environment				VII Options						
Model No. Ex. KUX113 - XW11AX - X			None	Weather proof type	JIS Flameproof type	JIS Intrinsically Safe type	FM Explosion proof type	FM Intrinsically Safe type	4 to 20mA	0.2 to 1.0 kgf / cm2	3 to 15 psi	0.2 to 1.0 bar	20 to 100 kPa	19.6 to 98.1 kPa	20 to 100kPa Double scale (kPa/kgf/cm2)	0.2 to 1.0kPa Double scale (kPa/kgf/cm2)	Air connection Rc 1 / 4	Air connection 1 / 4 NPT	Standard	Corrosion resistant paint	Heavy corrosion resistant paint	Silver finish	No option	With one flameproof packing (Available for JIS Flameproof only)	With output gauge	With by - pass set	With Pressure regulator with filter	With air piping elbow (material : SUS304)	1/2 NPT internal thread electrical conduit
	Model No.		- X	W	E	H	F	M	1	1	2	3	4	8	A	D	A	B	X	A	B	D	X	P	G	6	7	J	N
	Basic Model No.	Price	0	0	5	5	15	15	0	0	0	0	0	0	5	5	0	0	0	10	15	8	0	10	11		26	2	0
FIELD - TYPE I / P Converter	KUX113	286	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔		✔		✔