

Advanced Temperature Transmitter with FOUNDATION™ fieldbus

Issued : Jan. 1, 2003	Page : 4-2-1 (F)
Effective : Feb. 1, 2009	UNIT : 1000YEN

Basic Model No.				Option		List price(JPY)
ATT60						
Output	FOUNDATION™ Fieldbus *1	F				173
Housing	Water -proof and dust -proof structure	1				0
Electrical conduit connection	G1 / 2	1				0
	1 / 2NPT	2				0
	M20x1.5(with adaptor)	7				10
	Pg13.5(with adaptor)	8				10
Integral digital meter	Without		X			0
	LCD meter for deg. C *2		M			20
	LCD meter for deg. F *2		F			20
Finish	Standard finish		S			0
	Corrosion -resistant finish		A			7
	Corrosion -proof finish		B			10
Burnout feature	No selection		X			0
Options *3	Traceability certificate			A		10
	Mounting bracket			B		15
	Customer configurations(sensor type and measuring range) *4			C		5
	Two elbows for electrical conduits *5			F		10
	Calibration test report			T		2
	Fieldbus communication stack BASIC class			1		0

note: *1 Fieldbus communication stack BASIC class "code 1" in the Option must be selected.

*2 If sensor type is [mV], Engineering unit is displayed in [mV].

*3 Up to five options may be selected simultaneously.

*4 If it is required to configure sensor type, range and tag No. at the ex factory, please select "C" and specified specifications separately. If there is no specified specification, the unit will be configured with the default value.

*5 Only applicable for the G1/2 "code 1" in the Electrical connection.