

Model GTX32D(Highest static pressure type for standard differential pressure)

Model GTX42D(Highest static pressure type for high differential pressure)

Model GTX72D(Highest static pressure type for highest differential pressure)

Model No.:GTX__D-Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Issued : Jul. 1, 2008	Page : 1-0-4
Effective : Dec. 1, 2009	UNIT : 1000YEN

Basic Model No.

Measuring span	0.5 to 100kPa (50 to 10160mmH2O)	GTX32D
	35 to 700kPa (0.35 to 7kgf/cm2)	GTX42D
	0.25 to 14MPa (2.5 to 140kgf/cm2)	GTX72D

Basic price
396
468

Selection I

I	Output	4 to 20mA (SFN Communication)	A
		4 to 20mA (HART Communication)	B
		Digital output(DE communication)*7	D
II	Fill Fluid	Regular type (Silicone oil)	A
		For oxygen service (Fluorine oil)	H
III	Material (Meterbody cover, Vent/Drain plugs)	Meterbody cover	A
		Vent / Drain plugs	A
IV	Material (centerbody)	SUS316 (Diaphragm:SUS316L)	A
V	Process connections	Rc 1/4, without adapter flange	C
		1/4 NPT internal thread, without adapter flange	F
VI	Process installation	Vertical piping, top connection	A
		Vertical piping, bottom connection	B
VII	Bolt/nut	Carbon steel	A
		304 SST *5	B
		630 SST	C

Additional price
0
5
0
0
18

0
0
0
0
0
0
0
0
0
0
20
100

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *6	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
		NEPSI Type n	N5
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof	B
		Corrosion-resistant (Silver coating)	D
V	Failure alarm	UP scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat form)	5
		304 SST (Flat form)	6

0
5
0
8
8
8
8
8
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
0
2
10

Note)

*5 When 304 SST bolt/nut is selected, max working pressure rating is 23MPa(230kgf/cm2).

*6 Not applicable for the combination with code F1 "FM Explosion proof" of Explosion proof.

*7 Not applicable for the combination with code A1 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model No. GTX__D-Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Option		Additional price
XX	No options	0
A1	Adapter flange for corrosion-resistant application (316L SST or Tantalum for the wetted parts of centerbody)	15
A2	With external Zero/Span adjustment*11*16	30
F1	PED (97/23/EC) Conformity *1*2*3	30
G1	One elbow (left) *6*7*10	2
G2	One elbow (right) *6*7*10	2
G3	2 elbows *6*8*10	4
G4	Long vent/drain plugs	5
G6	Side vent/drain top *6	4
G7	Side vent/drain bottom *6	4
K1	Oil and water free finish	17
K3	Oil free finish *4	10
L1	Au Plating Diaphragm*15	TOKUMI
Q1	Safety Transmitter *5*16	0
Q2	NAMUR NE43 Compliant Output signal limits:3.8 to 20.5mA (Output 21.6mA/selected upper limit, 3.6mA/selected lower limit)*16	20
Q7	Alarm Output(contact output)	10
R1	Custom calibration	5
T1	Test report	2
T2	Mill certificate	21
T4	Traceability certificate	10
T5	NACE certificate *9	5
W1	Non SI Unit	0

Note)

- *1 "PED Conformity" is not applicable for the combination with FM,IECEx, KOSHA or NEPSI approvals.
- *2 "PED Conformity" is not applicable for the combination with GTX15D,30D, or 40D.
- *3 Not applicable for the combination with "304 SST Bolts/Nuts"
- *4 No need to select when Fill Fluid code H, or J is selected.
- *5 Not applicable for the combination with code A2,or Q7 of Option.
- *6 Not applicable for the combination with code A, or B of Process installation.
- *7 Not applicable for the combination with code F1 "FM Explosion proof" of Explosion proof.
- *8 Not applicable for any Explosion proof. Please select code XX "None" of Explosion proof.
- *9 Applicable for "ASTM B575", code B of Material (center body).
- *10 Not applicable for the combination with code B "M20 watertight" of Electrical connection.
- *11 Not applicable for the combination with code X "None" of Indicator. Please select "With indicator".
- *15 Not applicable for the combination with "Tantalum" of Material(center body).
- *16 Not applicable for the combination with code D "Digital output(DE communication)" of output