



Azbil Europe NV



Issue date: August 1st 2009
Validity: End of 2009
Currency: Euro

List Pricelist 2009

SDC25/26: Digital Indicating Controller

Decoding Table :		No space between each table																			
<table border="1" style="width: 100%; text-align: center;"> <tr> <td>---</td> <td>-</td> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>--</td> </tr> <tr> <td>I</td> <td>II</td> <td>III</td> <td>IV</td> <td>V</td> <td>VI</td> <td>VII</td> <td>VIII</td> </tr> </table>		---	-	--	-	-	-	-	--	I	II	III	IV	V	VI	VII	VIII				
---	-	--	-	-	-	-	--														
I	II	III	IV	V	VI	VII	VIII														
Table I	Description	Selection																			
	Digital Indicating Controller 48*96	C25	↓	230																	
	Digital Indicating Controller 96*96	C26	↓	261																	
Table II	Mounting and Wiring																				
	Panel mount with Terminals	T	* *	0																	
Table III	Controller Output Type																				
		Output 1	Output 2																		
	Relay	None	R0	* *	0																
	Voltage (SSR Drive)	None	V0	* *	0																
	Voltage (SSR Drive)	Current	VC	* *	42																
	Voltage (SSR Drive)	Voltage (SSR Drive)	VV	* *	32																
	Current	None	C0	* *	42																
	Current	Current	CC	* *	84																
Table IV	Analog Input Type																				
	Universal Input Type	U	* *	0																	
Table V	Power Supply																				
	100-240Vac	A	* *	0																	
	24-48Vac/dc	D	* *	32																	
Table VI	Option 1																				
	3 Event Relays	1	* *	0																	
	3 Event Relays and 1 Aux. output (current)	2	* *	42																	
	(See note 1) 2 independant Event Relays	4	* *	0																	
	" 2 independant Event Relays and 1 Aux. (current)	5	* *	42																	
Table VII	Option 2																				
	None	0	* *	0																	
	(See note 2) 2 current transf. & 4 Digital Inputs	1	* *	42																	
	" 2 current transf. & 4 Digital Inputs & RS485 Com	2	* *	84																	
Table VIII	Additional processing																				
	None	00	* *	0																	
	Inspection certificate	D0	* *	25																	

Note 1: Cannot be selected with option "D" in table V (DC model)

Note 2: Current transformer is sold separately, see below accessories

Accessories			
Description	Reference #	Availability	
Cable for PC Software	81440793-001	*	120
Smart PC Loader	SLP-C35	*	368
Current transformer (5.8 mm hole diameter)	QN206A	*	45
Current transformer (12 mm hole diameter)	QN212A	*	73
Mounting bracket (any model)	81409654-001	*	13
Mask cover (soft) 48*96	81441121-001		N/A
Mask cover (soft) 96*96	81441122-001		N/A
Mask cover (hard) 48*96	81446915-001	*	37
Mask cover (hard) 96*96	81446916-001	*	37
Solid State Relay, Din Rail, with Heat Sink (15 amp)	PGM10F015	*	55
Solid State Relay, Din Rail, with Heat Sink (25 amp)	PGM10F025	*	65
Terminal cover 48*96	81446912-001	*	15
Terminal cover 96*96	81446913-001	*	15