



Azbil Europe NV



Issue date: August 1st 2009
 Validity: End of 2009
 Currency: Euro

List Pricelist 2009 SDC35/36: Digital Indicating Controller

Decoding Table : No space between each table

I	II	III	IV	V	VI	VII	VIII
---	----	-----	----	---	----	-----	------

Description		Selection		
Table I	Digital Indicating Controller 48*96	C35	↓	368
	Digital Indicating Controller 96*96	C36	↓	387

Mounting and Wiring				
Table II	Panel mount with Terminals	T	* *	0

	Controller Output Type				
	Output 1	Output 2			
Table III (See note 3)	Relay	None	R0	* *	0
	Relays for motor drive*	None	R1	* *	74
	Voltage (SSR Drive)	None	V0	* *	0
	Voltage (SSR Drive)	Current 4 - 20mA	VC	* *	42
	Voltage (SSR Drive)	Linear DC 0 - 10V	VD	* *	42
	Voltage (SSR Drive)	Voltage (SSR Drive)	VV	* *	32
	Current 4 - 20mA	None	C0	* *	42
	Current 4 - 20mA	Current 4 - 20mA	CC	* *	84
	Current 4 - 20mA	Linear DC 0 - 10V	CD	* *	84
	Linear DC 0 - 10V	None	D0	* *	42
	Linear DC 0 - 10V	Linear DC 0 - 10V	DD	* *	84

Analog Input Type				
Table IV	Universal Input Type	U	* *	0

Power Supply				
Table V	100-240Vac	A	* *	0
	24-48Vac/dc	D	* *	32

Option 1				
Table VI (See note 1)	3 Event Relays	1	* *	0
	3 Event Relays and 1 Aux. output (current)	2	* *	42
	3 Event Relays and 1 Aux. output (volt)	3	* *	42
	2 independant Event Relays	4	* *	0
	" 2 independant Event Relays and 1 Aux. (current)	5	* *	42
	" 2 independant Event Relays and 1 Aux. (volt)	6	* *	42

Option 2				
Table VII (See note 2 & 3)	None	0	* *	0
	2 current transf. & 4 Digital Inputs	1	* *	42
	" 2 current transf. & 4 Digital Inputs & RS485 Com	2	* *	84
	" 2 current transf. & 2 Digital Inputs & RSP	3	* *	84
	" 2 current transf. & 2 Digital Inputs & RSP & RS485	4	* *	126

Additional processing				
Table VIII	None	00	* *	0
	Inspection certificate	D0	* *	25

Note 1: Cannot be selected with option "D" in table V (DC model)
 Note 2: Current transformer is sold separately, see below accessories
 Note 3: When R1 is selected for table III, current transformer option 2 is not available.
 Motor feedback input is available

Accessories			
Description	Reference #	Availability	
Cable for PC Software	81440793-001	*	120
Smart PC Loader	SLP-C35	*	368
Smart PC Loader with PID Simulator	SLP-C35PRO	*	520
Current transformer (5.8 mm hole diameter)	QN206A	*	45
Current transformer (12 mm hole diameter)	QN212A	*	73
Mounting bracket (any model)	81409654-001	*	13
Mask cover (soft) 48*96	81441121-001		N/A
Mask cover (soft) 96*96	81441122-001		N/A
Mask cover (hard) 48*96	81446915-001	*	37
Mask cover (hard) 96*96	81446916-001	*	37
Solid State Relay, Din Rail, with Heat Sink (15 amp)	PGM10F015	*	55
Solid State Relay, Din Rail, with Heat Sink (25 amp)	PGM10F025	*	65
Terminal cover 48*96	81446912-001	*	15
Terminal cover 96*96	81446913-001	*	15