

MODEL SELECTION

Issued: Jul. 1, 2008 Page: 1-0-17
 Effective: Feb. 1, 2011 UNIT: 1000YEN

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Flush 3 inches flange type for regular/ high temperature/ oxygen/ chlorine service)

Model No.:GTX R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O) 35 to 700kPa (0.35 to 7kgf/cm ²)	GTX35R GTX40R	Flush flange type 3 inches (80mm)
----------------	---	------------------	-----------------------------------

Selection I

I	Output	4 to 20mA (SFN Communication)	A		
		4 to 20mA (HART Communication)	B		
		Digital output(DE communication)*5	D		
II	Fill Fluid	Regular type (Silicone oil)	A		
		For high temperature service (Silicone oil)	B		
		For oxygen service (Fluorine oil)	H		
		For chlorine service(Fluorine oil) *2	J		
III	Wetted parts material	316 SST (Diaphragm:316L SST)	A		
		ASTM B575 (Equivalent to Hastelloy C-276)	B		
		Tantalum *1	C		
		316L SST	D		
IV	Flange rating	ANSI150	A1		
		ANSI300	A2		
		ANSI600	A3		
		JIS10K	J1		
		JIS20K	J3		
		JIS30K	J4		
		JIS63K	J6		
		JP150	P1		
		JP300	P2		
		JP600	P3		
		V	Flange size	3in./80A	F
		VI	Flange type	Flush type	A

VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		304 SST	304 SST	A
		304 SST	630 SST	C
		304 SST	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
		316L SST	Carbon steel	M

VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A
IX	Capillary length	2m	02
		3m	03
		4m	04
		5m	05
		6m	06
		7m	07
		8m	08
		9m	09
		10m	10
		2m (with Olefin Cover)	A2
		3m (with Olefin Cover)	A3
		4m (with Olefin Cover)	A4
		5m (with Olefin Cover)	A5
		6m (with Olefin Cover)	A6
		7m (with Olefin Cover)	A7
		8m (with Olefin Cover)	A8
		9m (with Olefin Cover)	A9
		10m (with Olefin Cover)	A0

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *4	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
		NEPSI Type n	N5
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6
		Direct mounting kit*3	D

Basic price
589
601

Additional price
0
5
0
0
62
62
62
0
155
250
40
0
15
20
0
0

10
20
0
90
100
80
110
120
100
0
5
10
20
30
40
50
60
70
80
25
30
40
50
60
70
80
90
100

0
5
0
8
8
8
8
8
8
8
8
8
8
8
8
8
8
8
8
20
0
14
16
0
0
0
2
6
10
30

*1 In case "Tantalum " is used for diaphragm material and in case of "For high-temperature service", normal operating temperaturer of wetted parts is -10 to +180deg.C
 *2 In case code J is selected, code C "Tantalum" of Wettedparts material should be selected.
 *3 Not applicable for "For high temperature service", code B of Fill Fluid.
 *4 Not applicable for the combination with code F1and F6 of Explosion proof.
 *5 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Extended 4 inches flange type for regular/ high temperature/ oxygen service)

Issued: Jul. 1, 2008 Page: 1-0-18
 Effective: Feb. 1, 2011 UNIT: 1000YEN

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Extended flange type 4 inches (100mm)
	35 to 700kPa (0.35 to 7kgf/cm ²)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*4	D	
II	Fill Fluid	Regular type (Silicone oil)*6	A	
		For high temperature service (Silicone oil) *1*5	B	
		For oxygen service (Fluorine oil)*6	H	
III	Wetted parts material	316 SST (Diaphragm:316L SST)*4	A	
		316L SST*1*5*6	D	
IV	Flange rating	ANSI150	A1	
		ANSI300*1	A2	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K*5*6	J4	
		JPI150	P1	
		JPI300*1	P2	
V	Flange size	4in./100A	G	
VI	Flange type	Extended Length 50mm	B	
		Extended Length 100mm	C	
		Extended Length 150mm*6	D	
		Extended Length 200mm*6	E	
		Extended Length 250mm *1*6	F	
		Extended Length 300mm *1*6	G	
VII	Flange material/bolt and nut material	Flange		
		304 SST	304 SST	A
		304 SST	630 SST	C
		304 SST	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
316L SST	Carbon steel	M		
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	
		6m	06	
		7m	07	
		8m	08	
		9m	09	
		10m	10	
		2m (with Olefin Cover)	A2	
		3m (with Olefin Cover)	A3	
		4m (with Olefin Cover)	A4	
		5m (with Olefin Cover)	A5	
		6m (with Olefin Cover)	A6	
		7m (with Olefin Cover)	A7	
		8m (with Olefin Cover)	A8	
		9m (with Olefin Cover)	A9	
10m (with Olefin Cover)	A0			

Additional price
0
5
0
0
62
62
0
120
0
15
0
25
40
0
15
0
123
136
150
175
189
200
10
20
0
90
100
80
110
120
100
0
5
10
20
30
40
50
60
70
80
25
30
40
50
60
70
80
90
100

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *3	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
		NEPSI Type n	N5
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6
		Direct mounting kit*2	D

0
5
0
8
8
8
8
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
5
10
30

*1 In case Fill Fluid: For high-temperature service and Flange Rating: ANSI/JPI300 and Wetted Parts material: 316L SST, Extended length of flange 250/300mm are not available.
 *2 Not applicable for "For high temperature service", code B of Fill Fluid.
 *3 Not applicable for the combination with code F1 and F6 of Explosion proof.
 *4 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.
 *5 In case Fill Fluid: For high-temperature service, not applicable for the combination with wetted parts material "316L" and Flange Type "JIS30K"
 *6 In case Fill Fluid: Regula type or for oxgen service and Flange rating: JIS30K and wetted parts material: 316L SST, Extension length of Flange 150/200/250/300mm are not available.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Flush 2 inches, 1.5inches flange type for regular/ high temperature/ oxygen service)

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Flush flange type 2 inches (50mm), 1.5 inches(40mm)
	35 to 700kPa (0.35 to 7kgf/cm ²)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*7	D	
II	Fill Fluid	Regular type (Silicone oil)	A	
		For high temperature service (Silicone oil)	B	
		For oxygen service (Fluorine oil)	H	
		For chlorine service(Fluorine oil)*5	J	
III	Wetted parts material	316 SST Diaphragm:316L SST	A	
		ASTM B575 (Equivalent to Hastelloy C-276)	B	
		Tantalum *1*2	C	
		316L SST	D	
IV	Flange rating	ANSI150	A1	
		ANSI300	A2	
		ANSI600	A3	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K	J4	
		JIS63K	J6	
		JP150	P1	
		JP1300	P2	
		JP1600	P3	
		V	Flange size	1.5in./40A*2
2in./50A	E			
VI	Flange type	Flush type	A	
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		304 SST	304 SST	A
		304 SST	630 SST	C
		304 SST	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
316L SST	Carbon steel	M		
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	
		2m (with Olefin Cover)	A2	
		3m (with Olefin Cover)	A3	
		4m (with Olefin Cover)	A4	
		5m (with Olefin Cover)	A5	
		-	-	-

Additional price
0
5
0
0
62
62
62
0
155
250
40
0
15
20
0
25
40
120
0
15
20
0
0
10
20
0
90
100
80
110
120
100
0
5
10
20
30
25
30
40
50

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *6	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
NEPSI Type n	N5		
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6
		Direct mounting kit*4	D

0
5
0
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
2
10
30

*1 In case "Tantalum " is used for diaphragm material and in case of "For high-temperature service", normal operating temperature of wetted parts is -10 to +180deg.C
*2 In case: Basic Model is GTX35R, and Tantalum is used for diaphragm material and Flange size is "Flush Diaphragm 1.5in./40mm", 2m or 3m (Code 02, 03, A2, or A3) for "Length of Capillary Tube " are applicable and minimum Span will be 10kPa
*4 Not applicable for "For high temperature service", code B of Fill Fluid.
*5 In case code J is selected, code C "Tantalum" of Wetted parts material should be selected.
*6 Not applicable for the combination with code F1 and F6 of Explosion proof.
*7 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Extended 3 inches, 2 inches flange type for regular/ high temperature/ oxygen service

Issued: Jul. 1, 2008	Page: 1-0-20
Effective: Feb. 1, 2011	UNIT: 1000YEN

Model No.:GTX R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

Measuring span	2.5 to 100kPa (250 to 10,160mmH)	GTX35R	Extended flange type 3 inches (80mm).
	35 to 700kPa (0.35 to 7kgf/cm ²)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*6	D	
II	Fill Fluid	Regular type (Silicone oil)	A	
		For high temperature service (Silicone oil)*3	B	
		For oxygen service (Fluorine oil)	H	
III	Wetted parts material	316 SST Diaphragm:316L SST	A	
		316L SST*3	D	
IV	Flange rating	ANSI150	A1	
		ANSI300	A2	
		ANSI600*2*3	A3	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K	J4	
		JIS63K	J6	
		JPI150	P1	
		JPI300	P2	
		JPI600*2*3	P3	
		V	Flange size	2in./50A*3
3in./80A*2	F			
VI	Flange type	Extended Length 50mm	B	
		Extended Length 100mm	C	
		Extended Length 150mm	D	
		Extended Length 200mm*3	E	
		Extended Length 250mm*3	F	
		Extended Length 300mm*3	G	
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		SUS304	SUS304	A
		SUS304	630 SST	C
		SUS304	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
316L SST	Carbon steel	M		
VIII	Gasket face finish	None Standard JISR3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	
		2m (with Olefin Cover)	A2	
		3m (with Olefin Cover)	A3	
		4m (with Olefin Cover)	A4	
		5m (with Olefin Cover)	A5	

Additional price
0
5
0
0
62
62
0
120
0
15
20
0
25
40
40
15
20
0
0
123
136
150
175
189
200

10
20
0
90
100
80
110
120
100

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *5	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
NEPSI Type n	N5		
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6
		Direct mounting kit*4	D

0
5
0
8
8
8
8
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
2
10
30

*2 Not applicable for the combination with Flange rating "ANSI/JPI600" and Flange size "3in./80A".

*3 In case Fill Fluid: For high-temperature service, Wetted Parts material "316L SST", Flange Rating: "ANSI/JPI600" and Flange size "2 in./80A" Extension length of Flange 200/250/300mm are not available.

*4 Not applicable for "For high temperature service", code B of Fill Fluid.

*5 Not applicable for the combination with code F1 and F6 of Explosion proof.

*6 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Combination extended 4 inches: flash 3in. flange type for regular/ high temperature/ oxygen service)

Issued: Sep. 10, 2010 Page: 1-0-21
 Effective: Feb. 1, 2011 UNIT: 1000YEN

Model No.:GTX__R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.				Basic price	
Measuring span	2.5 to 100kPa (250 to 10,160mmH)	GTX35R	Combination 3in. flash:4in. extended	589	
	35 to 700kPa (0.35 to 7kgf/cm ²)	GTX40R		601	
Selection I				Additional price	
I Output	4 to 20mA (SFN Communication)	A		0	
	4 to 20mA (HART Communication)	B		5	
	Digital output(DE communication)*4	D		0	
				0	
II Fill Fluid	Regular type (Silicone oil)*6	A		0	
	For high temperature service (Silicone oil) *1*6	B		62	
	For oxygen service (Fluorine oil)*6	H		62	
III Wetted parts material	316 SST (Diaphragm:316L SST)*4	A		0	
	316L SST*1*5*6	D		120	
IV Flange rating	ANSI150	A1		0	
	ANSI300*1	A2		15	
	JIS10K	J1		0	
	JIS20K	J3		25	
	JIS30K*5*6	J4		40	
	JPI150	P1		0	
	JPI300*1	P2		15	
				15	
V Flange size	Combination 3*flash:4*extended flange	R		0	
VI Flange type	Extended Length 50mm	B		123	
	Extended Length 100mm	C		136	
	Extended Length 150mm*6	D		150	
	Extended Length 200mm*6	E		175	
	Extended Length 250mm *1*6	F		189	
	Extended Length 300mm *1*6	G		200	
VII Flange material/bolt and nut material	Flange	Bolt/nut			
	304 SST	304 SST	A	10	
	304 SST	630 SST	C	20	
	304 SST	Carbon steel	D	0	
	316 SST	304 SST	E	90	
	316 SST	630 SST	G	100	
	316 SST	Carbon steel	H	80	
	316L SST	304 SST	J	110	
	316L SST	630 SST	L	120	
	316L SST	Carbon steel	M	100	
VIII Gasket face finish	None Standard JISRa3.2(12.5S)	A		0	
IX Capillary length	2m	02		5	
	3m	03		10	
	4m	04		20	
	5m	05		30	
	6m	06		40	
	7m	07		50	
	8m	08		60	
	9m	09		70	
	10m	10		80	
	2m (with Olefin Cover)	A2		25	
	3m (with Olefin Cover)	A3		30	
	4m (with Olefin Cover)	A4		40	
	5m (with Olefin Cover)	A5		50	
	6m (with Olefin Cover)	A6		60	
	7m (with Olefin Cover)	A7		70	
	8m (with Olefin Cover)	A8		80	
	9m (with Olefin Cover)	A9		90	
	10m (with Olefin Cover)	A0		100	
	Selection II				
	I Electrical connection	1/2 NPT, Watertight	A		0
M20, Watertight *3		B		5	
II Explosion proof	None	XX		0	
	FM Explosionproof	F1		8	
	FM Intrinsically safe	F2		8	
	FM Nonincendive	F5		8	
	Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6		8	
	ATEX Explosionproof	A1		8	
	ATEX Intrinsically safe	A2		8	
	ATEX Type n	A5		8	
	IECEX Explosionproof	E1		8	
	IECEX Intrinsically safe	E2		8	
	IECEX Type n	E5		8	
	NEPSI Explosionproof	N1		8	
	NEPSI Intrinsically safe	N2		8	
NEPSI Type n	N5		8		
III Indicator	None	X		0	
	With indicator	A		20	
IV Paint	Standard	X		0	
	Corrosion-proof (Urethane)	H		14	
	Corrosion-resistant (Silver color)	D		16	
V Failure alarm	UP Scale	A		0	
	DOWN scale	B		0	
VI Mounting	None	X		0	
	Carbon steel (Flat Form)	5		2	
	304 SST (Flat Form)	6		10	
	Direct mounting kit*2	D		30	

- *1 In case Fill Fluid: For high-temperature service and Flange Rating: ANSI/JPI300 and Wetted Parts material: 316L SST, Extended length of flange 250/300mm are not available.
- *2 Not applicable for "For high temperature service", code B of Fill Fluid.
- *3 Not applicable for the combination with code F1 and F6 of Explosion proof.
- *4 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.
- *5 In case Fill Fluid: For high-temperature service, not applicable for the combination with watted parts mateiral "316L" and Flange T
- *6 In case Fill Fluid: Regula type or for oxgen service and Flange rating: JIS30K and wetted parts material: 316L SST, Extension length of Flange 150/200/250/300mm are not available.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Combination extended 3 inches: flash 2in. flange type for regular/ high temperature/ oxygen service)

Issued: Sep. 10, 2010	Page: 1-0-22
Effective: Feb. 1, 2011	UNIT: 1000YEN

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Combination 2in. flash and 3 in. extended flange
	35 to 700kPa (0.35 to 7kgf/cm ²)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*6	D	
II	Fill Fluid	Regular type (Silicone oil)	A	
		For high temperature service (Silicone oil)	B	
		For oxygen service (Fluorine oil)	H	
III	Wetted parts material	316 SST Diaphragm:316L SST	A	
		316L SST	D	
IV	Flange rating	ANSI150	A1	
		ANSI300	A2	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K	J4	
		JPI150	P1	
		JPI300	P2	
V	Flange size	Combination 2in. flash and 3in. extended flange	P	
VI	Flange type	Extended Length 50mm	B	
		Extended Length 100mm	C	
		Extended Length 150mm	D	
		Extended Length 200mm	E	
		Extended Length 250mm	F	
		Extended Length 300mm	G	
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		SUS304	SUS304	A
		SUS304	630 SST	C
		SUS304	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
316L SST	Carbon steel	M		
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	
		2m (with Olefin Cover)	A2	
		3m (with Olefin Cover)	A3	
		4m (with Olefin Cover)	A4	
		5m (with Olefin Cover)	A5	

Additional price
0
5
0
0
62
62
0
120
0
15
0
25
40
0
15
0
123
136
150
175
189
200

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *5	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
NEPSI Type n	N5		
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6
		Direct mounting kit*4	D

10
20
0
90
100
80
110
120
100
0
5
10
20
30
25
30
40
50
0
5
0
8
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
2
10
30

*4 Not applicable for "For high temperature service", code B of Fill Fluid.

*5 Not applicable for the combination with code F1 and F6 of Explosion proof.

*6 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Flush 3 inches flange type for high temperature vacuum, high temperature high vacuum service

Issued: Jul. 1, 2008	Page: 1-0-23
Effective: Feb. 1, 2011	UNIT: 1000YEN

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.			
Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O) 35 to 700kPa (0.35 to 7kgf/cm ²)	GTX35R GTX40R	Flush flange type 3 inches (80mm)

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*3	D	
II	Fill Fluid	For high temperature vacuum service (Silicone oil)	C	
		For high temperature high vacuum service (Silicone oil)	D	
III	Wetted parts material	ASTM B575 (Equivalent to Hastelloy C-276)	B	
		Tantalum*1	C	
		316L SST	D	
IV	Flange rating	ANSI150	A1	
		ANSI300	A2	
		ANSI600	A3	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K	J4	
		JIS63K	J6	
		JPI150	P1	
		JPI300	P2	
		JPI600	P3	
		V	Flange size	3in./80A
VI	Flange type	Flush type	A	
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		304 SST	304 SST	A
		304 SST	630 SST	C
		304 SST	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
316L SST	Carbon steel	M		
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	
		6m	06	
		7m	07	
		8m	08	
		9m	09	
		10m	10	

Additional price

0
5
0
500
900
155
250
40
0
15
20
0
25
40
120
0
15
20
0
0
10
20
0
90
100
80
110
120
100
0
5
10
20
30
40
50
60
70
80

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *2	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEx Explosionproof	E1
		IECEx Intrinsically safe	E2
		IECEx Type n	E5
		NEPSI Explosionproof	N1
NEPSI Intrinsically safe	N2		
NEPSI Type n	N5		
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6

0
5
0
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
0
2
10

*1 In case "Tantalum " is used for diaphragm material, and in case of " For high-temperature service", normal operating temperature of wetted parts is -10 to +180deg.C
 *2 Not applicable for the combination with code F1 and F6 of Explosion proof.
 *3 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Extended 4 inches flange type for high temperature vacuum, high temperature high vacuum service

Issued: Jul. 1, 2008	Page: 1-0-24
Effective: Feb. 1, 2011	UNIT: 1000YEN

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Extended flange type 4 inches (100mm)
	35 to 700kPa (0.35 to 7kgf/cm ²)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*3	D	
II	Fill Fluid	For high temperature vacuum service (Silicone oil)	C	
		For high temperature high vacuum service (Silicone oil)	D	
III	Wetted parts material	316 SST (Diaphragm:316L SST)	A	
		316L SST*1*4	D	
IV	Flange rating	ANSI150	A1	
		ANSI300*1	A2	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K*4	J4	
		JPI150	P1	
		JPI300*1	P2	
V	Flange size	4in./100A	G	
VI	Flange type	Extended Length 50mm	B	
		Extended Length 100mm	C	
		Extended Length 150mm	D	
		Extended Length 200mm*1	E	
		Extended Length 250mm*1	F	
		Extended Length 300mm*1	G	
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		304 SST	304 SST	A
		304 SST	630 SST	C
		304 SST	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
316L SST	Carbon steel	M		
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	
		6m	06	
		7m	07	
		8m	08	
		9m	09	
		10m	10	

Additional price
0
5
0
500
900
0
120
0
15
0
25
40
0
15
0
123
136
150
175
189
200

10
20
0
90
100
80
110
120
100
0
5
10
20
30
40
50
60
70
80

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *2	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
NEPSI Type n	N5		
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6

0
5
0
8
8
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
2
10

*1 In case "ANSI/JPI300" is used for Flange Rating and "316L SST" is used for wetted parts material, not available for Extended length 200/250/300mm.
 *2 Not applicable for the combination with code F1 and F6 of Explosion proof.
 *3 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.
 *4 Not applicable for the combination with watted parts material "316L SST" and Flange rating "JIS30K".

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Flush 2 inches,1.5 inches flange type for high temperature vacuum, high temperature high vacuum service

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

	Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Flush flange type 2 inches (50mm), 1.5 inches(40mm)
		35 to 700kPa (0.35 to 7kgf/cm ²)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*3	D	
II	Fill Fluid	For high temperature vacuum service (Silicone oil)	C	
		For high temperature high vacuum service (Silicone oil)	D	
III	Wetted parts material	ASTM B575 (Equivalent to Hastelloy C-276)	B	
		Tantalum*1	C	
		316L SST	D	
IV	Flange rating	ANSI150	A1	
		ANSI300	A2	
		ANSI600	A3	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K	J4	
		JIS63K	J6	
		JPI150	P1	
		JPI300	P2	
		JPI600	P3	
V	Flange size	1.5in./40A	D	
		2in./50A	E	
VI	Flange type	Flush type	A	
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		304 SST	304 SST	A
		304 SST	630 SST	C
		304 SST	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
316L SST	Carbon steel	M		
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	

Additional price
0
5
0
500
900
155
250
40
0
15
20
0
25
40
120
0
15
20
0
0
0

Selection II

I	Electrical connection	1/2 NPT, Watertight	A	
		M20, Watertight *2	B	
II	Explosion proof	None	XX	
		FM Explosionproof	F1	
		FM Intrinsically safe	F2	
		FM Nonincendive	F5	
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6	
		ATEX Explosionproof	A1	
		ATEX Intrinsically safe	A2	
		ATEX Type n	A5	
		IECEx Explosionproof	E1	
		IECEx Intrinsically safe	E2	
		IECEx Type n	E5	
		NEPSI Explosionproof	N1	
		NEPSI Intrinsically safe	N2	
NEPSI Type n	N5			
III	Indicator	None	X	
		With indicator	A	
IV	Paint	Standard	X	
		Corrosion-proof (Urethane)	H	
		Corrosion-resistant (Silver color)	D	
V	Failure alarm	UP Scale	A	
		DOWN scale	B	
VI	Mounting bracket	None	X	
		Carbon steel (Flat Form)	5	
		304 SST (Flat Form)	6	

10
20
0
90
100
80
110
120
100
0
5
10
20
30
0
5
0
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
2
10

*1 In case "Tantalum" is used for diaphragm material and in case of "For high-temperature service", normal operating temperature of wetted parts is -10 to +180dc

*2 Not applicable for the combination with code F1 and F6 of Explosion proof.

*3 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model GTX35R(Remote-sealed type for standard differential pressure)

Model GTX40R(Remote-sealed type for high differential pressure)

Extended 3 inches, 2 inches flange type for high temperature vacuum, high temperature high vacuum service

Issued: Jul. 1, 2008	Page: 1-0-26
Effective: Feb. 1, 2011	UNIT: 1000YEN

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.

Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Extended flange type 3 inches (80mm), 2 inches(50mm)
	35 to 700kPa (0.35 to 7k _{gf} /cm ²)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*4	D	
II	Fill Fluid	For high temperature vacuum service (Silicone oil)	C	
		For high temperature high vacuum service (Silicone oil)	D	
III	Wetted parts material	316 SST (Diaphragm:316L SST)	A	
		316L SST*1*2	D	
IV	Flange rating	ANSI150	A1	
		ANSI300	A2	
		ANSI600*1*2	A3	
		JIS10K	J1	
		JIS20K	J3	
		JIS30K	J4	
		JIS63K	J6	
		JPI150	P1	
		JPI300	P2	
		JPI600*1*2	P3	
		V	Flange size	2in./50A
3in./80A*1	F			
VI	Flange type	Extended Length 50mm	B	
		Extended Length 100mm	C	
		Extended Length 150mm	D	
		Extended Length 200mm*2	E	
		Extended Length 250mm*2	F	
		Extended Length 300mm*2	G	
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		304 SST	304 SST	A
		304 SST	630 SST	C
		304 SST	Carbon steel	D
		316 SST	304 SST	E
		316 SST	630 SST	G
		316 SST	Carbon steel	H
		316L SST	304 SST	J
		316L SST	630 SST	L
		316L SST	Carbon steel	M
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m	02	
		3m	03	
		4m	04	
		5m	05	

Additional price
0
5
0
500
900
0
120
0
15
20
0
25
40
420
0
15
20
0
0
123
136
150
175
189
200

10
20
0
90
100
80
110
120
100
0
5
10
20
30

Selection II

I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *3	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
		NEPSI Type n	N5
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6

0
5
0
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
5
2
10

*1 Not applicable for the combination with Flange rating "ANSI/JPI600" and "Flange size 3 in./80A".

*2 In case Fill Fluid: For high-temperature service, and 2 in. Flange Rating: ANSI/JPI600 and Wetted Parts material: 316L SST, Extension length of Flange 200/250/300mm are not available.

*3 Not applicable for the combination with code F1 and F6 of Explosion proof.

*4 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

Model GTX35R(Remote-sealed type for standard differential pressure)
Model GTX40R(Remote-sealed type for high differential pressure)
Flush 3/4 inches, 1/2inches flange type for regular/ high temperature/ oxygen/ chorine service)

Issued: Jul. 1, 2008	Page: 1-0-27
Effective: Feb. 1, 2011	UNIT: 100YEN

Model No.:GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.			
Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Flush flange type 3/4 inches (20mm), 1/2 inches(15mm)
	35 to 700kPa (0.35 to 7kgf/cm ₂)	GTX40R	

Basic price
589
601

Selection I

I	Output	4 to 20mA (SFN Communication)	A	
		4 to 20mA (HART Communication)	B	
		Digital output(DE communication)*7	D	
II	Fill Fluid	Regular type (Silicone oil)	A	
		For high temperature service (Silicone oil)	B	
		For oxygen service (Fluorine oil)	H	
III	Wetted parts material	316 SST (Diaphragm:316L SST)*4	A	
		ASTM B575 (Equivalent to Hastelloy C-276)*5	B	
		316L SST*6	D	
IV	Flange rating	No flange		XX
V	Flange size	For small size flange model		X
VI	Flange type	For small flange type(with adapter, rear connection to capillary)*1		1
		For small flange type(with no adapter, rear connection to capillary)		3
		For small flange type, corrosion resistant model(with adapter, rear connection to capillary)*1*2		5
		For small flange type, high model(with adapter, rear connection to capillary)*1*2*4		6
VII	Flange material/bolt and nut material	Flange	Bolt/nut	
		No flange	304 SST	1
		No flange	630 SST	3
		No flange	Carbon steel	4
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A	
IX	Capillary length	2m		02
		3m		03
		4m		04
		5m		05
		2m (with Olefin Cover)		A2
		3m (with Olefin Cover)		A3
		4m (with Olefin Cover)		A4
		5m (with Olefin Cover)		A5

Additional price
0
5
0
0
62
62
0
0
155
40
0
0
0
0
50
50

10
20
0
0
5
10
20
30
25
30
40
50

Selection II

I	Electrical connection	1/2 NPT, Watertight	A	
		M20, Watertight *3	B	
II	Explosion proof	None		XX
		FM Explosionproof		F1
		FM Intrinsically safe		F2
		FM Nonincendive		F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive		F6
		ATEX Explosionproof		A1
		ATEX Intrinsically safe		A2
		ATEX Type n		A5
		IECEX Explosionproof		E1
		IECEX Intrinsically safe		E2
		IECEX Type n		E5
		NEPSI Explosionproof		N1
		NEPSI Intrinsically safe		N2
		NEPSI Type n		N5
III	Indicator	None		X
		With indicator	A	
IV	Paint	Standard		X
		Corrosion-proof (Urethane)		H
		Corrosion-resistant (Silver color)		D
V	Failure alarm	UP Scale		A
		DOWN scale		B
VI	Mounting bracket	None		X
		Carbon steel (Flat Form)		5
		304 SST (Flat Form)		6

0
5
0
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
2
10

Note)

- *1 Please select the small flange mounting kit model (HF-).
- *2 The combination with Model SDR(Elliptical Tube Flowmeter) is not available.
- *3 Not applicable for the combination with code F1 and F6 of Explosion proof.
- *4 In case code 6 is selected, wetted parts material "316 SST" should be selected.
- *5 Not applicable for the combination with code 6 of flange type.
- *6 Not applicable for the combination with code 5 and code 6 of flange type.
- *7 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

**Model GTX35R(Remote-sealed type for standard differential pressure)
Flush 3/4 inches, 1/2inches flange type for low temperature/fast response service Silicone oil**

Issued: Jul. 1, 2008	Page: 1-0-28
Effective: Feb. 1, 2011	UNIT: 1000YEN

Model No. :GTX_ _R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Basic Model No.			
Measuring span	2.5 to 100kPa (250 to 10,160mmH ₂ O)	GTX35R	Flush flange type 3/4 inches (20mm), 1/2 inches(15mm)

Basic price
589

Selection I			
I	Output	4 to 20mA (SFN Communication)	A
		4 to 20mA (HART Communication)	B
		Digital output(DE communication)*3	D
II	Fill Fluid	For low temperature / Fast response service (Silicone oil)	F
III	Wetted parts	316 SST (Diaphragm:316L SST)	A
IV	Flange rating	No flange	XX
V	Flange size	For small size flange model	X
VI	Flange type	For small flange type(with adapter, rear connection to capillary)*1	1
		For small flange type(with no adapter, rear connection to capillary)	3
VII	Flange material/bolt and nut material	Flange	Bolt/nut
		No flange	304 SST
		No flange	630 SST
		No flange	Carbon steel
VIII	Gasket face finish	None Standard JISRa3.2(12.5S)	A
IX	Capillary length	2m	02
		3m	03
		4m	04
		5m	05
		2m (with Olefin Cover)	A2
		3m (with Olefin Cover)	A3
		4m (with Olefin Cover)	A4
		5m (with Olefin Cover)	A5

Additional price
0
5
0
62
0
0
0
0
0
0

Selection II			
I	Electrical connection	1/2 NPT, Watertight	A
		M20, Watertight *2	B
II	Explosion proof	None	XX
		FM Explosionproof	F1
		FM Intrinsically safe	F2
		FM Nonincendive	F5
		Combined of FM Explosionproof, Intrinsically safe and Nonincendive	F6
		ATEX Explosionproof	A1
		ATEX Intrinsically safe	A2
		ATEX Type n	A5
		IECEX Explosionproof	E1
		IECEX Intrinsically safe	E2
		IECEX Type n	E5
		NEPSI Explosionproof	N1
		NEPSI Intrinsically safe	N2
NEPSI Type n	N5		
III	Indicator	None	X
		With indicator	A
IV	Paint	Standard	X
		Corrosion-proof (Urethane)	H
		Corrosion-resistant (Silver color)	D
V	Failure alarm	UP Scale	A
		DOWN scale	B
VI	Mounting bracket	None	X
		Carbon steel (Flat Form)	5
		304 SST (Flat Form)	6

10
20
0
5
10
20
30
25
30
40
50
0
5
10
8
8
8
8
8
8
8
8
8
8
8
8
8
0
20
0
14
16
0
0
0
0
5
2
10

- (Note)
- *1 Small flange mounting kit model (HF-) should be selected.
 - *2 Not applicable for the combination with code F1 and F6 of Explosion proof.
 - *3 Not applicable for the combination with code A2 "With external Zero/Span adjustment", Q1 "Safety Transmitter", and Q2 "NAMUR NE43 Compliant Output signal limits" of Option.

**Small flange type mounting kit
(Adapter flange)**

HF - I II III IV V - VI

									Basic price	
I	Adapter flange quantity	For DP remote (2 PIECES)*2*5	E						68	
		For high performance model DP remote (2 PIECES)*4*6*7	W						113	
II	Flange size	1/2in.		1					30	
		3/4in.		2					50	
III	Flange Rating	JIS10K			A				0	
		JIS20K			C				5	
		JIS30K			D				15	
		ANSI150			G				0	
		ANSI300*3			H				5	
		JPI150			N				0	
		JPI300			P				5	
IV	Adapter material	SCS14A or 316 SST				2			0	
V	Bolt/nut material	304 SST					2		0	
		630 SST					3		0	
							-			
VII	Option	None						X		0
		Oil and water free finish*1						1		0
		Oil free finish*1						2		0
		Long Vent / Drain Plug						3		10
		Assembled with a transmitter						4		5

Note)

- *1 When this option is selected, the same option for transmitter must be selected.
- *2 630 SST Bolt/nut material should be selected.
- *3 Refer to the specification sheet for the working pressure range.
- *4 The combination with Model SDR(Ellipitcal Tube Flowmeter) is not available.
- *5 Select this code when flange type code "1" is selected in the transmitter selection.
- *6 Select this code when flange type code "5" or "6" is selected in the transmitter selection.
- *7 304SST Bolt/nut material should be selected.

Model No.:GTX__R -Selection I (I II III IV V VI VII)-Selection II (I II III IV V VI)-Option

Option		Additional prices
No options	XX	0
With external Zero/Span adjustment*11*16	A2	30
Oil and water free finish	K1	17
Oil free finish*4	K3	10
Au Plating Diaphragm*17	L1	TOKUMI
0.1mm thickness diaphragm*12*13	M5	50
FEP protective film*14*15*18	N1	21
Safety Transmitter*5*16	Q1	0
NAMUR NE43 Compliant Output sign limits:3.8 to 20.5mA (Output 21.6mA/selected upper limit, 3.6mA/selected lower limit)*16	Q2	20
Alarm Output(contact output)*19	Q7	10
Custom calibration	R1	5
Test report	T1	2
Mill certificate	T2	21
Traceability certificate	T4	10
NACE certificate*9	T5	5
Non SI Unit	W1	0

Note)

- *4 No need to select when Fill Fluid code H, or J is selected.
- *5 Not applicable for the combination with code A2, or Q7 of Option
- *9 Applicable for "ASTM B575", code B of Material (center body).
- *11 Not applicable for the combination with code X "None" of Indicator. Please select "With indicator".
- *12 0.1 mm thickness diaphragm option is only available for Material of Wetted parts : "316 SST" and "316L SST".
- *13 0.1 mm thickness diaphragm option is only available for 4inches Extended Flange or 3inches Flush Flange
- *14 Not applicable for the combination with Extended Flange Type.
- *15 Not applicable for the combination with code B, C, and D of Fill Fluid. (Max. 110 degree C)
- *16 Not applicable for the combination with 1/2 inches or 3/4 inches flange.
- *17 Not applicable for the combination with "Tantalum" of Material(center body).
- *18 Not applicable for the combination with 1/2 inches or 3/4 inches flange.
- *19 Not applicable for the combination with code F2,F5,F6,N2,N5,E2,E5,A2 and A5 of Explosion proof.