

MTG15A - I II III IV V VI VII VIII IX - X XI - options (Some options can be selected per each model.)

Basic model No.	MTG15A-	Size	Code	Basic Price (JP 1000 Yen)											Lead time (week)		
				2.5	5	10	15	25	40	50	65	80	100	150		200	
		2.5mm *1	002	595													4
		5mm *1	005		595												4
		10mm *1	010			595											4
		15mm *1	015				595										4
		25mm	025					424									4
		40mm	040						440								4
		50mm	050							475							4
		65mm	065								580						4
		80mm	080									580					4
		100mm	100										645				4
		150mm	150											1,020			4
		200mm	200												1,335		4
				Additional Price (JP 1000 Yen)													
III	Lining	PFA	P	0													
III	Pipe connection	Wafer JIS10K	11	0													
		Wafer JIS16/20K	12	0													
		Wafer JIS30K	13	0													
		Wafer ANSI150	21	0													
		Wafer ANSI300	22	0													
		Wafer JPI150	61	0													
		Wafer JPI300	62	0													
		Flange JIS10K	J1	0	0	0	0	100	100	128	52	52	52	0	0		
		Flange JIS20K	J2	14	14	14	14	116	117	148	76	76	81	24	29	7	
		Flange JIS30K	J3	34	34	34	34	136	142	171	108	110	119	115	208	7	
		Flange JIS10K for 10mm size flange *2	J4	0	0	0										7	
		Flange JIS20K for 10mm size flange *2	J5	0	0	0										7	
		Flange ANSI150	A1	0	0	0	0	100	100	128	52	52	52	0	0	7	
Flange ANSI300	A2	23	23	23	23	116	117	148	101	101	101	47	64	7			
Flange JPI150	P1	0	0	0	0	100	100	128	52	52	52	0	0	7			
Flange JPI300	P2	23	23	23	23	116	117	148	101	101	101	47	64	7			
IV	Electrode	SUS316L	L	0													
		Hastelloy C	C	36											5		
		Titanium	K	41											5		
		Zirconium	H	170											5		
		Tantalum	T	103											5		
		Nickel	N	150											5		
		Platinum-iridium	P	175											5		
V	Grounding ring	SUS316	S	0	0	0	0	0	0	0	0	0	0	0			
		Hastelloy C	C	57	57	57	57	57	57	72	72	93	134	170	5		
		Titanium	K	52	52	52	52	52	52	67	67	82	124	155	5		
		Zirconium	H	104	104	104	104	104	104	134	134	164	248	305	5		
		Tantalum	T	103	103	103	103	103	103	113	113	134	206	258	5		
		Platinum	P	149	149	149	149	149	149	160	160	185	256	338	5		
VI	Wiring connection	G1/2 right side conduit w/ 1-piece flameproof gland	F	9													
		G1/2 left side conduit w/ 1-piece flameproof gland	G	9													
		G1/2 with 2-piece flameproof glands	H	18													
VII	Face to face dimension	Standard	A	0													
		Yamatake SMT3000 wafer type (40, 50, 80, 100mm)	S							42	40		44	71	6		
VIII	Installation/ Display direction	Horizontal piping mounting/ Display right side direction viewed from upstream	A														
		Horizontal piping mounting/ Display left side direction viewed from upstream	B														
		Horizontal piping mounting/ Display downstream side direction	C														
		Horizontal piping mounting/ Display upstream side direction	D														
		Vertical piping mounting/ Display right side of piping/Flow direction:Upward	E														
		Vertical piping mounting/ Display left side of piping/Flow direction:Upward	F														
IX	Calibration	Standard calibration (3 points 0, 50, 100%)	J														
X	Finish/paint	Standard paint	X	0													
		Corrosion-proof paint	2	10													
XI	Bolts/nuts	None	X	0													
		SUS304 bolts/nuts (for wafer style only)	2						5	5	5	5	5	20			
XII	Options	None	X	0													
		Traceability certificate	B	10													
		Material certificate (electrode/grounding ring)	C	45													
		Water free treatment	E	40													
		Oil free treatment	F	50													
		Gasket for plastic piping	G	10	10	10	10	10	14	19	24	35	45	80	120		
		All units (including Non SI units) available	H	5													
		Tropical treatment	J	52													
		with the Tag number plate on the converter housing *3	K	4													

Note \*1 Flange of size 2.5 to 15mm detector is 15 mm flange.  
\*2 Available for size 2.5 to 10 mm detector.  
\*3 Must be selected if tagging is required.