

Bosdellestraat 120/2, B-1933 ZAVENTEM, BELGIUM.
 TEL.: +32-(0)2/ 785.07.10. FAX: +32-(0)2/ 785.07.11.

To : Murat Bayram
 Electrical-Electronics Engineer

DATE: 23-juin-11

HTG / ENTEK TEKNİK
Att.: Maltepe, Istanbul/Turkey
Tel.: Tel:+90 216-4598660
Fax: Fax: +90 216-4598370
Email: <http://www.htgrup.com>
Web:

Your reference No. :
 Our Quotation No. : Q2011RH0108
 Contact person : Mr. Regis Houllier
 Tel: +33 3 22 54 83 47
 Fax: +33 3 22 54 83 29
 Email: regis.houllier@airlitec.com
 Web: <http://eu.azbil.com>

ITEM	MODEL	DESCRIPTION	Q'TY	U/PRICE (EURO)	AMOUNT (EURO)	LEAD TIME (Weeks)
1	PTG72G-N6B1G4-M-X	Pressure transmitter calibration range: 0 to 30 kg/cm2 Process connection: G1/2 Male screw Built-in indicator Hart protocol	4	350,00	1 400,00	8
2	PTG72G-N5B1G4-M-X	ditto calibration range: 0 to 10 kg/cm2	20	350,00	7 000,00	8
3	PTG72G-N3B1G4-M-X	ditto calibration range: 0 to 5000 mmH2O	7	350,00	2 450,00	8
4	GTX41D-BAADDAB-AXXAXA5-A1R1	DP Transmitter calibration range: 0 to 2 kg/cm2 Hart protocol Wetted part: SS316L Process connections: 1/2 NPT with adapter flange Bolts/Nuts SS304 Built-in indicator Mounting bracket Adapter flange for corrosion resistant application Custom calibration	2	811,00	1 622,00	8
5	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter DP Transmitter calibration range: 0 to 10000 mmH2O	2 11	115,00 793,00	230,00 8 723,00	8
6	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter DP Transmitter calibration range: 0 to 500 mmH2O	11 5	115,00 793,00	1 265,00 3 965,00	8
7	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter ditto calibration range: 0 to 2000 mmH2O	5 18	115,00 793,00	575,00 14 274,00	8
8	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter ditto calibration range: 0 to 5000 mmH2O	18 6	115,00 793,00	2 070,00 4 758,00	8
9	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter ditto calibration range: 0 to 1000 mmH2O	6 4	115,00 793,00	690,00 3 172,00	8
10	MVG1-2SA-X-A GTX35R-BAAA1FAEA02-AXXAXA5-R1	Manifold 3 ways mounted on Transmitter Remote DP Transmitter Flush flange 3" (80mm) model Hart protocol Ansi 150 flange Flush Type Flange material: SS316 Bolts/Nuts: SS304 Capilarity lenght: 2 meters Built-in indicator Mounting bracket Custom calibration	4 7	115,00 1 189,00	460,00 8 323,00	8

11	GTX30A-BAADDAB-AXXAXA5-R1	AP Transmitter calibration range: 0 to 760 mmHg Hart protocol Wetted part: SS316L Process connections: 1/2 NPT with adapter flange Bolts/Nuts SS304 Built-in indicator Mounting bracket Custom calibration	1	850,00	850,00	8
----	---------------------------	--	---	--------	--------	---

	Total	EURO	61 827,00
	Minimum Charge	EURO	0,00
	* Packing & Handling charges	EURO	0,00
	Freight Charge	EURO	
	Sub-total	EURO	61 827,00
	VAT 21%	EURO	
	Total	EURO	61 827,00

REMARKS:

- * Lead time may be changed depending on the condition of the outstanding orders at our factory side.
- * For our export procedure, End User Name + Country + End Use (company's main activity, product) must be specified on your Purchase Order Sheet.
- * Before shipping the goods please take notice that the payment must be registered in our Bank account.

TERMS and CONDITIONS:

- Trade Terms:** FCA JAPAN / Direct shipment from Japan by Air (Freight collect) by our forwarder, Unless otherwise instructed on your order sheet.
- Payment Terms:** 30 days from invoice date
- Minimum Order Amount:** Euro 150 per order (Packing & Handling and Freight charges excluded).
- Partial Shipment:** Not allowed.
- Shipping Route:** By Air freight
- Validity:** 60 days from quotation date.
- Cancellation:** Not allowed after your order is acknowledged.

(The Trade Terms are in accordance with Incoterms 2000.)

Regis Houllier
On behalf of Azbil Europe N.V.