

Bosdellestraat 120/2, B-1933 ZAVENTEM, BELGIUM.
 TEL.: +32-(0)2/ 785.07.10. FAX: +32-(0)2/ 785.07.11.

To : Gorgü Hydraulikservice
 Industriestrasse 15 a-d
 24558 Henstedt-Ulzburg
 Germany

DATE: 23-juin-11

Att.:
Tel.:
Fax:
Email: info@goergue-hydraulik.de
Web:

Your reference No. :
 Our Quotation No. : Q2011RH0220
 Contact person : Mr. Regis Houllier
 Tel: +33 3 22 54 83 47
 Fax: +33 3 22 54 83 29
 Email: regis.houllier@airlitec.com
 Web: <http://eu.azbil.com>

ITEM	MODEL	DESCRIPTION	Q'TY	U/PRICE (EURO)	AMOUNT (EURO)	LEAD TIME (Weeks)
1	PTG72G-N6B1G4-M-X	Presssure transmitter calibration range: 0 to 30 kg/cm2 Process connection: G1/2 Male screw Built-in indicator Hart protocol	4	404,00	1 616,00	8
2	PTG72G-N5B1G4-M-X	ditto calibration range: 0 to 10 kg/cm2	20	404,00	8 080,00	8
3	PTG72G-N3B1G4-M-X	ditto calibration range: 0 to 5000 mmH2O	7	404,00	2 828,00	8
4	GTX41D-BAADDAB-AXXAXA5-A1R1	DP Transmitter calibration range: 0 to 2 kg/cm2 Hart protocol Wetted part: SS316L Process connections: 1/2 NPT with adapter flange Bolts/Nuts SS304 Built-in indicator Mounting bracket Adapter flange for corrosion resistant application Custom calibration	2	936,00	1 872,00	8
5	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter DP Transmitter calibration range: 0 to 10000 mmH2O	2 11	133,00 915,00	266,00 10 065,00	8
6	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter DP Transmitter calibration range: 0 to 500 mmH2O	11 5	133,00 915,00	1 463,00 4 575,00	8
7	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter ditto calibration range: 0 to 2000 mmH2O	5 18	133,00 915,00	665,00 16 470,00	8
8	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter ditto calibration range: 0 to 5000 mmH2O	18 6	133,00 915,00	2 394,00 5 490,00	8
9	MVG1-2SA-X-A GTX31D-BAADDAB-AXXAXA5-A1R1	Manifold 3 ways mounted on Transmitter ditto calibration range: 0 to 1000 mmH2O	6 4	133,00 915,00	798,00 3 660,00	8
10	MVG1-2SA-X-A GTX35R-BAAA1FAEA02-AXXAXA5-R1	Manifold 3 ways mounted on Transmitter Remote DP Transmitter Flush flange 3" (80mm) model Hart protocol Ansi 150 flange Flush Type Flange material: SS316 Bolts/Nuts: SS304 Capilarity lenght: 2 meters Built-in indicator Mounting bracket Custom calibration	4 7	133,00 1 372,00	532,00 9 604,00	8

	Total	EURO	70 378,00
	Minimum Charge	EURO	0,00
	* Packing & Handling charges	EURO	0,00
	Freight Charge	EURO	
	Sub-total	EURO	70 378,00
	VAT 21%	EURO	
	Total	EURO	70 378,00

REMARKS:

- * Lead time may be changed depending on the condition of the outstanding orders at our factory side.
- * For our export procedure, End User Name + Country + End Use (company's main activity, product) must be specified on your Purchase Order Sheet.
- * Before shipping the goods please take notice that the payment must be registered in our Bank account.

TERMS and CONDITIONS:

Trade Terms: FCA JAPAN / Direct shipment from Japan by Air (Freight collect) by our forwarder, Unless otherwise instructed on your order sheet.

Payment Terms: advance payment

Minimum Order Amount: Euro 150 per order (Packing & Handling and Freight charges excluded).

Partial Shipment: Not allowed.

Shipping Route: By Air freight

Validity: 60 days from quotation date.

Cancellation: Not allowed after your order is acknowledged.

(The Trade Terms are in accordance with Incoterms 2000.)

Regis Houllier

On behalf of Azbil Europe N.V.