

MTG15A - I II III IV V VI VII VIII IX - X XI - options (Some options can be selected per each model.)

Basic model No. MTG15A-				Basic Price (JP 1000 Yen)												Lead time (week)			
				2.5	5	10	15	25	40	50	65	80	100	150	200				
I	Size	2.5mm *1	002	595														4	
		5mm *1	005		595														4
		10mm *1	010			595													4
		15mm *1	015				595												4
		25mm	025					424											4
		40mm	040						440										4
		50mm	050							475									4
		65mm	065								580								4
		80mm	080									580							4
		100mm	100										645						4
150mm	150											1,020					4		
200mm	200												1,335				4		
				Additional Price (JP 1000 Yen)															
Lining PFA				0															
III	Pipe connection	Wafer JIS10K	11																
		Wafer JIS16/20K	12																
		Wafer JIS30K	13																
		Wafer ANSI150	21																
		Wafer ANSI300	22																
		Wafer JPI150	61																
		Wafer JPI300	62																
		Flange JIS10K	J1			0	0	0	0	100	100	128	52	52	52	0	0		
		Flange JIS20K	J2			14	14	14	14	116	117	148	76	76	81	24	29		7
		Flange JIS30K	J3			34	34	34	34	136	142	171	108	110	119	115	208		7
		Flange JIS10K for 10mm size flange *2	J4			0	0	0											7
		Flange JIS20K for 10mm size flange *2	J5			0	0	0											7
		Flange ANSI150	A1			0	0	0	0	100	100	128	52	52	52	0	0		7
Flange ANSI300	A2			23	23	23	23	116	117	148	101	101	101	47	64		7		
Flange JPI150	P1			0	0	0	0	100	100	128	52	52	52	0	0		7		
Flange JPI300	P2			23	23	23	23	116	117	148	101	101	101	47	64		7		
IV	Electrode	SUS316L	L																
		ASTM B574 (Hastelloy C-276 equivalent)	C																
		Titanium	K																
		Zirconium	H																
		Tantalum	T																
		Niobium	N											150					
		Platinum-iridium	P																
V	Grounding ring	SUS316	S																
		ASTM B575 (Hastelloy C-276 equivalent)	C																
		Titanium	K																
		Zirconium	H																
		Tantalum	T																
		Platinum	P																
						0	0	0	0	0	0	0	0	0	0	0	0	0	
VI	Wiring connection	G1/2 right side coduit w/ 1-piece flameproof gland	F																
		G1/2 left side coduit w/ 1-piece flameproof gland	G																
		G1/2 with 2-piece flameproof glands	H																
VII	Face to face dimension	Standard	A																
		Yamatake SMT3000 wafer type (40, 50, 80, 100mm)	S																
VIII	Installation/ Display direction	Horizontal piping mounting/ Display right side direction viewed from upstream	A																
		Horizontal piping mounting/ Display left side direction viewed from upstream	B																
		Horizontal piping mounting/ Display downstream side direction	C																
		Horizontal piping mounting/ Display upstream side direction	D																
		Vertical piping mounting/ Display right side of piping/Flow direction:Upward	E																
		Vertical piping mounting/ Display left side of piping/Flow direction:Upward	F																
IX	Calibration	Standard calibration (3 points 0, 50, 100%)	J																
X	Finish/paint	Standard paint	X																
		Corrosion-proof paint	2																
XI	Bolts/nuts	None	X																
		SUS304 bolts/nuts (for wafer style only)	2																
XII	Options	None	X																
		Traceability certificate	B																
		Material certificate (electrode/grounding ring)	C																
		Water free treatment	E																
		Oil free treatment	F																
		Gasket for plastic piping	G																
		All units (including Non SI units) available	H																
		Tropical treatment	J																
		with the Tag number plate on the converter housing *3	K																
						10	10	10	10	10	14	19	24	35	45	80	120		

Note \*1 Flange of size 2.5 to 15mm detector is 15mm flange.  
\*2 Available for size 2.5 to 10 mm detector.  
\*3 Must be selected if tagging is required.