

Bosdellestraat 120/2, B-1933 ZAVENTEM, BELGIUM.
 TEL.: +32-(0)2/ 785.07.10. FAX: +32-(0)2/ 785.07.11.

To : Batex Trading
 Jalal Marvi e.K.
 Sude tenring 68
 94234 Viechtach Germany
 Att.: Erika Morgen
 Tel.:
 Fax:
 Email: erika.morgen@batextrading.com
 Web:

DATE: 16-avr-12

Your reference No. :
 Our Quotation No. : Q2012RH133
 Contact person : Mr. Regis Houllier
 Tel: +33 3 22 54 83 47
 Fax: +33 3 22 54 83 29
 Email: regis.houllier@airitec.com
 Web: <http://eu.azbil.com>

| ITEM | MODEL | DESCRIPTION | Q'TY | U/PRICE (EURO) | AMOUNT (EURO) | LEAD TIME (Weeks) |
|------|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------------------|------------------|----------------------|
| 5 | JTD910A-1E1F2-K2XX1-U2 | DP transmitter Span: 0,1 to 2Kpas Stainless steel wetted parts Process connection: 1/2 NPT Top Bolt/nut: SUS304 TIIS intrinsically safe With local indicator With 2" pipe mounting bracket | 5 | 1002 | 5 010,00 | 8 |
| 6 | KFKB12-1322B3T-M7 | Pressure indicating Controller PI type Range: 0,35 to 7 Mpas Bourdon tube Air piping: 1/4 NPT 2 inch pipe mounting bracket With built in manual controller and A/M switch With pressure regulator and filter | 5 | 4307 | 21 535,00 | 8 |
| 7 | STD924-A1H-00000-S2-MB-CC-ME-E1D9 GTX31D-AAAAACA-AXXAXA1-R1 | to be replaced by: DP transmitter GTX series Stainless steel wetted parts Process connection: 1/2 NPT with adapter flanges With local indicator With 2" pipe mounting bracket With custom calibration (to be given at order level) No EX approval Front connection | 5 | 585 | 2 925,00 | 8 |
| 8 | STD920-AIR-00000-R4-E9 SH8041 GTX31D-AAAAA-DAF2AXA1-XX | to be replaced by: DP transmitter GTX series Stainless steel wetted parts Process connection: 1/2 NPT with adapter flanges FM intrinsically safe With local indicator With 2" pipe mounting bracket Top connection | 30 | 590 | 17 700,00 | 8 |
| 9 | JTD236Z-A1T-00000-GN4-XX (CS) JTD960A-1E1F2-K2BX2-XX | to be replaced by: DP transmitter Span: 0,25 to 14Mpas Stainless steel wetted parts Process connection: 1/2 NPT Top Bolt/nut: SUS304 TIIS intrinsically safe With local indicator Corrosion proof finish With 2" pipe mounting bracket in SS | 5 | 1168 | 5 840,00 | 8 |

| | | |
|------------------------------|------|-----------|
| Total | EURO | 53 010,00 |
| Minimum Charge | EURO | 150,00 |
| * Packing & Handling charges | EURO | 0,00 |
| Freight Charge | EURO | |
| Sub-total | EURO | 53 010,00 |
| VAT 21% | EURO | |
| Total | EURO | 53 010,00 |

REMARKS:

- * Lead time may be changed depending on the condition of the outstanding orders at our factory side.
- * For our export procedure, End User Name + Country + End Use (company's main activity, product) must be specified on your Purchase Order Sheet.
- * Before shipping the goods please take notice that the payment must be registered in our bank account.
- * Certificate of Origin = 50 Euro
- * Cash Against Document = 80 Euro bank charges
- * Legalization of documents = 30 Euro per document

TERMS and CONDITIONS:

Trade Terms: FCA JAPAN / Direct shipment from Japan by Air (Freight collect) by our forwarder, Unless otherwise instructed on your order sheet.

Payment Terms: Advance Payment

Minimum Order Amount: Euro 150 per order (Packing & Handling and Freight charges excluded).

Partial Shipment: Not allowed.

Shipping Route: By Air freight

Validity: 60 days from quotation date.

Cancellation: Not allowed after your order is acknowledged.

(The Trade Terms are in accordance with Incoterms 2000.)

Regis Houllier
 On behalf of Azbil Europe N.V.