SPECIFICATION LIST

ITEM No.	MODEL / NAME / SPECIFICATION		
1	MODEL	SLX110Z-10511MD21-D1X-68D	
	SLX110-	Smart Displacement type Liquid Level Transmitter(Sp.Gr.Medium type)	
	Z-		
	1	Output/Communication type	4～20mADC(Standard)
	05	Measuring Range	0-500mm(H=500)
	1	Process Connection	External Chamber type,Side-Side Flange
	1	Main Material(Bonnet･Chamber/Torque tube Housing)	Carbon Steel / Carbon Steel
	M	Temperature/Torque tube Material	High Temperature / Inconel (200 - 350 degC)
	D	Pressure Rating(shape)	ANSI300 (RF Serration)
	2	Flange Diameter	2in. / 50mm (for External type)
	1-	Instrument Mounting	The Left Side
	D	Electrical Conduit and Explosion-proof	G1/2 and TIIS flame-proof (Exd II CT6) Standard Packing: 2 pieces
	1	Indicating Smart Meter	Digital Meter with Standard Reading(0～100%)
	X-	Finish	Standard Finish
	6	Options	Test Report
	8	Options	Material Certificate
	D	Options	Without Chamber
	Y131		SUS304 Bolt & Nut
	SH5158-A04		BONNET WITH VENT PLUG 3/4NPT
	SH5335		Tropical treatment equivalent
	Replacement from KFL(pneumatic) to SLX(electric), Old Production No : S-K021L-41-11A Existing Chamber Re-Used		