MagneW Neo Smart Two-wire Electromagnetic Flowmeter
Explsion-protected Apparatus Wafer/Flange Integral style

Issued : Jul. 22, 2003	Page : 2-4-11
Effective : Jul. 1, 2005	UNIT : 1000YEN

MTG15A—I II III IV V VI VII VIII IX - X XI - options (Some options can be selected per each model.)

Basic model No.	MTG15A-				Basic Price (JP 1000 Yen) 2.5	5	10	15	25	40	50	65	80	100	150	200	Lead time (week)
I	Size	2.5mm *1	002		595												4
		5mm *1	005			595											4
		10mm *1	010				595										4
		15mm *1	015					595									4
		25mm	025						424								4
		40mm	040							440							4
		50mm	050								475						4
		65mm	065									580					4
		80mm	080										580				4
		100mm	100											645			4
		150mm	150												1,020		4
		200mm	200													1,335	4

					Additional Price (JP 1000 Yen) 0
II	Lining	PFA	P		
III	Pipe connection	Wafer JIS10K	11		0
		Wafer JIS16/20K	12		0
		Wafer JIS30K	13		0
		Wafer ANSI150	21		0
		Wafer ANSI300	22		0
		Wafer JPI150	61		0
		Wafer JPI300	62		0
		Flange JIS10K	J1		0 0 0 0 100 100 128 52 52 52 0 0
		Flange JIS20K	J2		14 14 14 14 116 117 148 76 76 81 24 29 7
		Flange JIS30K	J3		34 34 34 34 136 142 171 108 110 119 115 208 7
		Flange JIS10K for 10mm size flange *2	J4		0 0 0 7
		Flange JIS20K for 10mm size flange *2	J5		0 0 0 7
		Flange ANSI150	A1		0 0 0 0 100 100 128 52 52 52 0 0 7
		Flange ANSI300	A2		23 23 23 23 116 117 148 101 101 101 47 64 7
		Flange JPI150	P1		0 0 0 0 100 100 128 52 52 52 0 0 7
		Flange JPI300	P2		23 23 23 23 116 117 148 101 101 101 47 64 7
IV	Electrode	SUS316L		L	0
		Hastelloy C		C	36 5
		Titanium		K	41 5
		Zirconium		H	170 5
		Tantalum		T	103 5
		Nickel		N	150 5
		Platinum-iridium		P	175 5
V	Grounding ring	SUS316		S	0 0 0 0 0 0 0 0 0 0 0 0
		Hastelloy C		C	57 57 57 57 57 57 57 72 72 93 134 170 5
		Titanium		K	52 52 52 52 52 52 52 67 67 82 124 155 5
		Zirconium		H	104 104 104 104 104 104 104 134 134 164 248 305 5
		Tantalum		T	103 103 103 103 103 103 103 113 113 134 206 258 5
		Platinum		P	149 149 149 149 149 149 149 160 160 185 256 338 5
VI	Wiring connection	G1/2 right side coduit w/ 1-piece flameproof gland		F	9
		G1/2 left side coduit w/ 1-piece flameproof gland		G	9
		G1/2 with 2-piece flameproof glands		H	18
VII	Face to face dimension	Standard		A	0
		Yamatake SMT3000 wafer type (40, 50, 80, 100mm)		S	42 40 44 71 6
VIII	Installation/ Display direction	Horizontal piping mounting/ Display right side direction viewed from upstream		A	
		Horizontal piping mounting/ Display left side direction viewed from upstream		B	
		Horizontal piping mounting/ Display downstream side direction		C	
		Horizontal piping mounting/ Display upstream side direction		D	
		Vertical piping mounting/ Display right side of piping/Flow direction:Upward		E	
		Vertical piping mounting/ Display left side of piping/Flow direction:Upward		F	
IX	Calibration	Standard calibration (3 points 0, 50, 100%)		J	
				-	
X	Finish/paint	Standard paint		X	0
		Corrosion-proof paint		2	10
XI	Bolts/nuts	None		X	0
		SUS304 bolts/nuts (for wafer style only)		2	5 5 5 5 5 20
				-	
XII	Options	None		X	0
		Traceability certificate		B	10
		Material certificate (electrode/grounding ring)		C	45
		Water free treatment		E	40
		Oil free treatment		F	50
		Gasket for plastic piping		G	10 10 10 10 10 14 19 24 35 45 80 120
		All units (including Non SI units) available		H	5
		Tropical treatment		J	52
		with the Tag number plate on the converter housing *3		K	4

Note
*1 Flange of size 2.5 to 15mm detector is 15 mm flange.
*2 Available for size 2.5 to 10 mm detector.
*3 Must be selected if tagging is required.