

Basic Model No.	Size	Liner material	Flange connection type	Maximum working pressure (kPa)	
MGG18D, MGG17D	2.5 ~ 200mm	PFA, Polyurethane rubber	/	2068	
	15 ~ 100mm	Ceramic		4000	
MGH18D	40 ~ 200mm	PFA		2068	
MGG19D	2.5 ~ 200mm	PFA, Polyurethane rubber		2068	
MGG18U, MGG19U	2.5 ~ 15mm	PFA		1000	
MGG18F, MGG19F, MGG17F	2.5 ~ 600mm	/		ANSI 150	1400
				DIN PN10	1000
				DIN PN16	1600
				JIS 10k	1400
	2.5 ~ 200mm			ANSI 300	2068
			DIN PN25	2000	
			JIS 20k	2068	
			JIS 30k	2068	
	250 ~ 400mm		ANSI 300	2000	
	250 ~ 600mm		DIN PN25	2000	
JIS 20k		2000			
MGH18F	40 ~ 300mm	/	ANSI 150	1400	
			DIN PN10	1000	
			DIN PN16	1600	
			JIS 10k	1400	
	40 ~ 200mm		ANSI 300	2068	
			DIN PN25	2000	
			JIS 20k	2068	
			JIS 30k	2068	
	250 ~ 300mm		ANSI 300	2000	
			DIN PN25	2000	
JIS 20k		2000			