

12-2-2.

**Table 1 VPP Model No. Selection (Tentative)**

Model No.		(1)	-	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
VPP											
(1) Type	Double acting - Low pressure	02									
	Double acting - High pressure	03									
	Single acting	08									
(2) Finish	Standard			0							
	Corrosion-proof (Acryl baked)			A							
	Corrosion-proof (Epoxy resin baked)			B							
(3) Pneumatic tubing connection	Rc 1/4				R						
	NPT 1/4				N						
(4) Air supply pressure	2.0 - 3.5 kgf/cm <sup>2</sup>					1					
	3.6 - 4.5 kgf/cm <sup>2</sup>					2					
	4.6 - 7.0 kgf/cm <sup>2</sup>					3					
	200 - 340 kPa					4					
	350 - 450 kPa					5					
	460 - 700 kPa					6					
(5) Pressure gauge	kgf/cm <sup>2</sup>						1				
	Psi						2				
	bar						3				
	kPa						4				
	Others						5				
(6) Input signal	0.2 - 1.0 kgf/cm <sup>2</sup>							1			
	0.2 - 0.6 kgf/cm <sup>2</sup>							2			
	0.6 - 1.0 kgf/cm <sup>2</sup>							3			
	20 - 100 kPa							4			
	20 - 60 kPa							5			
	60 - 100 kPa							6			
(7) Applicable acuator									Z		
(8) Cam characteristics	Linear										L
	EQ%										P
	QO										Q
(9) Ambient temperature	-30 to 80°C										N
	Others										Z