

three line display and configuration via keypad interface ...

measures mass flow, temperature and pressure simultaneously ...

built in data logger ...



VPFlowScope®

'If you can not measure it, you can not improve it'
(Lord Kelvin, 1883)

- > gas flow
- > pressure
- > temperature



Features:

- > The VPFlowScope measures mass flow, pressure and temperature simultaneously.
- > A built-in display with keypad for configuration with no need for pc or laptop.
- > A built-in data logger for long term monitoring of trends in compressed air consumption and compressor performance.


Smart, Simple & Complete:

- > **All-in one device.** The VPFlowScope measures three parameters at once, making extra sensors and cables redundant.
- > **Graphical display.** Real-time Information is at your disposal every minute of the day. Powerful data analysis software generates graphical output on your PC.
- > **Easy to install.** Just mount the VPFlowScope in the pipe and you can start measuring immediately, after setting the installation parameters such as tube diameter.
- > **Cost saver.** The VPFlowScope keeps a permanent eye on compressed air consumption and gives insight in the performance of your compressed air system. It is the ideal tool for compressed air cost allocation, leak detection, utility management and maintenance planning.

Specifications:

flow range:	0..80 mn/s, 0..150 mn/s,
pressure:	0... 16 bar
temperature:	up to 50 °C
probe length:	400 mm (300,600)
standard outputs:	4..20 mA, RS485
mounting:	0.5 inch compression fitting
accuracy:	< 2% of reading*
gases:	compressed air, N ₂ , inert gases
data logger:	500.000 points

* Please note that for insertion probes, the field accuracy depends on installation conditions.



VPFlowScope®

VPFlowScope is a registered trademark of Van Putten Instruments B.V. Patents pending. © 2006



VP INSTRUMENTS

Buitenwatersloot 335
2614 GS Delft
The Netherlands

T: 00 31 15 213 15 80
F: 00 31 15 213 06 69
www.vpinstruments.com
info@vpinstruments.com