

Honeywell

Honeywell Middle East Ltd.
P.O. Box 45595; Abu Dhabi, UAE
Proforma Invoice

Istanbul, January 20, 2003



Industrial Control Division

Proposal No : MC3Z201R

(To ref. in your order)

Your Reference :-

To: REPASAEG AUTOMATION
Bagdat caddesi Feneryolu
132/11 ISTANBUL / TURKEY
Tel : 90-216 418 62 14
Fax: 90-216 418 62 14

} continue fore.

Ship to : AS ABOVE

FOR GAS SUPPLY COMPANY -

Delivery : Apprx. 12-14 weeks after receipt of order

Packing : Export

Route : AIR

Delivery Terms : See Price Details

Payment Terms : L/C

Validity : 120

IGBANK

| Item | Qty | Model and Description | Unit Price USD | Amount USD |
|------|-----|-----------------------|----------------|------------|
|------|-----|-----------------------|----------------|------------|

| | | | | |
|---|------|---|-----|---------|
| 1 | 1282 | <p>INLET / OUTLET PRESSURE SENSOR (0-6 , 0-25 BAR)</p> <p>SMART GAUGE PRESSURE TRANSMITTER</p> <p>HONEYWELL</p> <p>Smart Gauge Pressure Transmitter. Model no: STG94L-EIG-00000-1C Man: Honeywell / USA Span: 0-20 to 0-500 Psi. / 0-1,4 to 0-35 bar Your calib. Range : 0-25 bar, 0-6 bar Output : Two wire , 4-20 mA DC linear output Process Head: 316 St. St. Barrier Diaphragm: 316LSS. Fill Fluid: Silicon Process Head Configuration: 1/2"NPT. Electrical conn.: 1/2" NPT Power Supply : 10,8 to 42,4 V DC Current Range :3.0 to 21.8 mA Temperature limits Operating temperature : -40 to 125 deg C Storage temp. : -55 to 125 deg C Humidity% RH : 0-100 Electronics Housing : Low copper Aliminum. Meets NEMA 4X (Watertight),NEMA7X (Explosion proof) Accuracy : 0,075 % of URL (includes combined effects of linearity,hystersis and repeatability) Stability : +/-0,015% of URL per year with 5 year guarantee Reliability : Field reliability > 600 years Overpressure limits : 50 bar Supply Voltage effect : 0.005% of calibrated span Temperature effect Zero temperature effect : +/-0.1625% of span Combined Zero and Span temperature effect : +/-0.25% of span Weight : 1,7 kg Approved EEx d IIC T6 Explosion Proof : Class I,Div.1,Groups A,B,C,D Dust Ignition Proof: Class II,III,Div.1 Groups E,F,G Non Incendive : Class I,Div.2 Groups A,B,C,D Intrinsically Safe : Class I,II,III, Div. 1,Groups A,B,C,D,E,F,G</p> | 320 | 410.240 |
|---|------|---|-----|---------|

| Item | Qty | Model and Description | Unit Price USD | Amount USD |
|--|-----|--|----------------|-------------------|
| 2 | 807 | GAS / TEMPERATURE SENSOR SMART TEMPERATURE TRANSMITTER HONEYWELL STT250 Smart Temperature Transmitter Model no : STT25M-0-EN0-00E-000-000-00-1C Man. : Honeywell / USA | 165 | 133.155 |
| <p> Isolated 4-20 mA DC output Temp.Input: All kind of T/C and 4,3 or 2 wire RTD (User selectable) Adjustment range: No limits to adjustments within the maximum range and mininum span Isolation : Input/Output galvanic isolation withstands 500 Vac dielectirc strenght test for 1 minute Supply Voltage : 10,8 to 35 V DC ,2 wire system Accuracy of span : 0.025 % with certificate of conformance Humidity limits : 5-100 % RH Failure Mode : Open circuit/burnout detection is user selectable. Upscale or downscale with critical status message. Latching or non-latching sensor burnout action. Update time : 0.5 secs approxiamately. Stability : 0.05% of max.span per year with 5 year guarantee Vibration effect : Maximum of 4g over 15 to 200 Hz Power supply voltage effect : 0,005 % of Max span per Volt. Ambient temperature effect : +/- 0.045% of span Weight : 1,175 kg Housing : Explosion proof head Cable / Conduit entry : 1/2" NPT Proses / Sensor entry : 1/2" NPT RFI rejection: +- 0.1% of span at 30 V/m over 20 to 1,000 Mhz EMC compliance: In compliance with 89/336/EEC electromagnetic compatibility (EMC)Directive Damping time constant:Adjustable from 0 to 102 seconds digital damping Approved EEx d IIC T6 Explosion Proof : Class I,Div.1,Groups A,B,C,D Dust Ignition Proof: Class II,III,Div.1 Groups E,F,G Non Incendive : Class I,Div.2 Groups A,B,C,D Intrinsically Safe : Class I,II,III, Div. 1,Groups A,B,C,D,E,F,G </p> | | | | |
| TOTAL Ex-FACTORY | | | USD | 543.395,00 |
| Handling & Charges | | | USD | 10.868,00 |
| TOTAL FOB - Phoenix | | | USD | 554.263,00 |
| <p>The Payment should be made in favour of :</p> <p style="text-align: center;"> Honeywell Middle East Ltd. P.O. Box 45595; Abu Dhabi , UAE </p> <p style="text-align: center;"> Through: IISBC Bank Middle East P.O. Box 25 ; Sharjah, UAE Acc. No: 040-051955-102 </p> | | | | |