



Company:

phone:

Name:

mobile:

Street/Straße:

Fax:

PO City / PLZ Stadt:

e-mail:

Compresseurs d'air  
Vente et location

Eric SLOMIANY  
+33 (0) 6 08 76 17 95

Date of visit:	<input type="checkbox"/> 20.04	<input checked="" type="checkbox"/> 21.04	<input type="checkbox"/> 22.04	<input type="checkbox"/> 23.04	<input type="checkbox"/> 24.04	Catego
Talked with:	<input type="checkbox"/> Ogihara	<input checked="" type="checkbox"/> Tom	<input type="checkbox"/> Martin			Note:

6 rue Joseph Machard  
54330 OMELMONT

Tel / Fax: +33 (0) 3 83 41 22 06  
E-mail: ees.slomiany@free.fr

Company Profile:

WHAT ARE THEY LOOKING FOR + VISIT CARD: short written note / application

COMPRÉHENSION / REVENIR

Mass flowmeter (MCF-Application):

MCFXXX0ARND0100X0 Massendurchflussmesser MCF-Series (N2, Air)

Code Description

MCF

- 008 2-200 nl/min, Pipe size 8A (1/4" Rc ISO 7/1)
- 015 5-500 nl/min, Pipe size 15A (1/2" Rc ISO 7/1)
- 025 30-3000 nl/min, Pipe size 25A (1" Rc ISO 7/1)
- 040 60-6000 nl/min, Pipe size 40A (1 1/2" Rc ISO 7/1)
- 050 120-12000 nl/min, Pipe size 50A (2" Rc ISO 7/1)
- 0 Massendurchflussmesser
- A Werkstoff Messrohr: Aluminiumlegierung
- R Rc-Gewinde
- N Luft / Stickstoff
- D01 Spannungsversorgung 24 VDC / Ausgang: 4-20 mA  
Puls- bzw. Schaltausgang (Open collector)
- 0 Keine Option
- 0 Keine Option
- 0 Ohne Inspektionszertifikat
- D mit Inspektionszertifikat (Werksprüfzeugnis)
- 0 Produkt Version

→ MCF

MAKE QUESTION ! in RS

CURRENTLY USING V<sup>1</sup> WSTA

Mass flowmeter (Application):

CMS, MQV, MPC, MVF

Technical Data:

- Process gases (Air/N<sub>2</sub>/O<sub>2</sub>/Ar/CO<sub>2</sub>/CH<sub>4</sub>/C<sub>2</sub>H<sub>6</sub>/C<sub>3</sub>H<sub>8</sub>/H<sub>2</sub>/He)
- Flow rate range (0,5/2/5/10/20/50/200/500/1000/2000L [Sl/min]):
- NI/min= 0,9318 x Sl/min =
- Accuracy (% FS):
- Humidity+particles:
- Range: 100:1
- Pressure [bar, 100 kPa]:
- Differential pressure (MQV):
- Gas-Temperature [°C]:
- Output signal (0-5V, 1-5V, 4-20mA):
- Communication (RS485 if SUS316 or H<sub>2</sub>He):
- Power supply: 24 VDC
- Pipe connection (RC 1/4, 1/2 Swt, 1/2 VCR, 9/16-18 UNF):
- Display (Intergal, Remote):
- Material (PBT resin, SUS304/316 SUS316):
- Certificates/Approvals:
- Cable length (2m, 5 m):
- Pieces:
- Target price:
- Special:

Activities:

Responsibility:

- T. Bohez
- Martin
- Ogihara