

Report Trade Show (COMVAC Ha



NOVAIR sas
OXYPLUS Technologies sas

Company: p
Name: n
Street/Straße: Fax: e-m
PO City / PLZ Stadt:

OXY-LL

6, rue Paul Langevin
Z.A. Bernard Vergnaud
93274 SEVRAN Cedex, France

Bernard Zenou
Chief Executive Officer

www.novair.fr
www.oxyplus-technologies.com

Date of visit:	<input type="checkbox"/> 20.04	<input checked="" type="checkbox"/> 21.04	<input type="checkbox"/> 22.04	<input type="checkbox"/> 23.04	<input type="checkbox"/> 24.04	Ca
Talked with:	<input type="checkbox"/> Ogihara	<input checked="" type="checkbox"/> Tom	<input type="checkbox"/> Martin			No

Tél. +33 (0) 1 43 84 94 83
Fax +33 (0) 1 43 84 87 40
E-mail bernard.zenou@novair.fr

Company Profile:
WHAT ARE THEY LOOKING FOR + VISIT CARD: short written note / applic

NITROGEN - OXYGEN APPLICATIONS

Mass flowmeter (MCF-Application):

MCFXXX0ARND0100X0 Massendurchflussmesser MCF-Series (N2, Air)

Code	Description
MCF	
008	2-200 nl/min, Pipe size 8A (1/4" Rc ISO 7/1)
015	5-500 nl/min, Pipe size 15A (1/2" Rc ISO 7/1)
025	30-3000 nl/min, Pipe size 25A (1" Rc ISO 7/1)
040	60-6000 nl/min, Pipe size 40A (1 1/2" Rc ISO 7/1)
050	120-12000 nl/min, Pipe size 50A (2" Rc ISO 7/1)
0	Massendurchflussmesser
A	Werkstoff Messrohr: Aluminiumlegierung
R	Rc-Gewinde
N	Luft / Stickstoff
D01	Spannungsversorgung 24 VDC / Ausgang: 4-20 mA
	Puls- bzw. Schaltausgang (Open collector)
0	Keine Option
0	Keine Option
0	Ohne Inspektionszertifikat
D	mit Inspektionszertifikat (Werksprüfzeugnis)
0	Produkt Version

MCF

CMG

CHS

oxygen

Nitrogen MCF - good price

Mass flowmeter (Application):

CMS, MQV, MPC, MVF

Technical Data:

- Process gases (Air/N₂/O₂/Ar/CO₂/CH₄/C₃H₈/C₄H₁₀/H₂/He):
- Flow rate range (0.5/2/5/10/20/50/200/500/1000/2000) (Sl/min):
- Sl/min = 0,9318 x Sl/min =
- Accuracy (% FS):
- Humidity+particles:
- Range: 100:1
- Pressure [bar, 100 kPa]:
- Differential pressure (MQV):
- Gas-Temperature [°C]:
- Output signal (0-5V, 1-5V, 4-20mA):
- Communication (RS485 if SUS316 or H₂/He):
- Power supply: 24 VDC
- Pipe connection (RC1/4, 1/2 Swl, 1/2 VCR, 9/16-18 UNF):
- Display (Intergal, Remote):
- Material (PBT resin, SUS304/316 SUS316):
- Certificates/Approvals:
- Cable length (2m, 5 m):
- Pieces:
- Target price:
- Special:

Activities:

Responsibility:

- F. Bohez
- Martin
- Ogihara