

Technical data	Unit Type Rating	<b>Mag. level gauge ITA-10 and ITA-10.0 PN100</b>	12.02.2007
----------------	------------------------	---	------------

**Base equipment for mag. level gauge type ITA-10 and ITA-10.0**

Principle	: Communicating tubes with magnetic float
Mounting position	: Vertical
Measuring range	: <b>Max. 5000 mm (one part)</b> > 5000 mm 2- or multipart
Pipe size	: 60,3 x 3,2 mm seamless, with studs or Butt weld construction with T-pieces
Process connections	: to specify: <b>Flanged DN15-25 (1/2 -1 600# RF)</b> <b>Welding or threaded stud</b> Flanged DN32-50 (1 1/4-2" 600# RF)
Vent/drain connections	: Plug 1/2" NPT (see code F)
Pipe material	: 316Ti Hasteloy C4 (2.4610) Inconel 625 (2.4856) Inconel 825 (2.4858) Titanium (3.7035) (Other pipe materials also available)
Flange material	: as pipe material ITA@-10.0 = Carbon steel
Float material	: Titanium, Titanium/E-CTFE coated
Operation temperature	: -50 to + 400°C
Operation pressure	: Max. 100 bar
Density	: Min. 0,4632 kg/dm <sup>3</sup> *
Bolts/Nuts	: CS SS
Gaskets:	: Spiral wound 316Ti <b>Cam profile 316Ti</b>
Indication rail	: Makrolon up to 120°C Aluminium up to 400°C 316SS up to 400°C
Float types:	: Cylindrical, sealed type Length: 270 mm <b>330 mm</b> <b>430 mm</b> <b>530 mm</b> 630 mm
Dimensions	: <b>A = 240 mm*</b> <b>B = 130 mm**</b> <b>C = 40 mm</b>

**Base Equipment printed bold!**

\* for densities < 0,4632 kg/dm<sup>3</sup> enlarge the scale A

\*\*for end cap. B=170 mm for WN.

