

Technical data	Unit Type Rating	<b>Mag. level gauge ITA-7 and ITA-7.0 PN64</b>	12.02.2007
----------------	------------------------	--	------------

### Base equipment for mag. level gauge type ITA-7 and ITA-7.0

Principle	: Communicating tubes with magnetic float
Mounting position	: Vertical
Measuring range	: <b>Max. 5000 mm (one part)</b> > 5000 mm 2- or multipart
Pipe size	: 60,3 x 2 mm seamless, Buttweld construction with T- pieces
Process connections	: to specify: <b>Flanged DN15-25 (½ -1 300# RF)</b> <b>Welding of threaded stud</b> Flanged DN50 (2" 300# RF)
Vent/drain connections	: Plugged ½" NPT (see code F)
Pipe material	: 316Ti Hasteloy C4 (2.4610) Inconel 625 (2.4856) Inconel 825 (2.4858) Titanium (3.7035) (Other pipe materials also available)
Flange material	: as pipe material ITA®-7.0 = Carbon steel
Float material	: Titanium, Titanium/E-CTFE coated
Operation temperature	: -50 to + 400°C
Operation pressure	: Max. 64 bar
Density	: 0,682 kg/dm <sup>3</sup> * <b>min. 0,4243 kg/dm<sup>3</sup></b> <b>(depending on the float type)</b>
Bolts/Nuts	: A193/A194 B7/2H A193/A194 B8/M8 CS hot dipped galvanized SS
Gaskets:	: Spiral wound, 316Ti Cam profile, 316Ti
Indication rail	: Makrolon up to 120°C Aluminium up to 400°C 316SS up to 400°C
Float types:	: Cylindrical, sealed type Length: 270 mm <b>330 mm</b> <b>530 mm</b> 630 mm
Dimensions	: <b>A = 240 mm*</b> <b>B = 130 mm</b> <b>C = 40 mm</b>

**Base Equipment printed bold!**

\* for densities < 0,682 kg/dm<sup>3</sup> enlarge the scale A

