

Transmitters for Liquid Level, Interface and Density

Intelligent Δp -Transmitter, Flange-mounted

Type: 144 FP



Technical Information

01/2010

International Headquarters:

Intra-Automation GmbH
Otto-Hahn-Str. 20
41515 Grevenbroich
GERMANY

☎ +49-(0)2181-75665-0

☎ +49-(0)2181-64492

✉ info@intra-automation.de

💻 www.intra-automation.com

Sales Office for the Benelux:

B.V. Intra-Automation HTP
PO Box 10

4731 AA Oudenbosch

THE NETHERLANDS

☎ +31-(0)165-322201

☎ +31-(0)165-322970

✉ info@intra-automation.nl

Intra-Automation GmbH
Otto-Hahn-Str. 20
41515 Grevenbroich

Technical Information 144FP
Rev. 0
01/2010
Subject to technical alteration.

Description

Intelligent transmitters type 144FP are designed to perform measurements for liquid level, interface or density of liquids. The measurement is based on the hydrostatic pressure principle. Easy remote configuration and supervision with PC or Universal Handterminal. The devices can also be operated conventionally using the local keys. Digital communication facilities complete operation and configuration via PC or control system. The transmitters are approved for use in hazardous areas.

Features

◆	Communication HART, FoxCom, PROFIBUS PA or FOUNDATION Fieldbus
◆	Conventional operation with local keys
◆	Easy adaptation to the measuring point without calibration at the workshop.
◆	Backdocumentation of measuring point
◆	Continuous self-diagnostics
◆	Configurable safety value
◆	Software lock for local keys and reconfiguration
◆	Simulation of analogue output for loop-check
◆	Local display in %, mA or physical units
◆	Signal noise suppression by Smart Smoothing
◆	Linear or customized characteristic
◆	Process temperature from -50 °C to +120 °C
◆	Materials for use with aggressive media
◆	Mieco sintermetal sensor technology

Technical Data

Output:

HART and FoxCom analogue mode:

Lower range value	continuously adjustable within the measuring limits
Turn down	1:1...1:50
Signal range	4...20 mA / 20...4 mA
Operating range	3,8...20 mA
Admissible load	$R_{Bmax} = \frac{U_s - 12V}{0,023A}$ (U _s = supply voltage)
Accuracy	±0,1 %
Transfer function	linear

FoxCom digital mode:

Output current const.	ca. 12 mA
-----------------------	-----------

Communication HART

Connection	Two wire system
Supply voltage U _s	12...42 V DC, V _{ss} < 1 %
Current sink	max. 23 mA
Analogue output	4...20 mA
Operating range	3,8...21 mA
Digital Communication	HART-Protocol, 1200 Baud

Communication PROFIBUS PA / Foundation Fieldbus

Connection	Twisted and shielded two wire cable acc. to recommendation based on IEC 1158-2
Supply voltage U_S	9...32 V DC, $V_{SS} < 1\%$
Current sink	10,5 mA $\pm$ 0,5 mA (base current)
Digital communication	PROFIBUS PA Protocol acc. class B profile, EN 50170 and DIN 19245 part 4
Signal amplitude	± 8 mA
Fault current	< 13 mA
Operating values	acc. IEC 1158-2
Bus connection	Fieldbus-Interface acc. IEC 1158-2

Operating Conditions

Process temperature	-50 °C...+120 °C
Pressure rating	
- acc. DIN	PN16, 40, 63, 100, 160, 250
- acc. ANSI	Class 150, 300, 600, 900, 1500
Ambient temperature	
- without indicator	-40 °C...+85 °C
- with indicator	-40 °C...+70 °C
Relative humidity	up to 100 %
Condensation	Permitted
Transportation- / storage temp.	-50 °C...+85 °C
Protection class	IP66 (acc. DIN 40 050)

Measuring ranges, Overload limit

Span Code	Measuring span		Measuring limits	Overload limit
	min.	max.		
-A	3,2 mbar 1,28 in H ₂ O	64 mbar 25,7 in H ₂ O	-64...64 mbar 25,7...25,7 in H ₂ O	max. pressure rating flange PN16/40 Cl. 150/300
-B	32 mbar 12,8 in H ₂ O	640 mbar 258 in H ₂ O	-640...640 mbar -258...258 in H ₂ O	
-C	200 mbar 80,3 H ₂ O	4000 mbar 1606 in H ₂ O	-4000...4000 mbar -1606...1606 in H ₂ O	

Ordering informationen

Model code

Code	Description																																	
144FP	Intelligent Δp Transmitter for level, density and interface measurement, flange mounted																																	
Span Limits																																		
	<table><tr><th></th><th>mbar</th><th>inH2O</th><th>kPa</th></tr><tr><td>A</td><td>3,2 & 64</td><td>1,28 & 25,7</td><td>0,35 & 6,4</td></tr><tr><td>B</td><td>32 & 640</td><td>12,8 & 257</td><td>3,2 & 64</td></tr><tr><td>C</td><td>200 & 4000</td><td>80,3 & 1606</td><td>20 & 400</td></tr></table>		mbar	inH2O	kPa	A	3,2 & 64	1,28 & 25,7	0,35 & 6,4	B	32 & 640	12,8 & 257	3,2 & 64	C	200 & 4000	80,3 & 1606	20 & 400																	
	mbar	inH2O	kPa																															
A	3,2 & 64	1,28 & 25,7	0,35 & 6,4																															
B	32 & 640	12,8 & 257	3,2 & 64																															
C	200 & 4000	80,3 & 1606	20 & 400																															
Flange size and pressure rating																																		
	<table><tr><th></th><th>Flange size</th><th>Pressure rating</th></tr><tr><td>10</td><td>DN 50</td><td>PN 16/40</td></tr><tr><td>11</td><td>DN 80</td><td>PN 16/40</td></tr><tr><td>12</td><td>DN 100</td><td>PN 16</td></tr><tr><td>13</td><td>DN 100</td><td>PN 40</td></tr><tr><td>21</td><td>2"</td><td>ANSI Class 150</td></tr><tr><td>22</td><td>2"</td><td>ANSI Class 300</td></tr><tr><td>31</td><td>3"</td><td>ANSI Class 150</td></tr><tr><td>32</td><td>3"</td><td>ANSI Class 300</td></tr><tr><td>41</td><td>4"</td><td>ANSI Class 150</td></tr><tr><td>42</td><td>4"</td><td>ANSI Class 300</td></tr></table>		Flange size	Pressure rating	10	DN 50	PN 16/40	11	DN 80	PN 16/40	12	DN 100	PN 16	13	DN 100	PN 40	21	2"	ANSI Class 150	22	2"	ANSI Class 300	31	3"	ANSI Class 150	32	3"	ANSI Class 300	41	4"	ANSI Class 150	42	4"	ANSI Class 300
	Flange size	Pressure rating																																
10	DN 50	PN 16/40																																
11	DN 80	PN 16/40																																
12	DN 100	PN 16																																
13	DN 100	PN 40																																
21	2"	ANSI Class 150																																
22	2"	ANSI Class 300																																
31	3"	ANSI Class 150																																
32	3"	ANSI Class 300																																
41	4"	ANSI Class 150																																
42	4"	ANSI Class 300																																
Flangecontact face																																		
C	Form C DIN2526 (Rz=40-160 μ m) [with 10-13]																																	
R	Form RF Raised Face ANSI B16.5 [with 21-42]																																	
Diaphragm extension length																																		
0	no extension																																	
Flange face materials (process wetted)																																		
S	1.4571 / 1.4404 (316)																																	
Diaphragm material																																		
S	1.4435 / 1.4404 (316L)																																	
C	Hastelloy C																																	
Sensor O-Ring Maerial and temperature limits																																		
	<table><tr><th></th><th>Material</th><th>Temperature limits</th></tr><tr><td>V</td><td>FPM / FKM (Viton)</td><td>-20...+120 °C / -4...+248 °F</td></tr><tr><td>P</td><td>PTFE</td><td>-40...+120 °C / -40...+248 °F</td></tr><tr><td>E</td><td>EPDM</td><td>-40...+120 °C / -40...+248 °F</td></tr></table>		Material	Temperature limits	V	FPM / FKM (Viton)	-20...+120 °C / -4...+248 °F	P	PTFE	-40...+120 °C / -40...+248 °F	E	EPDM	-40...+120 °C / -40...+248 °F																					
	Material	Temperature limits																																
V	FPM / FKM (Viton)	-20...+120 °C / -4...+248 °F																																
P	PTFE	-40...+120 °C / -40...+248 °F																																
E	EPDM	-40...+120 °C / -40...+248 °F																																
Sensor filling fluid																																		
1	Silicone oil																																	
2	Inerte fluid																																	
Electrical Classification																																		
EA4	CENELEC EEx ia IIC T4																																	
EDZ	CENELEC EEx d IIB																																	
0B4	Zone 0 – IIB T4 (HART)																																	
0C4	Zone 0 – IIC T4 (HART)																																	
0B6	Zone 0 – IIB T6 (PROFIBUS / FOUNDATION Fieldbus)																																	
0C6	Zone 0 – IIC T6 (PROFIBUS / FOUNDATION Fieldbus)																																	
1C4	Zone 1 – IIC T4 (HART)																																	
1B6	Zone 1 – IIB T6 (HART)																																	
1C6	Zone 1 – IIC T6 (PROFIBUS / FOUNDATION Fieldbus)																																	
2C4	Zone 2 – IIC T4 (HART) (d)																																	
2C6	Zone 2 – IIC T6 (PROFIBUS / FOUNDATION Fieldbus) (d)																																	
D1B	ATEX explosion proof – Zone 1 – IIB T6																																	
D1C	ATEX explosion proof – Zone 1 – IIC T6																																	
NSP	Ex N IIC BS 6941																																	
NFM	FM Nonincendive																																	
FDZ	FM Explosion proof																																	
CDZ	CSA Explosion proof (c)																																	
FAA	FM Intrinsically safe																																	
CAA	CSA Intrinsically safe																																	
GAA	RUSSIAN Intrinsically safe (c)																																	
ZZZ	without																																	
Amplifier housing																																		
P	Aluminium with operating buttons and external push buttons																																	
Cable entry																																		
M	M20 x 1,5 without cable gland																																	
N	½-14 NPT without cable gland																																	
Communication																																		
H	HART																																	
F	FoxCom analogue (4-20 mA)																																	
P	PROFIBUS PA																																	
B	FOUNDATION Fieldbus																																	

Options	
A	LCD indicator (required for amplifier housing P)
O	Cleande for Oxygen Service (nto with filling fluid 1)
T	Customized configuration
R	Remote amplifier mounting kit (3 m), mounted (c)
B	Remote amplifier mounting kit (10 m), mounted (c)
TAG no. Labelling	
S	Stamped with weather resistant colour
L	Stainless steel label fixed with wire
F	Stainless steel label fixed on amplifier
National certificates	
E	Zone 0, IIA, IIB
V	Overfill protection acc. WHG (c)
X	Dust-ignition proof per Zone 10 (with electr. Classification EA4)
G	GOST Metrologic Certificate (c)
Zertifikate	
1	EN 10204-2.1 (DIN 50 049-2.1) Certificate of Compliance
2	EN 10204-2.3 (DIN 50 049-2.3) Specific Test Report (Calibration)
3	EN 10204-3.1.B (DIN 50 049-3.1.B) Inspection certificate of process wetted material
6	Comply with NACE Standard MR-01-75 (with diaphragm material Hstelloy C only for ECEPSE006T)
(b)) not with electr. classification EDZ, FDZ, CDZ, D1B, D1C	
(c) not available	
(d) pending	
(f) VbF included in Zone 0	

Besides the products covered by this brochure, Intra-Automation GmbH also manufactures other high-quality and high precision instruments for industrial measurement tasks. For more information, please contact us (contact details on the backside of this brochure).

Flow measurement



Itabar®-Flow Sensor



IntraSonic IS210 Ultrasonic Flow Meter

Level measurement



ITA-mag. Level Gauge



MAGLINK Level Indicator

Other Measurement Tasks:



DigiFlow Flow and Level Computers



IntraCon Digital Controllers



IntraDigit Digital Indicators / Meters

**INTRA-AUTOMATION**

MESS- UND REGELINSTRUMENTE / MEASUREMENT AND CONTROL

**TÜVRheinland®**
CERT
ISO 9001**International Headquarters:**

Intra-Automation GmbH
Otto-Hahn-Str. 20
41515 Grevenbroich
GERMANY

☎ +49 – (0) 21 81 / 7 56 65-0

☎ +49 – (0) 21 81 / 6 44 92

✉ info@intra-automation.de

💻 www.intra-automation.com

Sales Office for the BENELUX:

B.V. Intra-Automation HTP
PO Box 10
4731 AA Oudenbosch
THE NETHERLANDS

☎ +31 – (0)165 – 32 22 01

☎ +31 – (0)165 – 32 29 70

✉ info@intra-automation.nl