

Price List New Products 2010



Description		Article No.						Price €
Basic Sensor	Schmidt Flow Sensor SS 20.261; Output signal 4..20mA; overpressure up to 8 bar and press fitting; cable 1,5m	526 335 -	X	Y	Z			629,00
Optionen:								Price €
Sensor length	Sensor length 200 mm		1					0,00
	Sensor length 350 mm		2					0,00
Measuring range and calibration	Measuring range 0..40m/s			1				0,00
	Measuring range 0..60m/s			2				0,00
	Measuring range 0..90m/s			3				68,00
	Standard adjustment					1		0,00
	High precision adjustment including ISO calibration certificate for flow						2	195,00
Description		Article No.						Price €
Accessories	Welding sleeve steel G1/2", according to EN 10241, 5 pieces	524 916						31,00
	LED-Display in wall-mounted housing for volume flow and flow velocity	527 320						385,00
	LED-Display in wall-mounted housing, as 527 320, but with additional totalizer and 2.nd measuring input	527 330						430,00
A	Ball valve							on request



Description		Article No.							Price €
Basic Sensor	Schmidt Flow Sensor 20.250; Output signal 4..20mA and 0..10V;	526 340 -	X	Y	Z	P	A	340,00	
Options:									
Mechanical Version	Sensor length 300 mm		1					0,00	
	Sensor length 500 mm		2					0,00	
Measuring range and calibration	Measuring range 0...1 m/s			1				0,00	
	Measuring range 0...10 m/s			2				0,00	
	Measuring range 0...20 m/s			3				0,00	
	Standard adjustment					1		0,00	
	High precision adjustment including ISO calibration certificate for flow						2	195,00	
Protection design	Without protective coating					1		0,00	
	Protective coating					2		80,00	
Connecting cable	Cable length 1,5 m						1	0,00	
	Special cable length: _____mm						2	on request	
Description		Article No.							Price €
Accessories	Mounting flange steel, galvanic zinc-plated	301 048							37,00
	Wall-mounting flange, stainless steel, PTFE-clamping ring	520 181							143,00
	Press fitting, stainless steel, G 1/2, atmospheric pressure	301 082							61,00
	Press fitting, brass, G 1/2, atmospheric pressure	517 206							30,00
	Welded sleeve steel G 1/2, EN 10241, 5 pcs	524 916							31,00
	Welded sleeve stainless steel G 1/2, EN10241, 2 pcs	524 882							23,00
	LED-Display in wall-mounted housing for volume flow and flow velocity	527 320							385,00
	LED-Display in wall-mounted housing, as 527 320, but with additional totalizer and 2.nd measuring input	527 330							430,00
A									

